

Propositions-as-Types and Shared State

Pedro Rocha and Luís Caires

NOVA LINCS Tech Report 10/2021

NOVA Laboratory for Computer Science and Informatics
NOVA University of Lisbon, Portugal
June, 2021



Abstract

We develop a principled integration of shared mutable state into a proposition-as-types linear logic interpretation of a session-based concurrent programming language. While the foundation of type systems for the functional core of programming languages often builds on the proposition-as-types correspondence, automatically ensuring strong safety and liveness properties, imperative features have mostly been handled by extra-logical constructions. Our system crucially builds on the integration of nondeterminism and sharing, inspired by logical rules of differential linear logic, and ensures session fidelity, progress, confluence and normalisation, while being able to handle first-class shareable reference cells storing any persistent object. We also show how preservation and, perhaps surprisingly, progress, resiliently survive in a natural extension of our language with first-class locks. We illustrate the expressiveness of our language with examples highlighting detailed features, up to simple shareable concurrent ADTs.

1 INTRODUCTION

In this paper we introduce a propositions-as-types (PaT) approach to mutable state, defined as a conservative extension of the classical linear logic interpretation for session-typed processes [Caires et al. 2016; Wadler 2012] with first-class shareable reference cells. Modern software construction depends on imperative state, state sharing, and concurrency, with even mainstream functional programming languages such as ML variants or Haskell offering explicit typed support for mutable state. Still, safely programming with state, aliasing and concurrency (and reasoning about the combination) has always been considered a significant challenge, with the study of programming abstractions, logics and type systems for disciplining interference being a prolific research topic for decades [Ahmed et al. 2007; Caires and Seco 2013; Jung et al. 2018a; Nanevski et al. 2008; O’Hearn and Reynolds 2000; Sunshine et al. 2011].

While the design of type systems for the functional core of programming languages (e.g., the polymorphic lambda calculus) conveniently connects to the PaT correspondence [Cardelli 1991; Howard 1980; Wadler 2015]), which intrinsically ensures strong safety and liveness properties, the notion of mutable state seems to escape from the paradigm, notwithstanding the long identified deep connections between linear logic and stateful computation [Wadler 1990a], and recent advances such as [Balzer and Pfenning 2017]. Imperative state is then usually expressed by diverging from logical principles; a consequence is that many important properties offered “for free” by PaT, such as type preservation, progress / deadlock freedom, equational reasoning on program behaviour via proof equivalence, or (strong) normalisation, do not automatically result from the basic typing discipline, and need in general additional extra-logical techniques to be achieved.

We thus believe that computational models for mutable state subscribing to the full ideology of PaT (proofs as programs, formulas as types, evaluation as proof simplification) are still lacking.

A main challenge is that while in PaT computation corresponds to proof reduction, that is, the observable behaviour of a program term does not change under cut reduction / elimination, and the normal form summarises the program / proof denotation, the execution of programs with shared state and concurrency typically induces non-deterministic behaviour, e.g. as in concurrent writes to the same memory cell. Non-determinism in computations is often mentioned as an obstacle for PaT, since it may lead to loss of confluence in a (candidate) notion of proof simplification. Moreover, the existence of proof normal forms may be also compromised in the presence of shared state, since non-termination may be expressed with a higher-order store (e.g., Landin’s knot).

In the seminal PaT correspondences between session processes and linear logic [Caires and Pfenning 2010; Wadler 2012], there is no “real” non-determinism. Programs exhibit parallelism and

a degree of concurrency, in the sense that many sessions may run simultaneously and independently, but the computation is nevertheless confluent. The key reason is that no races occur in communications within a linear session or even between different linear sessions. Also, processes may concurrently invoke the same replicated server, however, the typing discipline induced by the promotion rule for $!A$ ensures that the server behaviour is identical for each invocation (cf. uniform receptiveness of shared names [Sangiorgi 1999]). In such a setting, the overall computation remains essentially “functional” [Toninho and Yoshida 2021], which is not surprising given the well known interpretations of linear logic as linear lambda calculi.

The question then arises about whether and how mutable shared state might be faithfully expressed in a PaT model. In this work we approach the issue by exploring the Curry-Howard correspondence from a programming language perspective, building on a conservative extension of standard classical linear logic. As suggested by Cardelli [Cardelli 1991], “one can extrapolate [the] correspondence and turn it into a predictive tool: if a concept is present in type theory but absent in programming, or vice-versa, it can be very fruitful to both areas to investigate and see what the corresponding concept might be in the other context”.

Our system fully complies with the PaT ideology (proofs as programs, formulas as types, evaluation as proof simplification). Its core ingredients are: (a) the introduction of two dual “exponential” modalities and the interpretation of their proof rules as language constructs for manipulating reference cells and (b) a principled integration of the well-known interplay between concurrency and non-determinism in algebraic concurrency theory [Hennessy and Milner 1985] now emerging from our proof theoretic analysis. Our typing rules for the imperative fragment are inspired by those for the exponentials and sum connectives of differential linear logic (DiLL) [Ehrhard 2018; Ehrhard and Regnier 2006], allowing us to internalise non-determinism equationally (an idea also explored by Beffara in the context of process algebra [Beffara 2008]), thus allowing us to capture concurrent interactions on shared state equationally, by cut-reduction / proof simplification.

Propositions-as-types pays back: programs in our basic language naturally enjoy type preservation, progress, confluence and normalisation. We also show how the key properties of our system, including progress / deadlock freedom, resiliently survive to a principled extension of our language with first-class locks. The intrinsic modularity of the PaT approach naturally ensures its compatibility with all constructs in related work that as well follows PaT, including parametric polymorphism [Caires et al. 2013; Wadler 2012], dependent types [Toninho et al. 2011], code mobility [Toninho et al. 2013], or multiparty protocols [Caires and Pérez 2016; Carbone et al. 2016]. As an example, we illustrate how the inclusion of second-order quantifiers [Caires et al. 2013; Wadler 2012] allows us to elegantly express concurrent and shareable stateful ADTs within our basic PaT framework.

1.1 Overview

We provide a high-level overview of π SS, which is a session-typed π -calculus with shared state, anticipating the technical presentation of the next sections. Our basic session discipline (see [Honda 1993; Honda et al. 1998]) applies to concurrent processes which communicate through private channels connecting two partners and is related to Linear Logic (LL) via a Curry-Howard correspondence: types correspond to propositions and are assigned to session channels, processes to proofs, and process congruence/reduction to proof simplification. In fact, π SS is a conservative extension of the fundamental session-based interpretations of LL [Caires and Pfenning 2010; Wadler 2012].

Within a linear session two parties communicating on each endpoint of the session channel comply with a certain protocol, characterised by a session type. Duality on types, (A/\bar{A}) where A and \bar{A} are dual types, corresponds to linear logic negation and captures symmetry in interaction: when one process closes, the other waits for the session to be closed ($1/\perp$); when one sends, the

other receives $(A \otimes B/\overline{A} \wp \overline{B})$; when one offers a menu, the other chooses an option from the menu $(A \& B/\overline{A} \oplus \overline{B})$, and so on. The exponentials $(!A/?\overline{A})$ type replicated servers and their invocation by clients. Composition of two processes P, Q interacting on a session x of type A is represented by the cut rule, written $P \mid x : A \mid Q$, where P uses channel x at type A and process Q uses x at type \overline{A} . Let us start by considering the following simple session process.

$$\text{menu } m \triangleq \text{case } m \{ \mid \text{inl} : \text{recv } m(b); \text{send } m(b'.\text{not } b b'); \text{close } m \\ \mid \text{inr} : \text{recv } m(b_1); \text{recv } m(b_2); \text{send } m(b'.\text{and } b_1 b_2 b'); \text{close } m \}$$

Process menu m offers a menu with two choices: inl or inr. In case the choice is inl, it receives a boolean b , computes the negation of b (to b') and sends back the result b' . In case the choice is inr, it receives two booleans b_1 and b_2 , computes their conjunction (to b') and sends back the result b' . Both branches finalize the session m by closing it, no further interactions will take place. Process menu m offers on m a protocol of type $\text{Menu} \triangleq (\overline{\text{Bool}} \wp (\text{Bool} \otimes \mathbf{1})) \& (\overline{\text{Bool}} \wp (\overline{\text{Bool}} \wp (\text{Bool} \otimes \mathbf{1})))$. Process client m is a client of menu m , providing at m the dual type $\overline{\text{Menu}}$

$$\text{client } m \triangleq m.\text{inr}; \text{send } m(b_1.\text{true } b_1); \text{send } m(b_2.\text{false } b_2); \text{recv } m(b'); \text{wait } m; \text{print } b'$$

It chooses the option inr (conjunction), sends two linear booleans, receives a result b' on m , waits for the session to be closed and then prints b' . Since menu m and client m have dual types on session m they can be composed with a cut

$$\text{system}_0 \triangleq \text{menu } m \mid m : \text{Menu} \mid \text{client } m$$

Execution of system_0 will eventually result in the boolean value false to be printed out. Process menu m executes and terminates after interacting with the client. Then, one may define a replicated server on name s , by server $s \triangleq !s(m); \text{menu } m$. It is typed by $!\text{Menu}$ and persistently offers the boolean menu, spawning a linear session on a fresh m (of type Menu) on each invocation.

Our basic πCLL language corresponds exactly to second-order Classical Linear Logic with mix. The main novelty in this paper results from the addition of two duality-related modalities to type mutable state: $\boxtimes A$ (read *box why not*) which type reference cells, and $\boxplus \overline{A}$ (read *box bang*) which type cell usage, and which are governed by logical principles that take inspiration in DiLL [Ehrhard 2018]. The associated basic constructs are processes (proofs) that represent first class reference cells storing persistent values, and cell usage operations read, write and free. For example, consider

$$\text{system}_1 \triangleq \text{cell } c(b.\text{true } b) \mid c : \boxtimes \text{Bool} \mid \text{read } c(b'.\text{false } b'); \text{free } c; P(b_r)$$

In system_1 a reference cell at c , initialised with the persistent boolean value true and typed by $c : \boxtimes \text{Bool}$, is composed (by cut) with a process that uses c at type $\boxplus \overline{\text{Bool}}$. It first reads the cell, then writes the boolean false, frees the usage, and continues as process $P(b)$. Reference cells and usages are handled linearly, therefore cannot be implicitly discarded nor copied. Releasing a cell usage is expressed by the free operation (which corresponds to co-weakening). In example system_1 , after the cell usage is released, cell deallocation occurs since there is no other usage of it; notice that c does not occur in $P(b)$, as enforced by typing of free. Now, the dynamic semantics of our language is defined from a structural congruence (\equiv) and reduction (\rightarrow) relations (Definitions 6.3, 6.4), where reduction is closed under structural congruence; and we have the reductions

$$\begin{aligned} \text{system}_1 &\rightarrow \text{true } b_r \mid b_r : !\text{Bool} \mid (\text{cell } c(b.\text{true } b) \mid c : \boxtimes \text{Bool} \mid \text{wrt } c(b'.\text{false } b'); \text{free } c; P(b_r)) \\ &\rightarrow \text{true } b_r \mid b_r : !\text{Bool} \mid (\text{cell } c(b'.\text{false } b') \mid c : \boxtimes \text{Bool} \mid \text{free } c; P(b_r)) \\ &\rightarrow \text{true } b_r \mid b_r : !\text{Bool} \mid P(b_r) \end{aligned}$$

We now turn to sharing: our language supports sharing of cell usages via the share c operation which corresponds to duplication of a cell usage c (typing rule for share corresponds to

co-contraction). Consider the example

$$\text{system}_2 \triangleq \text{cell } c(b.\text{true } b) \mid c : \boxtimes \text{Bool} \mid \text{share } c \{ \text{wrt } c(b_1.\text{true } b_1); P_1 \parallel \text{wrt } c(b_2.\text{false } b_2); P_2 \}$$

system_2 illustrates two concurrent threads sharing a memory cell: one thread writes the boolean true and continues as P_1 , whereas the other thread writes false and continues as P_2 .

We look in detail how system_2 executes. First, system_2 is expanded into a sum ($P + Q$) in which the two concurrent write operations are interleaved and brought to evidence, using the fundamental structural conversion law \equiv [AA] which relates concurrency with nondeterminism. This yields

$$\text{system}_2 \equiv \text{cell } c(b.\text{true } b) \mid c : \boxtimes \text{Bool} \mid (\text{wrt } c(b_1.\text{true } b_1); \text{wrt } c(b_2.\text{false } b_2); \text{share } c \{P_1 \parallel P_2\} + \text{wrt } c(b_1.\text{false } b_1); \text{wrt } c(b_2.\text{true } b_2); \text{share } c \{P_1 \parallel P_2\})$$

A process of the form $P + Q$ represents a non-deterministic choice between alternatives P and Q , each offering the same interface and typing, cf. sum in process algebra. Sums are also present in DiLL [Ehrhard 2018] where cut elimination need to generate sums of proofs. In our model, sum satisfy the expected axioms of nondeterministic sums of process algebras [Hennessy and Milner 1985], like commutativity, associativity and idempotency, remarkably modelled as logical proof conversions. Now, further laws of \equiv allows cut to be distributed over sum, so that

$$\text{system}_2 \equiv (\text{cell } c(b.\text{true } b) \mid c : \boxtimes \text{Bool} \mid \text{wrt } c(b_1.\text{true } b_1); \text{wrt } c(b_2.\text{false } b_2); \text{share } c \{P_1 \parallel P_2\}) + (\text{cell } c(b.\text{true } b) \mid c : \boxtimes \text{Bool} \mid \text{wrt } c(b_2.\text{false } b_2); \text{wrt } c(b_1.\text{true } b_1); \text{share } c \{P_1 \parallel P_2\})$$

Using reduction on each summand to execute the write operations, last writer wins, and we obtain

$$\text{system}_2 \xrightarrow{*} (\text{cell } c(b_2.\text{false } b_2) + \text{cell } c(b_1.\text{true } b_1)) \mid c : \boxtimes \text{Bool} \mid \text{share } c \{P_1 \parallel P_2\}$$

Notice how sums internalise nondeterminism in processes / proof terms, allowing us to define confluent proof simplification. In this example, all possible reduction sequences from system_2 reach a unique process up to structural congruence after performing the four write operations.

As mentioned above, at some point in computation, all cell clients must release their (shared) cell usages. It is interesting to give an intuitive understanding about how our semantics handles release of shared cell usages, that lazily leads to ultimate cell deallocation when no usage remains active; when this happens cells get “deallocated”. For example, consider the process

$$\text{system}_3 \triangleq \text{cell } c(b.\text{true } b) \mid c : \boxtimes \text{Bool} \mid \text{share } c \{ \text{wrt } c(b'.\text{false } b'); \text{free } c; P \parallel \text{free } c; Q \}$$

In this case, when a read or write operation competes with a free operation, the free operation gets postponed, this is captured by a structural conversion \equiv law [FA].

$$\text{system}_3 \equiv \text{cell } c(b.\text{true } b) \mid c : \boxtimes \text{Bool} \mid \text{wrt } c(b'.\text{false } b'); \text{share } c \{ \text{free } c; P \parallel \text{free } c; Q \} \rightarrow \text{cell } c(b'.\text{false } b') \mid c : \boxtimes \text{Bool} \mid \text{share } c \{ \text{free } c; P \parallel \text{free } c; Q \}$$

Then, by \equiv law [FF], the two shared free operations are collapsed into a single one that is then propagated up in the sharing tree. All free operations executed by threads sharing c eventually collapse into a *single* free operation, which then causes the cell to be erased.

$$\begin{aligned} & \text{cell } c(b'.\text{false } b') \mid c : \boxtimes \text{Bool} \mid \text{share } c \{ \text{free } c; P \parallel \text{free } c; Q \} \\ & \equiv \text{cell } c(b'.\text{false } b') \mid c : \boxtimes \text{Bool} \mid \text{free } c; (P \parallel Q) \rightarrow P \parallel Q \end{aligned}$$

In this example, after freeing up c , the thread continuations P and Q will continue running in parallel (via mix) but of course they are no longer accessing the cell.

1.2 Contributions and Structure of the Paper

In Section 2 we review the polymorphic session-typed calculus πCLL , which exactly corresponds to second-order Classical Linear Logic with mix. In Section 3 we introduce our process model and type system πSS , which extends πCLL with shared state, sums, and two novel dual modalities inspired by principles of differential linear logic. Considerations about the structure of proof reductions motivate a simple extension πSSL of our basic system πSS with locking primitives, which we present in Section 4. These languages are conservative extensions of classical linear logic according to $\pi\text{CLL} \subset \pi\text{SS} \subset \pi\text{SSL}$. In Section 5 we showcase the expressiveness of our language πSSL by implementing a mutable shareable stack and queue objects. This also illustrates how the presence of standard existential and universal type quantifiers [Cardelli and Wegner 1985; Mitchell and Plotkin 1988] harmoniously combine with the basic stateful framework of πSSL , allowing us to express mutable ADTs. Throughout the paper several other examples are provided. In Section 6 we formalise the reduction semantics of πSSL and prove that, as a consequence of the proof-theoretic approach, the language enjoys type preservation (Theorem 6.6) and deadlock-freedom (Theorem 6.14). In the following Sections, we prove key meta-theoretic properties of our system. In Section 7 we establish that our system πSSL , internalising non-determinism with sum processes, enjoys confluence (Theorem 7.8), thus proof reductions and conversions represent proof identities or behavioural equivalences. As a consequence, we also reveal a new connection between logic interpretations of programming languages, concurrency and non-determinism. In Section 8 we study proof normalisation / cut-elimination (Theorem 8.4) for the sub-calculus of πSS without quantifiers. A consequence of the sub-formula property of cut-free proofs (Proposition 8.3) is that any system that implements standard linear logic based session types (even if it manipulates state) normalises to a (non-deterministic) cut-free process that does not manipulate state (Corollary 8.5). In Section 9 we give a brief description of our prototype type checker and interpreter, which was submitted as an artifact for evaluation [Rocha and Caires 2021], as companion to this paper. Finally, in Section 10 we discuss related work, Section 11 offers closing remarks and discusses future work. Complete definitions and detailed proofs are in the supplementary material.

2 THE BASIC LANGUAGE πCLL

Our starting point is the typed language πCLL for session-based interacting processes, akin to the session π -calculus, related to classical linear logic (with mix) via a Curry-Howard correspondence [Caires et al. 2013; Caires and Pfenning 2010; Caires et al. 2016; Wadler 2012]: (session) types correspond to propositions (and types are assigned to session channels), processes correspond to proofs, and process congruence/reduction corresponds to proof simplification.

Typing Judgements. Typing judgments are of the form

$$P \vdash \underbrace{x_1 : A_1, \dots, x_n : A_n}_{\Delta}; \underbrace{y_1 : B_1, \dots, y_m : B_m}_{\Gamma}$$

and mean that a process P , seen as a black box, offers a set of channel endpoints $x_1, \dots, x_n, y_1, \dots, y_m$ that follow a protocol specified by their respective types $A_1, \dots, A_n, B_1, \dots, B_m$. Later, we will see how to connect two channel endpoints x and y that have dual protocols $x : A$ and $y : \bar{A}$.

Since we are interpreting a dyadic formulation of CLL, typing contexts are separated (with a semi-colon) into two parts: a linear part denoted by Δ and an unrestricted (or exponential) part denoted by Γ . Δ is linearly handled, which means that we cannot copy nor discard channels, whereas Γ allows weakening and contraction. This dyadic formulation was introduced in [Andreoli 1992] and adopted in the session-based interpretations of [Caires and Pfenning 2010; Caires et al. 2016].

$$\begin{array}{c}
\frac{}{\mathbf{0} \vdash \emptyset; \Gamma} \text{[T0]} \quad \frac{P \vdash \Delta'; \Gamma \quad Q \vdash \Delta; \Gamma}{P \parallel Q \vdash \Delta', \Delta; \Gamma} \text{[Tpar]} \\
\\
\frac{}{\text{fwd } x \ y \vdash x : \bar{A}, y : A; \Gamma} \text{[Tfwd]} \quad \frac{P \vdash \Delta', x : A; \Gamma \quad Q \vdash \Delta, x : \bar{A}; \Gamma}{P \ |x : A| \ Q \vdash \Delta', \Delta; \Gamma} \text{[Tcut]} \\
\\
\frac{}{\text{close } x \vdash x : \mathbf{1}; \Gamma} \text{[T1]} \quad \frac{Q \vdash \Delta; \Gamma}{\text{wait } x; Q \vdash \Delta, x : \perp; \Gamma} \text{[T}\perp\text{]} \\
\\
\frac{P_1 \vdash \Delta, x : A; \Gamma \quad P_2 \vdash \Delta, x : B; \Gamma}{\text{case } x \ \{ | \text{inl} : P_1 \ | \ \text{inr} : P_2 \} \vdash \Delta, x : A \ \& \ B; \Gamma} \text{[T}\&\text{]} \\
\\
\frac{Q_1 \vdash \Delta', x : \bar{A}; \Gamma}{x.\text{inl}; Q_1 \vdash \Delta', x : \bar{A} \oplus \bar{B}; \Gamma} \text{[T}\oplus_l\text{]} \quad \frac{Q_2 \vdash \Delta', x : \bar{B}; \Gamma}{x.\text{inr}; Q_2 \vdash \Delta', x : \bar{A} \oplus \bar{B}; \Gamma} \text{[T}\oplus_r\text{]} \\
\\
\frac{P_1 \vdash \Delta_1, y : A; \Gamma \quad P_2 \vdash \Delta_2, x : B; \Gamma}{\text{send } x(y.P_1); P_2 \vdash \Delta_1, \Delta_2, x : A \otimes B; \Gamma} \text{[T}\otimes\text{]} \quad \frac{Q \vdash \Delta, z : \bar{A}, x : \bar{B}; \Gamma}{\text{recv } x(z); Q \vdash \Delta, x : \bar{A} \wp \bar{B}; \Gamma} \text{[T}\wp\text{]} \\
\\
\frac{P \vdash y : A; \Gamma}{!x(y); P \vdash x : !A; \Gamma} \text{[T!]} \quad \frac{Q \vdash \Delta; \Gamma, x : \bar{A}}{?x; Q \vdash \Delta, x : ?\bar{A}; \Gamma} \text{[T?]} \\
\\
\frac{P \vdash y : A; \Gamma \quad Q \vdash \Delta; \Gamma, x : \bar{A}}{y.P \ |x : A| \ Q \vdash \Delta; \Gamma} \text{[Tcut!]} \quad \frac{Q \vdash \Delta, z : \bar{A}; \Gamma, x : \bar{A}}{\text{call } x(z); Q \vdash \Delta; \Gamma, x : \bar{A}} \text{[Tcall]} \\
\\
\frac{P \vdash \Delta, x : \{B/X\}A; \Gamma}{\text{send } x \ B; P \vdash \Delta, x : \exists X.A; \Gamma} \text{[T}\exists\text{]} \quad \frac{Q \vdash \Delta, x : \bar{A}; \Gamma}{\text{recv } x(X); Q \vdash \Delta, x : \forall X.\bar{A}; \Gamma} \text{[T}\forall\text{]} \\
\\
\frac{P \vdash y : !A; \Gamma}{\text{cell } x(y.P) \vdash x : \boxplus A; \Gamma} \text{[Tcell]} \quad \frac{Q \vdash \Delta; \Gamma}{\text{free } x; Q \vdash \Delta, x : \boxminus \bar{A}; \Gamma} \text{[Tfree]} \\
\\
\frac{Q \vdash \Delta, z : ?\bar{A}, x : \boxplus \bar{A}; \Gamma}{\text{read } x(z); Q \vdash \Delta, x : \boxplus \bar{A}; \Gamma} \text{[Tread]} \quad \frac{Q_1 \vdash z : !A; \Gamma \quad Q_2 \vdash \Delta, x : \boxminus \bar{A}; \Gamma}{\text{wrt } x(z.Q_1); Q_2 \vdash \Delta, x : \boxminus \bar{A}; \Gamma} \text{[Twrite]} \\
\\
\frac{P \vdash \Delta', x : \boxplus \bar{A}; \Gamma \quad Q \vdash \Delta, x : \boxminus \bar{A}; \Gamma}{\text{share } x \ \{ P \ \parallel \ Q \} \vdash \Delta', \Delta, x : \boxplus \bar{A}; \Gamma} \text{[Tshare]} \quad \frac{P \vdash \Delta; \Gamma \quad Q \vdash \Delta; \Gamma}{P + Q \vdash \Delta; \Gamma} \text{[Tsum]}
\end{array}$$

Fig. 1. Typing Rules $P \vdash \Delta; \Gamma$ for πSS .

We assume that channel names in Δ and Γ are pairwise distinct. The empty context is written \emptyset . If Γ is empty we write just $P \vdash \Delta$ instead of $P \vdash \Delta; \emptyset$. We write Δ, Δ' (two comma-separated contexts) for the disjoint union of Δ and Δ' . All the typing rules of πSS are displayed in Figure 1.

We now go through each of the connectives of πCLL , presenting their associated typing rules (static semantics) and principal cut-reductions (dynamic semantics) in detail.

Inaction, Cut, Parallel. Inaction and composition are typed by the rules

$$\frac{}{\mathbf{0} \vdash \emptyset; \Gamma} \text{[T0]} \quad \frac{P \vdash \Delta', x : A; \Gamma \quad Q \vdash \Delta, x : \bar{A}; \Gamma}{P \ |x : A| \ Q \vdash \Delta', \Delta; \Gamma} \text{[Tcut]} \quad \frac{P \vdash \Delta'; \Gamma \quad Q \vdash \Delta; \Gamma}{P \parallel Q \vdash \Delta', \Delta; \Gamma} \text{[Tpar]}$$

Rule [T0] is computationally interpreted by the inaction $\mathbf{0}$ process, which types with the empty linear typing context and an arbitrary unrestricted context Γ , and operationally it does nothing.

The logical cut rule [Tcut] is interpreted by interactive composition. Processes P and Q run concurrently, interacting on a single private linear session x . Process P provides a behaviour of type A along x , whereas Q offers on x a dual behaviour of type \bar{A} . Cut is annotated with the type of its left argument, but we sometimes omit this annotation.

Finally, rule [Tpar] corresponds to linear logic mix rule and types the independent composition of two processes P and Q , which run in parallel without ever interfering with each other, but offering together a common interface. Since the linear typing context is linearly handled, we assume that Δ and Δ' are disjoint. The same principle applies to [Tcut].

Session Termination. The dual types $\mathbf{1}$ (one) and \perp (bottom) type session termination

$$\frac{}{\text{close } x \vdash x : \mathbf{1}; \Gamma} \text{ [T1]} \quad \frac{Q \vdash \Delta; \Gamma}{\text{wait } x; Q \vdash \Delta, x : \perp; \Gamma} \text{ [T}\perp\text{]}$$

Process $\text{close } x$ closes a session x and $\text{wait } x; Q$ waits for the session to be closed, continuing as Q . The interaction is modelled by the reduction rule

$$\text{close } x \mid x : \mathbf{1} \mid \text{wait } x; Q \rightarrow Q \quad \text{[1}\perp\text{]}$$

where, after the interaction, the session on x disappears. As already highlighted, process reductions in our language correspond to adequate proof conversions, and are intrinsically type preserving (subject reduction holds (Theorem 6.6)). We illustrate this correspondence with rule [1 \perp]:

$$\frac{\frac{}{\text{close } x \vdash x : \mathbf{1}; \Gamma} \text{ [T1]} \quad \frac{Q \vdash \Delta; \Gamma}{\text{wait } x; Q \vdash \Delta, x : \perp; \Gamma} \text{ [T}\perp\text{]}}{\text{close } x \mid x \mid \text{wait } x; Q \vdash \Delta; \Gamma} \text{ [Tcut]} \rightarrow Q \vdash \Delta; \Gamma$$

Forwarding. Process $\text{fwd } x \ y$ interprets the identity axiom (on linear names)

$$\frac{}{\text{fwd } x \ y \vdash x : \bar{A}, y : A; \Gamma} \text{ [Tfwd]}$$

Operationally, it acts as a link redirecting all interactions between channels x and y . The associated reduction is implemented by name substitution [Caires et al. 2012]

$$\text{fwd } x \ y \mid y : A \mid P \rightarrow \{x/y\}P \quad \text{[fwd]}$$

Send and Receive. The dual types $A \otimes B$ (tensor) and $\bar{A} \wp \bar{B}$ (par) type session communication

$$\frac{P_1 \vdash \Delta_1, y : A; \Gamma \quad P_2 \vdash \Delta_2, x : B; \Gamma}{\text{send } x(y.P_1); P_2 \vdash \Delta_1, \Delta_2, x : A \otimes B; \Gamma} \text{ [T}\otimes\text{]} \quad \frac{Q \vdash \Delta, z : \bar{A}, x : \bar{B}; \Gamma}{\text{recv } x(z); Q \vdash \Delta, x : \bar{A} \wp \bar{B}; \Gamma} \text{ [T}\wp\text{]}$$

We abbreviate $A \multimap B \triangleq \bar{A} \wp B$. Process $\text{send } x(y.P_1); P_2$ sends a fresh session channel y on session x . Dually, process $\text{recv } x(z); Q$ receives a name z on session x . Name y is bound in P_1 and z is bound in Q . The send process is composed of two independent parts: a term P_1 which implements the session on (fresh) channel $y : A$ to be sent, and a term P_2 which provides the continuation session behaviour on $x : B$. The associated reduction is expressed by

$$\text{send } x(y.P_1); P_2 \mid x : A \otimes B \mid \text{recv } x(z); Q \rightarrow P_2 \mid x : B \mid (P_1 \mid y : A \mid \{y/z\}Q) \quad \text{[}\otimes\wp\text{]}$$

Notice that a cut on a session $A \otimes B$ gives origin to two *lower rank* cuts on sessions A and B . The inner cut on y connects the continuation Q of the receiver with the provider P_1 of the sent channel,

whereas the outer cut on x connects Q to the continuation P_2 of the sending process. Observe that the type associated with session x evolves from $A \otimes B$ to B upon communication.

As in [Caires and Pfenning 2010; Wadler 2012], only fresh (bound) names are sent in communication, following the *internal* mobility discipline of Boreale [Boreale 1996], as opposed to *external* mobility in which free names can be transmitted. However, the free output of (free) linear name y can be encoded as $\text{send } x \ y; P \triangleq \text{send } x(z. \text{fwd } y \ z); P$. The following typing rule is then admissible

$$\frac{P \vdash \Delta, x : B; \Gamma}{\text{send } x \ y; P \vdash \Delta, y : \bar{A}, x : A \otimes B; \Gamma} \text{ [T}\otimes_f\text{]}$$

Offer and Choice. The dual types $A \& B$ (with) and $\bar{A} \oplus \bar{B}$ (plus) type offer and choice

$$\frac{P_1 \vdash \Delta, x : A; \Gamma \quad P_2 \vdash \Delta, x : B; \Gamma}{\text{case } x \{ | \text{inl} : P_1 \mid \text{inr} : P_2 \} \vdash \Delta, x : A \& B; \Gamma} \text{ [T}\&\text{]}$$

$$\frac{Q_1 \vdash \Delta', x : \bar{A}; \Gamma}{x. \text{inl}; Q_1 \vdash \Delta', x : \bar{A} \oplus \bar{B}; \Gamma} \text{ [T}\oplus_l\text{]} \quad \frac{Q_2 \vdash \Delta', x : \bar{B}; \Gamma}{x. \text{inr}; Q_2 \vdash \Delta', x : \bar{A} \oplus \bar{B}; \Gamma} \text{ [T}\oplus_r\text{]}$$

Process $\text{case } x \{ | \text{inl} : P_1 \mid \text{inr} : P_2 \}$ offers a menu of two options: left P_1 and right P_2 , whereas $x. \text{inl}; Q_1$ and $x. \text{inr}; Q_2$ choose left and right, respectively. The two associated reduction rules are

$$\begin{aligned} \text{case } x \{ | \text{inl} : P_1 \mid \text{inr} : P_2 \} \mid x : A \& B \mid x. \text{inl}; Q_1 &\rightarrow P_1 \mid x : A \mid Q_1 \quad [\&\oplus_l] \\ \text{case } x \{ | \text{inl} : P_1 \mid \text{inr} : P_2 \} \mid x : A \& B \mid x. \text{inr}; Q_2 &\rightarrow P_2 \mid x : B \mid Q_2 \quad [\&\oplus_r] \end{aligned}$$

Example 2.1 (Maybe). We define Maybe $A \triangleq \mathbf{1} \oplus A$. Processes $\text{nothing } x \vdash x : \text{Maybe } A$ and just $a \ x \vdash a : \bar{A}, x : \text{Maybe } A$ are encoded as $\text{nothing } x \triangleq x. \text{inl}; \text{close } x$ and just $a \ x \triangleq x. \text{inr}; \text{fwd } a \ x$.

Example 2.2 (Linear Booleans). We encode the linear booleans as sessions of type $\text{Bool} \triangleq \mathbf{1} \oplus \mathbf{1}$

$$\text{ifalse } b \vdash b : \text{Bool} \quad \text{ltrue } b \vdash b : \text{Bool} \quad \text{ifalse } b \triangleq b. \text{inl}; \text{close } b \quad \text{ltrue } b \triangleq b. \text{inr}; \text{close } b$$

Consider processes $\text{discard } x \vdash x : \overline{\text{Bool}}$, $\text{not } x \ y \vdash x : \overline{\text{Bool}}, y : \text{Bool}$ and $\text{and } x \ y \ z \vdash x : \overline{\text{Bool}}, y : \overline{\text{Bool}}, z : \text{Bool}$ which operate on linear booleans and are defined by

$$\begin{aligned} \text{discard } x &\triangleq \text{case } x \{ | \text{inl} : \text{wait } x; \mathbf{0} \mid \text{inr} : \text{wait } x; \mathbf{0} \} \\ \text{not } x \ y &\triangleq \text{case } x \{ | \text{inl} : \text{wait } x; \text{true } y \mid \text{inr} : \text{wait } x; \text{false } y \} \\ \text{and } x \ y \ z &\triangleq \text{case } x \{ | \text{inl} : \text{wait } x; (\text{discard } y \parallel \text{false } z) \mid \text{inr} : \text{wait } x; \text{fwd } y \ z \} \end{aligned}$$

Process $\text{discard } x$ consumes a linear boolean on x , $\text{not } x \ y$ consumes a linear boolean on x and produces its negated value on y and $\text{and } x \ y \ z$ consumes booleans on channels x and y and produces their logical conjunction on channel z . Process $\text{and } x \ y \ z$ starts by performing case analysis on x . If x chooses left (false), then it waits for the session to be closed and then, in parallel, discards y (the output is false regardless of the input on y) and produces the boolean false on z . On the other hand, if x chooses right (true), then it waits for the session to be closed and then links the boolean y to z .

Servers. The dual types $!A$ (bang) and $? \bar{A}$ (why not) type server definition and client invocation

$$\frac{P \vdash y : A; \Gamma}{!x(y); P \vdash x : !A; \Gamma} \text{ [T!]} \quad \frac{Q \vdash \Delta; \Gamma, x : \bar{A}}{?x; Q \vdash \Delta, x : ? \bar{A}; \Gamma} \text{ [T?]}$$

$$\frac{P \vdash y : A; \Gamma \quad Q \vdash \Delta; \Gamma, x : \bar{A}}{y. P \mid !x : A \mid Q \vdash \Delta; \Gamma} \text{ [Tcut!]} \quad \frac{Q \vdash \Delta, z : \bar{A}; \Gamma, x : \bar{A}}{\text{call } x(z); Q \vdash \Delta; \Gamma, x : \bar{A}} \text{ [Tcall]}$$

The term $!x(y); P$ denotes a process that persistently offers on x a service of type A provided by P (the server body): it corresponds to the well-known replicated server process in the π -calculus. Process $?x; Q$ moves a session $x : \bar{A}$ from the linear to the unrestricted context (to be typed as $x : \bar{A}$) and proceeds as Q . Whereas $[\text{Tcut}]$ acts on the linear context, $[\text{Tcut}!]$ acts on the unrestricted context. The term $y.P \mid x : A \mid Q$ composes a server body P with a pool of clients represented by Q , and which can request a service an unbounded (possibly zero) number of times. Process $\text{call } x(z); Q$ calls a service on the server x , to be processed on the fresh name z , and continues as Q . The interaction between $[\text{T}!]$ and $[\text{T}?]$ is expressed by rule $[\text{!}]$

$$!x(y); P \mid x : !A \mid ?x; Q \rightarrow y.P \mid x : A \mid Q \quad [\text{!}]$$

where a linear cut on $x : !A$ reduces to an unrestricted cut on $x : A$. This cut-reduction is standard in dyadic presentations of linear logic [Pfenning 1995] and it may be computationally understood as activation of the linear server code in a thread pool, for shared invocation by clients. Then, server invocation by clients is modelled by rule $[\text{call}]$

$$y.P \mid x : A \mid \text{call } x(z); Q \rightarrow \{z/y\}P \mid z : A \mid (y.P \mid x : A \mid Q) \quad [\text{call}]$$

A linear replica of the server body is instantiated on the fresh name z as $\{z/y\}P$. Notice that the server body is still available to the continuation Q for (possibly) further requests.

The identity axiom over the unrestricted context is interpreted by the copycat process

$$\text{fwd}; w \ y \triangleq !w(z); \text{call } y(z'); \text{fwd } z \ z' \vdash w : !A; \Gamma, y : \bar{A}$$

Free output on unrestricted names y is defined by $\text{send } x \ y; P \triangleq \text{send } x(w.\text{fwd}; w \ y); P$. Notice that given $P \vdash \Delta, x : B; \Gamma, y : \bar{A}$ we have $\text{send } x \ y; P \vdash \Delta, x : !A \otimes B; \Gamma, y : \bar{A}$.

Example 2.3. Consider the boolean-negation server $\text{not}; s \vdash s : !(\text{Bool} \multimap \text{Bool} \otimes 1)$, defined by

$$\text{not}; s \triangleq !s(c); \text{rcv } c(b); \text{send } c(b'. \text{not } b \ b'); \text{close } c$$

that persistently, on each call on s , spawns a process that receives a boolean b on channel c , sends back its negated value b' and closes c . The following process

$$\begin{aligned} ?s; (C_1 \ s \ \parallel C_2 \ s) \vdash s : ?(\text{Bool} \otimes \text{Bool} \multimap \perp), \text{ where} \\ C_1 \triangleq \text{call } s(c); \text{send } c(b. \text{true } b); \text{rcv } c(b'); \text{wait } c; C'_1 \\ C_2 \triangleq \text{call } s(c); \text{send } c(b. \text{false } b); \text{rcv } c(b'); \text{wait } c; C'_2 \end{aligned}$$

activates the server on s , which is then shared between two clients that run in parallel. Client C_1 calls a service on s which is spawned on c . Then, on c , the client sends true , receives the computed boolean b' , waits for the server to close the session and continues as C'_1 . Client C_2 behaves as C_1 but sends the boolean false instead. Both continuations $C'_1, C'_2 \vdash b' : \text{Bool}; s : \text{Bool} \otimes \text{Bool} \multimap \perp$ consume the received boolean b' and still have access to the boolean server s for further calls.

Polymorphism. The dual pair $\exists X.A$ (exists) and $\forall X.\bar{A}$ (for all) of existential and universal quantifiers implement type abstraction

$$\frac{P \vdash \Delta, x : \{B/X\}A; \Gamma}{\text{send } x \ B; P \vdash \Delta, x : \exists X.A; \Gamma} [\text{T}\exists] \quad \frac{Q \vdash \Delta, x : \bar{A}; \Gamma}{\text{rcv } x(X); Q \vdash \Delta, x : \forall X.\bar{A}; \Gamma} [\text{T}\forall]$$

In rule $[\text{T}\forall]$, X does not occur free in Δ, Γ . Process $\text{send } x \ B; P$ sends the representation type B along x , and then continues as P . Dually, process $\text{rcv } x(X); Q$ receives on x a representation and continues as Q . The associated reduction is

$$\text{send } x \ B; P \mid x : \exists X.A \mid \text{rcv } x(X); Q \rightarrow P \mid x : \{B/X\}A \mid \{B/X\}Q \quad [\exists\forall]$$

The presence of existential quantifiers allow us to hide the representation datatype (cf. [Mitchell and Plotkin 1988]) of our concurrent shareable stateful ADTs, as we will show when introducing the Stack and Queue examples (Section 5). On the other hand, with universal quantifiers we can express inductive datatypes such as naturals and lists (see [Toninho and Yoshida 2021; Wadler 1990b]), as we illustrate in the following example, by encoding the Church numerals.

Example 2.4 (Inductive types). We illustrate the usage of type quantifiers to encode inductive types, by implementing the naturals with polymorphic sessions (cf. [Girard et al. 1989])

$$\begin{aligned} \text{Nat} &\triangleq \forall X.X \multimap !(X \multimap X) \multimap X \\ \text{zero } n &\triangleq \text{rcv } n(X); \text{rcv } n(z); \text{rcv } n(s); ?s; \text{fwd } z \ n \\ \text{succ } n \ m &\triangleq \text{rcv } m(X); \text{rcv } m(z); \text{rcv } m(s); ?s; \\ &\quad \text{send } n \ X; \text{send } n \ z; \text{send } n \ s; \text{call } s(c); \text{send } c \ n; \text{fwd } c \ m \end{aligned}$$

Terms of type Nat receive a type variable X , a value $z : X$ and a server $s : !(X \multimap X)$ and call the server s a finite (possibly zero) number of times on z to return a value $n : X$. Notice that $\text{zero } n \vdash n : \text{Nat}$ simply forwards z on n without calling the server s . On the other hand, $\text{succ } n \ m \vdash n : \text{Nat}, m : \text{Nat}$ calls the server one more time on the output produced by the calls of n . The encoding of the naturals allows for the definition of recursive operations. For example, the predicate $\text{zero? } n \ b \vdash n : \text{Nat}, b : \text{Bool}$ that consumes a natural n and produces the boolean true if n is zero and false otherwise is defined by

$$\text{zero? } n \ b \triangleq \text{send } n \ \text{Bool}; \text{send } n(z.\ \text{true } z); \text{send } n(s.\ \text{kfalse } s); \text{fwd } n \ b$$

where $\text{kfalse } s \vdash s : !(\text{Bool} \multimap \text{Bool})$ is a server that outputs false regardless of the input.

3 πSS : A LANGUAGE WITH SHARED STATE

In this section we describe πSS , the main novelty of this paper, which is a PaT conservative extension of πCLL with shared state. We present several examples that illustrate the main features of πSS .

Reference Cells. The modalities \boxtimes and \boxminus introduce reference cells and discipline their usage

$$\begin{aligned} &\frac{P \vdash y : !A; \Gamma}{\text{cell } x(y.P) \vdash x : \boxtimes A; \Gamma} \text{ [Tcell]} && \frac{Q \vdash \Delta; \Gamma}{\text{free } x; Q \vdash \Delta, x : \boxminus \bar{A}; \Gamma} \text{ [Tfree]} \\ &\frac{Q \vdash \Delta, z : ?\bar{A}, x : \boxminus \bar{A}; \Gamma}{\text{read } x(z); Q \vdash \Delta, x : \boxminus \bar{A}; \Gamma} \text{ [Tread]} && \frac{Q_1 \vdash z : !A; !Q_2 \vdash \Delta, x : \boxminus \bar{A}; \Gamma}{\text{wrt } x(z.Q_1); Q_2 \vdash \Delta, x : \boxminus \bar{A}; \Gamma} \text{ [Twrite]} \end{aligned}$$

The $\text{cell } x(y.P)$ construct denotes a reference cell at x storing a process P . P defines some replicated session behaviour at y (y binding in P). A thread releases its usage of a cell with $\text{free } x; Q$, typed by [Tfree]. When a cell is not being shared with any other thread, free will cause the cell to be "deallocated", as modelled by the reduction rule $\boxtimes\boxtimes\text{f}$

$$\text{cell } x(y.P) \mid x : \boxtimes A \mid \text{free } x; Q \rightarrow Q \quad \boxtimes\boxtimes\text{f}$$

Processes read and write reference cells with constructs $\text{read } x(y); Q$ and $\text{wrt } x(y.Q_1); Q_2$. Reading is modelled by the reduction rule $\boxtimes\boxtimes\text{r}$

$$\text{cell } x(y.P) \mid x : \boxtimes A \mid \text{read } x(z); Q \rightarrow \{z/y\}P \mid z : !A \mid (\text{cell } x(y.P) \mid x : \boxtimes A \mid Q) \quad \boxtimes\boxtimes\text{r}$$

The contents P are atomically read, copied (it is typed $y : !A$) and received by the continuation Q at parameter z , by composition with cut. The system reduces to a process with two cuts. The inner cut

connects the reference cell to the continuation Q , whereas the outer cut connects Q to a spawned copy $\{z/y\}P$ of the cell contents. The write operation is expressed by rule $[\boxplus\boxminus w]$

$$\text{cell } x(y.P) \mid x : \boxplus A \mid \text{wrt } x(z.Q_1); Q_2 \quad \rightarrow \quad \text{cell } x(z.Q_1) \mid x : \boxplus A \mid Q_2 \quad [\boxplus\boxminus w]$$

Here, the contents of cell x are atomically and destructively updated by the write operation. The cell changes its contents from $y.P$ to $z.Q_1$, but its protocol $\boxplus A$ is left unchanged.

A cell is a persistent object in the sense that it may be sequentially read and written an arbitrary number of times, until freed by all clients. The basic cell protocol $\boxplus A$ may be expressed by the recursive equation $\boxplus A = \&\{\text{free} : 1, \text{read} : !A \otimes \boxplus A, \text{write} : !A \multimap \boxplus A\}$. A cell usage name is a linear object (it lies in the linear context) and therefore cannot be implicitly copied and discarded (as opposed to unrestricted names). However, cell usages are explicitly released with the free operation and cell aliases can be created via an explicit share operation, which shall be introduced shortly.

A (replicated) value stored in a cell cannot depend on free linear names (see the premise of $[\text{Tcell}]$), in particular, it cannot depend on free cell references, so our language cannot express circular data structures. Particularly, we cannot express the Landin's knot, which is sensible, since otherwise this would break normalisation. However, a (replicated) value stored in a cell may of course allocate and use reference cells locally.

Our rules for reference cells take inspiration in the proof rules for the DiLL [Ehrhard 2018] modalities $?A$ and $!A$ (which are operations with a very different semantics from the usual linear logic exponentials). In general, our $\boxplus A$ and $\boxminus A$ modalities follow principles of DiLL $?A$ and $!A$ modalities respectively. In this sense, $[\text{Tcell}]$ corresponds to \boxplus -dereliction and $[\text{Tfree}]$ corresponds to \boxminus -co-weakening. Typing rules $[\text{Tread}]$ and $[\text{Twrite}]$ are new, they incorporate \boxminus -co-dereliction, but also follow the general structure of the typing rules for receive ($[\text{T}\&]$) and send ($[\text{T}\otimes]$).

Example 3.1 (First-Class Cells). Our references cells are first-class (as in e.g., ML). In particular, cell references may be passed along session channels as in the following code

$$(\text{cell } c(v.V) \mid c : \boxplus A \mid \text{send } x c; S) \mid x : \boxplus A \otimes B \mid \text{recv } x(c'); \text{free } c'; R \quad \xrightarrow{+} \quad S \mid x : B \mid R$$

In this example, an usage to cell reference c is sent along channel x to the receiver, that frees it upon reception on the input parameter c' . Typing information is shown in detail below

$$\begin{array}{ll} (1) V \vdash v : !A; \Gamma & (2) S \vdash \Delta_1, x : B; \Gamma & (3) R \vdash \Delta_2, x : \bar{B}; \Gamma \\ (4) \text{cell } c(v.V) \vdash c : \boxplus A; \Gamma & & [\text{Tcell}], (1) \\ (5) \text{send } x c; S \vdash \Delta_1, c : \boxminus \bar{A}, x : \boxplus A \otimes B; \Gamma & & [\text{T}\otimes_f], (2) \\ (6) \text{free } c'; R \vdash \Delta_2, c' \boxminus \bar{A}, x : \bar{B}; \Gamma & & [\text{Tfree}], (3) \\ (7) \text{recv } x(c'); \text{free } c'; R \vdash \Delta_2, x : \boxplus A \multimap \bar{B}; \Gamma & & [\text{T}\&], (6) \\ (8) \text{cell } c(v.V) \mid c \mid \text{send } x c; S \vdash \Delta_1, z : \boxplus A \otimes B; \Gamma & & [\text{Tcut}], (4), (5) \\ (9) (\text{cell } c(v.V) \mid c \mid \text{send } x c; S) \mid x \mid \text{recv } x(c'); \text{free } c'; R \vdash \Delta_1, \Delta_2; \Gamma & & [\text{Tcut}], (7), (8) \end{array}$$

Notice that the sending process loses access to the reference cell c as shown by typing judgement (2): the name c is not available in its continuation S .

Example 3.2 (Higher-Order Store). We illustrate the use of higher-order store by giving an (inefficient) array implementation [Pierce 2002] in πSS . Let $\text{Array} \triangleq \boxplus(!\text{Nat} \multimap \text{Nat})$. An array is a reference cell to a *function* from naturals to naturals. Let

$$\begin{array}{l} \text{init } a \triangleq \text{cell } a(s.!s(f); \text{recv } f(n); ?n; \text{zero } f) \\ \text{lookup } a \ n \ m \ a' \triangleq \text{read } a(s); ?s; \text{call } s(f); \text{send } f \ n; (\text{fwd } f \ m \parallel \text{fwd } a \ a') \end{array}$$

Process `init a` $\vdash a : \text{Array}$ allocates a reference cell a with a function f that outputs the natural zero on each inputed index n . Process `lookup a n m a'` $\vdash a : \overline{\text{Array}}, n : \overline{\text{!Nat}}, m : \text{Nat}, a : \text{Array}$ computes the n -th entry of the array a on m and forwards the unmodified array on a' . Code for the operation `update a n m a'` $\vdash a : \overline{\text{Array}}, n : \overline{\text{!Nat}}, m : \overline{\text{!Nat}}, a : \text{Array}$, that updates the n -th entry of the array a with m , producing the updated array on a' , is given in the supplementary material.

Sharing and Nondeterminism. Share and sum are typed by the rules

$$\frac{P \vdash \Delta', x : \overline{\square A}; \Gamma \quad Q \vdash \Delta, x : \overline{\square A}; \Gamma}{\text{share } x \{P \parallel Q\} \vdash \Delta', \Delta, x : \overline{\square A}; \Gamma} [\text{Tshare}] \quad \frac{P \vdash \Delta; \Gamma \quad Q \vdash \Delta; \Gamma}{P + Q \vdash \Delta; \Gamma} [\text{Tsum}]$$

The `share x {P || Q}` construct allows a reference cell at x to be aliased and manipulated by multiple threads, as the following example involving concurrent writers illustrates

$$\text{cell } x(y.V) \mid x \mid \text{share } x \{ \text{wrt } x(y.V_1); P \parallel \text{wrt } x(y.V_2); Q \}$$

Here the cell at x is being accessed by concurrent threads `wrt x(y.V1); P` and `wrt x(y.V2); Q`. Intuitively, the final state of the cell depends on the order of writes. In our PaT interpretation the process above reduces (via cut-reduction) to a sum that shows the alternative states of the cell after both writes (last writer wins), and corresponds to non-deterministic sum of process algebras.

$$(\text{cell } x(y.V_1) + \text{cell } x(y.V_2)) \mid x \mid \text{share } x \{P \parallel Q\}$$

The typing rule for share precisely corresponds to \square -co-contraction (cf. DiLL). Co-contraction enforces that processes P and Q may linearly interact at the shared reference x , but not on other linear objects - the linear context is handled multiplicatively. This condition is important for deadlock freedom, and related with the relevance of acyclicity for cut-elimination in linear logic proofs (e.g., as in the session type systems [Caires and Pfenning 2010; Wadler 2012], in which interaction is expressed by the cut, different threads cannot share more than one communication channel). However, notice that (1) a single shared cell may store all the state shared by the two threads (e.g. in a resource bundle, a sequence of values) and (2) a reference cell can be used by any number of client threads, by iterated use of the share construct.

Example 3.3 (Dynamic Sharing). Notwithstanding the seemingly static character of the share construct (which appears as a special form of parallel composition where two threads are allowed to share a single mutable cell), notice that the topology of the sharing trees arising from nested share blocks may actually change dynamically during computation, because of the extrusion of cell references along session channels to outside the share block. Consider the following reduction

$$\begin{aligned} & \text{share } x \{R \parallel \text{send } z x; P\} \mid z \mid \text{recv } z(y); \text{share } y \{Q \parallel S\} \\ & \xrightarrow{+} P \mid z \mid \text{share } x \{R \parallel \text{share } x \{ \{x/y\}Q \parallel \{x/y\}S \} \} \end{aligned}$$

Here, a shared alias of x is sent along z to a partner receive process, that inputs the alias and further shares it between threads Q and S . Hence, access to x , initially only shared between the two threads R and `send z x; P`, ends up being shared among the three threads R , $\{x/y\}Q$ and $\{x/y\}S$. The thread `send z x; P` transfers ownership of x on output – references aliases are linear values, whose visibility may only be duplicated by the share construct. Indeed, linear typing of session

send ensures that P must lose access to x . We show typings for components of the above reduction

- (1) $R \vdash \Delta_1, x : \boxed{\bar{A}}; \Gamma$ (2) $P \vdash \Delta_2, z : B; \Gamma$ (3) $Q \vdash \Delta_3, y : \boxed{\bar{A}}, z : \bar{B}; \Gamma$ (4) $S \vdash \Delta_4, y : \boxed{\bar{A}}; \Gamma$
- (5) $\text{send } z \ x; P \vdash \Delta_2, x : \boxed{\bar{A}}, z : \boxed{A} \otimes B; \Gamma$ $[[\text{T}\otimes_f], (2)]$
- (6) $\text{share } x \{R \parallel \text{send } z \ x; P\} \vdash \Delta_1, \Delta_2, x : \boxed{\bar{A}}, z : \boxed{A} \otimes B; \Gamma$ $[[\text{Tshare}], (1), (5)]$
- (7) $\text{share } y \{Q \parallel S\} \vdash \Delta_3, \Delta_4, y : \boxed{\bar{A}}, z : \bar{B}; \Gamma$ $[[\text{Tshare}], (3), (4)]$
- (8) $\text{recv } z(y); \text{share } y \{Q \parallel S\} \vdash \Delta_3, \Delta_4, z : \boxed{A} \multimap \bar{B}; \Gamma$ $[[\text{T}\otimes], (7)]$
- (9) $\text{share } x \{R \parallel \text{send } z \ x; P\} \mid z \mid \text{recv } z(y); \text{share } y \{Q \parallel S\} \vdash \Delta_1, \Delta_2, \Delta_3, \Delta_4, x : \boxed{\bar{A}}; \Gamma$
 $[[\text{Tcut}], (6), (8)]$

We revisit this example in Section 6, providing a step-by-step derivation for the reduction above.

4 πSSL : A LANGUAGE WITH SHARED STATE AND LOCKS

In this Section, we extend our basic stateful language πSS with typed locking primitives, without breaking the key property of deadlock freedom. Although one could suspect that locking behaviour may break the progress property, the linear logic type discipline resiliently preserves the deadlock freedom property, where typing ensures acyclicity in communication, herein in locking. The key insight is that reductions in the components of $\text{share } x \{P \parallel Q\}$ are independent (apart from x , P and Q are typed in disjoint linear contexts, as in e.g., $P \parallel Q$), and concurrent operations on x are always converted to a sum via interleaving, before they interact with the cell at x . In particular, reductions are always available in any component of the resulting sum, and of course, progress in one component of a sum does not depend on progress of the other branch. The presence of locks will drop some summands that otherwise would break atomicity of the critical sections, but, intuitively, dropping a summand will never break progress.

To the collection of types we thus add a pair of dual modalities \boxed{A} (locked box why not) and $\boxed{\bar{A}}$ (locked box bang) that represent a locked state and that act as "mirror" of the basic modalities \boxed{A} , $\boxed{\bar{A}}$, which in turn represent the unlocked state. A key property enforced by the locked usage modality $\boxed{\bar{A}}$ is that only a single thread usage may be actively interacting with the (locked) memory cell. Lock and unlock operations essentially alternate between the two states

$$\frac{Q \vdash \Delta, x : \boxed{\bar{A}}; \Gamma}{\text{lock } x; Q \vdash \Delta, x : \boxed{\bar{A}}; \Gamma} [\text{Tlock}] \quad \frac{Q \vdash \Delta, x : \boxed{\bar{A}}; \Gamma}{\text{unlock } x; Q \vdash \Delta, x : \boxed{\bar{A}}; \Gamma} [\text{Tunlock}]$$

The associated reductions are

$$\begin{aligned} \text{cell } x(y.P) \mid x : \boxed{A} \mid \text{lock } x; Q &\rightarrow \text{cell } x(y.P) \mid x : \boxed{A} \mid Q \quad [\boxed{\square}\square] \\ \text{cell } x(y.P) \mid x : \boxed{A} \mid \text{unlock } x; Q &\rightarrow \text{cell } x(y.P) \mid x : \boxed{A} \mid Q \quad [\boxed{\square}\square\text{u}] \end{aligned}$$

The previously introduced typing rules $[\text{Tcell}]$, $[\text{Tread}]$ and $[\text{Twrite}]$ have now a mirrored version, corresponding to (unique) locked usage.

$$\frac{P \vdash y : !A; \Gamma}{\text{cell } x(y.P) \vdash x : \boxed{A}; \Gamma} \quad \frac{Q \vdash \Delta, y : ?\bar{A}, x : \boxed{\bar{A}}; \Gamma \quad P \vdash y : !A; \Gamma \quad Q \vdash \Delta, x : \boxed{\bar{A}}; \Gamma}{\text{read } x(y); Q \vdash \Delta, x : \boxed{\bar{A}}; \Gamma \quad \text{wrt } x(y.P); Q \vdash \Delta, x : \boxed{\bar{A}}; \Gamma}$$

Similarly, the principal cut conversions $[\boxed{\square}\square\text{r}]$ and $[\boxed{\square}\square\text{w}]$ have a mirrored version $[\boxed{\square}\square\text{r}]$ and $[\boxed{\square}\square\text{w}]$, respectively. Rule $[\boxed{\square}\square\text{r}]$ (resp., $[\boxed{\square}\square\text{w}]$) is written as $[\boxed{\square}\square\text{r}]$ (resp., $[\boxed{\square}\square\text{w}]$) but with the type annotation \boxed{A} replaced by $\boxed{\bar{A}}$. Therefore, the behavioural 1-state protocol of cells is extended to a 2-state protocol, which we may write as

$$\begin{aligned} \boxed{A} &= \&\{\text{free} : \mathbf{1}, \text{read } :!A \otimes \boxed{A}, \text{write } :!A \multimap \boxed{A}, \text{lock} : \boxed{A}\} \\ \boxed{\bar{A}} &= \&\{\text{read } :!A \otimes \boxed{\bar{A}}, \text{write } :!A \multimap \boxed{\bar{A}}, \text{unlock} : \boxed{\bar{A}}\} \end{aligned}$$

Besides [Tshare], two additional co-contraction rules are now added for taming locked usage:

$$\frac{P \vdash \Delta', x : \boxed{\bar{A}}; \Gamma \quad Q \vdash \Delta, x : \boxed{\bar{A}}; \Gamma}{\text{shareL } x \{P \parallel Q\} \vdash \Delta', \Delta, x : \boxed{\bar{A}}; \Gamma} [\text{TshareL}] \quad \frac{P \vdash \Delta', x : \boxed{\bar{A}}; \Gamma \quad Q \vdash \Delta, x : \boxed{\bar{A}}; \Gamma}{\text{shareR } x \{P \parallel Q\} \vdash \Delta', \Delta, x : \boxed{\bar{A}}; \Gamma} [\text{TshareR}]$$

These constructs are slight variations of [Tshare] keeping track of the component currently holding the lock, left ($\text{shareL } x \{P \parallel Q\}$), and right ($\text{shareR } x \{P \parallel Q\}$), and particular congruence rules apply to them (see Fig. 5). For example, consider system

$$\text{cell } c(b.\text{true } b) \mid c : \boxed{\text{Bool}} \mid \text{share } c \{\text{lock } c; \text{wrt } c(b'.\text{false } b'); \text{unlock } c; P \parallel \text{lock } c; Q\}$$

Here, two concurrent lock actions are competing for exclusive access of the boolean cell. By \equiv law [LL] this process is rewritten into an \equiv -equivalent nondeterministic sum $S_1 + S_2$, where the two lock instructions get interleaved. Each summand S_i is then

$$\begin{aligned} S_1 &\triangleq \text{cell } c(b.\text{true } b) \mid c : \boxed{\text{Bool}} \mid \text{lock } c; \text{shareL } c \{\text{wrt } c(b'.\text{false } b'); \text{unlock } c; P \parallel \text{lock } c; Q\} \\ S_2 &\triangleq \text{cell } c(b.\text{true } b) \mid c : \boxed{\text{Bool}} \mid \text{lock } c; \text{shareR } c \{\text{lock } c; \text{wrt } c(b'.\text{false } b'); \text{unlock } c; P \parallel Q\} \end{aligned}$$

Notice that reductions in summands S_1, S_2 of process $S_1 + S_2$ are now completely independent. We will then continue by illustrating reduction for S_1 , the case of S_2 being similar. We have

$$\begin{aligned} S_1 &\rightarrow \text{cell } c(b.\text{true } b) \mid c : \boxed{\text{Bool}} \mid \text{shareL } c \{\text{wrt } c(b'.\text{false } b'); \text{unlock } c; P \parallel \text{lock } c; Q\} (\rightarrow [\boxed{\text{L}}]) \\ &\equiv \text{cell } c(b.\text{true } b) \mid c : \boxed{\text{Bool}} \mid \text{wrt } c(b'.\text{false } b'); \text{shareL } c \{\text{unlock } c; P \parallel \text{lock } c; Q\} (\equiv [\text{leftA}]) \\ &\rightarrow \text{cell } c(b'.\text{false } b') \mid c : \boxed{\text{Bool}} \mid \text{shareL } c \{\text{unlock } c; P \parallel \text{lock } c; Q\} (\rightarrow [\boxed{\text{w}}]) \\ &\equiv \text{cell } c(b'.\text{false } b') \mid c : \boxed{\text{Bool}} \mid \text{unlock } c; \text{share } c \{P \parallel \text{lock } c; Q\} (\equiv [\text{leftU}]) \\ &\rightarrow \text{cell } c(b'.\text{false } b') \mid c : \boxed{\text{Bool}} \mid \text{share } c \{P \parallel \text{lock } c; Q\} (\rightarrow [\boxed{\text{u}}]) \end{aligned}$$

First, the process locks and gives exclusive cell access to the left component of shareL. The congruence rules only allows cell operations on the left component to commute to the front of the shareL, as expressed by \equiv law [leftA]. Therefore, the write operation takes precedence over the pending lock operation of the right component. When the left component unlocks, the shareL is converted back to a share via \equiv rule [leftU]. Afterwards, process P loses exclusive access to the cell and now all operations on c coming from P (except for free) compete with the lock operation of the right component (\equiv rules [LA] and [LL]).

Typing rules [Tshare], [TshareL] and [TshareR] ensure that at most one process is holding the lock in a share topology. Interestingly, lock ownership may be freely communicated.

Example 4.1 (Counter). Let Nat be the type of the natural numbers of Example 2.4 and consider persistent versions of the previously defined processes $\text{zero } n$ and $\text{succ } n m$

$$\text{zero}_! n \triangleq !n(n0); \text{zero } n0 \vdash n : !\text{Nat}$$

$$\text{succ}_! n m \triangleq !m(m0); \text{call } n(n0); \text{succ } n0 m0 \vdash m : \overline{\text{Nat}}; n : \overline{\text{Nat}}$$

Define $\text{COUNTER} = \boxed{\text{Nat}}$ and the following processes

$$\text{c_zero } c \triangleq \text{cell } c(n.\text{zero}_! n) \vdash c : \text{COUNTER}$$

$$\text{client}_1 c \triangleq \text{read } c(n); ?n; \text{wrt } c(m.\text{succ}_! n m); \text{free } c; \mathbf{0} \vdash c : \overline{\text{COUNTER}}$$

$$\text{client}_2 c \triangleq \text{lock } c; \text{read } c(n); ?n; \text{wrt } c(m.(\text{succ}_! n m)); \text{unlock } c; \text{free } c; \mathbf{0} \vdash c : \overline{\text{COUNTER}}$$

$$\text{system}_i \triangleq \text{c_zero } c \mid c \mid \text{share } c \{\text{client}_i c \parallel \text{client}_i c\}, i \in \{1, 2\}$$

Process c_zero is a counter set to zero and $\text{client}_1 c$ and $\text{client}_2 c$ are two clients. $\text{client}_1 c$ reads the counter, writes back its incremented value, frees its usage and continues as the inaction process. $\text{client}_2 c$ is a variant of $\text{client}_1 c$ in which the read-and-increment sequence is within a critical section. system_i is the result of sharing the counter with two concurrent threads, each being client_i .

$\text{Stack } A \triangleq \exists X.!(X \multimap \text{Menu}(X)) \otimes X$ $\text{Menu}(X) \triangleq \&\{$ $\text{push} : !A \multimap X \otimes \mathbf{1},$ $\text{pop} : \text{Maybe } !A \otimes X \otimes \mathbf{1},$ $\text{share} : X \wp X \wp \perp,$ $\text{free} : \mathbf{1}\}$	$\text{mpush } c \ s \triangleq$ $\text{lock } s;$ $\text{read } s(l);$ $\text{recv } c(a);$ $?a; ?l;$ $\text{wrt } s(l'. \text{cons! } a \ l \ l');$ $\text{unlock } s;$ $\text{send } c \ s;$ $\text{close } c$	$\text{mshare } c \ s \triangleq$ $\text{recv } c(s_1);$ $\text{recv } c(s_2);$ $\text{wait } c;$ $\text{share } s \{$ $\quad \text{fwd } s \ s_1 \ $ $\quad \text{fwd } s \ s_2 \}$
$\text{stack } s \triangleq$ $\text{send } s(\boxplus \text{List } !A);$ $\text{send } s(m. !m(c); \text{menu } c);$ $\text{cell } s(l. \text{nil! } l)$	$\text{mpop } c \ s \triangleq$ $\text{lock } s;$ $\text{read } s(l);$ $?l;$ $\text{send } c(h. \text{head! } l \ h);$ $\text{wrt } s(l'. \text{tail! } l \ l');$ $\text{unlock } s;$ $\text{send } c \ s;$ $\text{close } c$	$\text{mfree } c \ s \triangleq$ $\text{free } s;$ $\text{close } c$
$\text{menu } c \triangleq$ $\text{recv } c(s);$ $\text{case } c\{$ $\quad \text{push} : \text{mpush } c \ s$ $\quad \text{pop} : \text{mpop } c \ s$ $\quad \text{share} : \text{mshare } c \ s$ $\quad \text{free} : \text{mfree } c \ s\}$		

Fig. 2. A Shared Stack - Server.

After the read-and-increment sequences being executed, system_1 leaves the cell in a nondeterministic superposition of two states $\text{cell } c(n.\text{one! } n) + \text{cell } c(n.\text{two! } n)$, where $\text{one! } n$ and $\text{two! } n$ offer persistently the naturals one and two on channel n . On the other hand, system_2 evolves to a single state $\text{cell } c(n.\text{two! } n)$. This is because the interleavings that break the intended atomicity of read-and-increment are dropped in the presence of locks.

5 MUTABLE SHAREABLE ADTS

We illustrate how shared mutable state fits together with πCLL by presenting two ADTs: a shared stack and a queue object. The representation type of both ADTs is hidden from the client through existential types. All the client gets is a menu of operations to act on the ADT, among which, as we shall see for the stack, lies the capability to share the representation with another client.

5.1 A Shared Stack

Code for the Stack, together with type definitions, is provided in Figure 2. An object of type $\text{Stack } A$ sends some representation type X , then outputs a persistent server of type $X \multimap \text{Menu}(X)$ and continues as X . The type expression $\text{Menu}(X)$, which depends on the representation type X , offers a menu with four options: push, pop, share and free. In this example, we use a labelled version of offer and choice, which is a standard generalisation, (see e.g. [Caires and Pérez 2017]).

Process $\text{stack } s$ is an object of type $s : \text{Stack } A$ whose representation type is $\text{List } !A$ (lists of elements of type $!A$) and whose persistent server body is given by $\text{my menu } c \vdash c : \boxplus \text{List } A \multimap \text{Menu}(\boxplus \text{List } A)$. Note that the stack is initially empty ($\text{cell } s(l.\text{nil! } l)$).

In the companion artifact [Rocha and Caires 2021] we encode the list datatype $\text{List } A$, together with the following operations: $\text{nil! } l \vdash l : !\text{List } !A$ offers persistently the empty list, $\text{cons! } a \ l \ l' \vdash l' : !\text{List } !A$; $a : \overline{A}, l : \text{List } !A$ computes on l' the result of prepending a to the head of l , $\text{head! } l \ h \vdash h :$

$\text{unpack } s \triangleq$ <pre style="margin: 0;"> recv s(X); recv s(m); ?m; client_m s </pre>	$\text{cfree}_m s; P \triangleq$ <pre style="margin: 0;"> call m(c); send c s; c.free; wait c; P </pre>	$\text{cpop}_m s; [P s', Q s' a] \triangleq$ <pre style="margin: 0;"> call m(c); send c s; c.pop; recv c(h); case h{ Nothing : recv c(s'); wait c; P s'; Just : recv c(a); recv c(s'); wait c; Q s' a} </pre>
$\text{cshare}_m s \text{ in } [P_1 s_1, P_2 s_2] \triangleq$ <pre style="margin: 0;"> call m(c); send c s; c.share; send c(s₁. P₁ s₁); send c(s₂. P₂ s₂); close c </pre>	$\text{cpush}_m s a; (P s') \triangleq$ <pre style="margin: 0;"> call m(c); send c s; c.push; send c a; recv c(s'); wait c; P s' </pre>	

Fig. 3. A Shared Stack - Client Operations.

Maybe $!A; l : \overline{\text{List } !A}$ produces on x the head of the list l (which might be none if the list is empty) and tail; $l' \vdash l' : !\text{List } !A; \overline{\text{List } !A}$ produces on l' the tail of list l .

Method $\text{mpush } c s \vdash c : !A \multimap \boxed{\text{List } !A} \otimes 1, s : \boxed{\text{List } !A}$ locks the stack s and then gets the current state in $l : !\text{List } !A$, through a read operation. Then receives on channel c an element $a : !A$ to be inserted on top of the stack. The persistent names a and l are then activated before being used. The stack is updated with a new list l' that is the result of prepending a to l . The updated stack is then unlocked and sent back to the client, after which the communication session c is closed.

Method $\text{mpop } c s$ accesses the contents of the stack s on l and sends its head element $h : \oplus\{\text{Nothing} : 1, \text{Just } !A\}$. The head of the list l might be Nothing if it is empty or Just an element $x : !A$. Then, the stack is updated with the tail of list l . Notice that, like in method mpush , all the stack's critical accesses are protected within lock-unlock sections.

Stack clients will not be able to tamper with the representation reference, being forced to manipulate it via the provided methods. Thus, the process operations that share and free a cell are exported with the ADT methods $\text{mshare } c s$ and $\text{mfree } c s$. Process $\text{mfree } c s$ frees its usage to the stack s and closes the session on c . Method $\text{mshare } c s \vdash c : X \wp X \wp \perp, s : \overline{X}$ (where $X = \boxed{\text{List } !A}$) receives two stack handlers s_1 and s_2 , waits for the client to terminate the session and proceeds as an operation that shares the stack s between s_1 and s_2 . We find it quite satisfying how the type interface of mshare expresses the co-contraction principle in an abstract and extremely clean way.

Code defining client operations is in Figure 3. Process $\text{unpack } s \vdash s : \text{Stack } A$ receives the opaque abstract type X and a communication channel m to invoke the stack menu, continuing as $\text{client}_m s$. Process $\text{client}_m s$ can be defined composing the available protocols: cpush_m , cpop_m , cshare_m and cfree_m . $\text{cpush}_m s a; (P s')$ pushes the element a on stack s and continues as $P s'$ (we use s' to denote the returned updated stack after a method call). $\text{cpop}_m s; [P s', Q s' a]$: pops an element from the stack s and continues as $P s'$ if the stack is empty and as $Q s' a$ if the stack's top element is a . $\text{cshare}_m s \text{ in } [P_1 s_1, P_2 s_2]$ shares the stack s between handlers s_1 and s_2 which are implemented by processes P_1 and P_2 (respectively). $\text{cfree}_m s; P$: frees the handler s to the stack and continue as P .

Client protocol $\text{push}_m s a; (P s')$ starts by requesting a service on the stack's menu server, which will be handled on c . Then, sends the stack, selects the operation push and sends the element a to be

inserted. Then, it receives the updated stack s' , waits for the server to terminate the communication on c and continues as $P s'$. The other client protocols follow a similar pattern.

We now consider two sample systems system^1 and system^2 which are the result of composing the stack with two alternative client codes client_m^1 and client_m^2

$$\begin{aligned} \text{system}^i &\triangleq \text{stack } s \mid s \mid \text{recv } s(X); \text{recv } s(m); ?m; \text{client}_m^i s, i \in \{1, 2\} \\ \text{client}_m^1 &\triangleq \text{cpush}_m s a; \text{cpop}_m s; [P s', Q s' b] \\ \text{client}_m^2 &\triangleq \text{cshare}_m s \text{ in } [\text{cpush}_m s a; (P s'), \text{cpop}_m s; [Q s', R s' b]] \end{aligned}$$

client_m^1 defines a thread that calls methods `push` and `pop` sequentially, whereas client_m^2 call those methods concurrently. As expected, the computation of system^1 is deterministic: after the interactions the client continues as $Q s' b$ where $b = a$ and s' is an empty stack. On the other hand, system^2 evolves to a nondeterministic sum of two systems. In one of these systems, the `pop` operation occurred after the `push`, and so client_m^2 continues as $\text{cshare}_m s' \text{ in } [P s', R s' b]$, where s' is an empty stack and $a = b$. On the hand, if `push` occurs after `pop`, then client_m^2 evolves to $\text{cshare}_m s' \text{ in } [P s', Q s' b]$ where s' is a stack with one element a .

5.2 Queue

We now implement an efficient queue, which uses a pair of lists as its representation type (see [Okasaki 1998]). One of the lists (say l_e) is used for enqueueing and the other (say l_d) for dequeueing. Elements are inserted in the front of l_e and removed from the front of l_d . When l_d is empty it is updated with the reverse of l_e , and then l_e becomes empty. Let $\text{Queue} \triangleq \text{Eview} \wp \text{Dview}$. A queue is an object with two views: one for enqueueing (`Eview`) and another for dequeueing (`Dview`). Similarly to the stack implementation, we use existential types to encode each view

$$\begin{aligned} \text{Eview} &\triangleq \exists X.!(X \multimap E(X)) \otimes X, \text{ where } E(X) \triangleq !A \multimap X \otimes \mathbf{1} \\ \text{Dview} &\triangleq \exists X.!(X \multimap D(X)) \otimes X, \text{ where } D(X) \triangleq \text{Maybe } !A \otimes X \otimes \mathbf{1} \end{aligned}$$

The signatures of $E(X)$ and $D(X)$ are same as for methods `push` and `pop` (respectively) from the previous stack example. Code for $\text{queue}(d) \vdash d : \text{Queue}$, $\text{eview}(e, c_e) \vdash e : \text{Eview}$, $c_e : \overline{\text{List}} \ !A$ and $\text{dview}(d, c_e) \vdash d : \text{Dview}$, $c_e : \overline{\text{List}} \ !A$ is given below

$$\begin{aligned} \text{queue}(d) &\triangleq \text{recv } d(e); \text{cell } c_e(l_e. \text{nil}; l_e) \mid c_e \mid \text{share } c_e \{ \text{eview}(e, c_e) \parallel \text{dview}(d, c_e) \} \\ \text{eview}(e, c_e) &\triangleq \text{send } e (\overline{\text{List}} \ !A); \text{send } e(c_1. !c_1(c); \text{menq } c); \text{fwd } e c_e \\ \text{dview}(d, c_e) &\triangleq \text{send } d (\overline{\text{List}} \ !A \otimes \overline{\text{List}} \ !A); \text{send } d(c_1. !c_1(c); \text{mdeq } c); \\ &\quad \text{send } d(c_d. \text{cell } c_d(l_d. \text{nil}; l_d)); \text{fwd } d c_e \end{aligned}$$

`Queue` receives on channel d name e and continues as a configuration in which the reference c_e , to the initially empty list l_e for enqueueing, is being shared between the two views. $\text{eview}(e, c_e)$ sends on e its representation type (a reference to a list), then sends the persistent server for enqueueing and continues as process that forwards c_e . $\text{dview}(d, c_e)$ sends its representation type (a tensor of of two cells), sends the server for dequeueing, sends c_d and continues as process that forwards c_e .

Notice that the conjunction that puts together the two views to form the `Queue` protocol is a `par` (\wp) and not a `tensor` (\otimes) since the two views share a reference cell and therefore are not orthogonal. Nevertheless, when l_d is nonempty, the operations of enqueueing and dequeueing can be performed in parallel. The complete definition is provided in [Rocha and Caires 2021].

$$\begin{aligned}
\mathcal{N} ::= & \quad x, y, z, \dots \text{ (names)} \\
P, Q ::= & \quad \mathbf{0} \text{ (inaction)} \mid \mathbf{fwd} \ x \ y \text{ (forwarder)} \mid P \parallel Q \text{ (par)} \mid \\
& \quad P \mid x : A \mid Q \text{ (cut)} \mid y.P \mid !x : A \mid Q \text{ (cut!)} \mid \mathbf{share} \ x \ \{P \parallel Q\} \text{ (share)} \mid \\
& \quad P + Q \text{ (sum)} \mid \mathbf{shareL} \ x \ \{P \parallel Q\} \text{ (share-left)} \mid \mathbf{shareR} \ x \ \{P \parallel Q\} \text{ (share-right)} \\
(\mathcal{A}, \mathcal{B} ::=) & \quad \mathbf{close} \ x \text{ (close)} \mid \mathbf{wait} \ x; P \text{ (co-close)} \mid \\
& \quad x.\mathbf{inl}; P \text{ (choose left)} \mid x.\mathbf{inr}; P \text{ (choose right)} \mid \mathbf{case} \ x \ \{\mid \mathbf{inl} : P \mid \mathbf{inr} : Q\} \text{ (offer)} \mid \\
& \quad \mathbf{send} \ x(y.P); Q \text{ (send)} \mid \mathbf{recv} \ x(y); P \text{ (receive)} \mid \\
& \quad !x(y); P \text{ (server)} \mid ?x; P \text{ (activation)} \mid \mathbf{call} \ x(y); P \text{ (call)} \mid \\
& \quad \mathbf{send} \ x \ A; P \text{ (type send)} \mid \mathbf{recv} \ x(X); P \text{ (type receive)} \mid \\
& \quad \mathbf{cell} \ x(y.P) \text{ (cell)} \mid \mathbf{free} \ x; P \text{ (free)} \mid \mathbf{read} \ x(y); P \text{ (read)} \mid \\
& \quad \mathbf{wrt} \ x(y.P); Q \text{ (write)} \mid \mathbf{lock} \ x; P \text{ (lock)} \mid \mathbf{unlock} \ x; P \text{ (unlock)}
\end{aligned}$$
Fig. 4. Processes P .

6 SEMANTICS, TYPE PRESERVATION AND PROGRESS

We present the syntax and the operational semantics of π SSL, which is defined from structural congruence \equiv and reduction \rightarrow . We then prove that the semantics is type preserving and deadlock-free. Since the process syntax depends on types due to polymorphism, types are introduced first.

Definition 6.1 (Types). Types are defined by

$$A, B ::= \mathbf{1} \mid \perp \mid A \oplus B \mid A \& B \mid A \otimes B \mid A \wp B \mid !A \mid ?A \mid \exists X.A \mid \forall X.A \mid \boxplus A \mid \boxminus A \mid \boxtimes A \mid \boxdiv A$$

where X denotes a type variable. Duality \bar{A} is the involution on types defined by

$$\bar{\mathbf{1}} \triangleq \perp \quad \overline{A \otimes B} \triangleq \bar{A} \wp \bar{B} \quad \overline{A \oplus B} \triangleq \bar{A} \& \bar{B} \quad \overline{!A} \triangleq ?\bar{B} \quad \overline{\exists X.A} \triangleq \forall X.\bar{A} \quad \overline{\boxplus A} \triangleq \boxminus \bar{A} \quad \overline{\boxtimes A} \triangleq \boxdiv \bar{A}$$

Definition 6.2 (Processes). The syntax of process terms is defined in Fig. 4.

The static part of the syntax comprises inaction, par, cut, cut!, share, sum, share-left and share-right; the dynamic part includes actions \mathcal{A}, \mathcal{B} , and forwarder. An action is typically a process $\alpha; P$, where α is an action-prefix and P is the continuation. The subject $s(\mathcal{A})$ of an action \mathcal{A} is the leftmost name occurrence of \mathcal{A} . For example, the subject of the action $\mathbf{send} \ x(y.P); Q$ is x .

The expression $P \mid x \mid Q$ binds the name x on processes P and Q . $y.P \mid !x \mid Q$ binds y in P and x in Q . Actions $\mathbf{send} \ x(y.P); Q$, $\mathbf{recv} \ x(y); P$, $!x(y); P$, $\mathbf{call} \ x(y); P$, $\mathbf{cell} \ x(y.P)$, $\mathbf{read} \ x(y); P$, $\mathbf{wrt} \ x(y.P); Q$ bind y on P . All other name occurrences are free. The set of free names of P is denoted by $fn(P)$; if $fn(P) = \emptyset$, we say P is closed. The expressions $\mathbf{recv} \ x(X); P$, $\exists X.A$ and $\forall X.A$ bind the type variable X on process P and type A . Capture-avoiding substitution and α -conversion are defined as usual. We denote by $\{x/y\}P$ the process obtained by replacing the name y by x on P . Similarly, we denote by $\{A/X\}B$ (resp., $\{A/X\}P$) the type (resp., process) obtained by replacing X by A in B (resp., P).

Definition 6.3 (Structural Congruence $P \equiv Q$). Structural congruence \equiv is the least congruence on processes that includes α -conversion and

- commutative laws for forwarder, par, cut, share and sum;
- commuting conversions for each pair of operations par, cut, cut!, share, share-left and sum;
- laws that distribute cut! over par, cut, cut!, share, share-left and share-right;

Share Commuting Conversions

$$\text{share } x \{ \text{free } x; P \parallel \text{free } x; Q \} \equiv \text{free } x; (P \parallel Q) \text{ [FF]}$$

$$\text{share } x \{ \text{free } x; P \parallel x.\alpha; Q \} \equiv x.\alpha; \text{share } x \{ \text{free } x; P \parallel Q \} \text{ [FA]}$$

$$\text{share } x \{ \text{free } x; P \parallel \text{lock } x; Q \} \equiv \text{lock } x; \text{shareR } x \{ \text{free } x; P \parallel Q \} \text{ [FL]}$$

$$\text{share } x \{ x.\alpha; P \parallel x.\beta; Q \} \equiv x.\alpha; \text{share } x \{ P \parallel x.\beta; Q \} + x.\beta; \text{share } x \{ x.\alpha; P \parallel Q \} \text{ [AA]}$$

$$\text{share } x \{ \text{lock } x; P \parallel x.\alpha; Q \} \equiv \text{lock } x; \text{shareL } x \{ P \parallel \alpha; Q \} + x.\alpha; \text{share } x \{ \text{lock } x; P \parallel Q \} \text{ [LA]}$$

$$\text{share } x \{ \text{lock } x; P \parallel \text{lock } x; Q \} \equiv$$

$$\text{lock } x; \text{shareL } x \{ P \parallel \text{lock } x; Q \} + \text{lock } x; \text{shareR } x \{ \text{lock } x; P \parallel Q \} \text{ [LL]}$$

$$\text{shareL } x \{ x.\alpha; P \parallel Q \} \equiv x.\alpha; \text{shareL } x \{ P \parallel Q \} \text{ [leftA]}$$

$$\text{shareL } x \{ \text{unlock } x; P \parallel Q \} \equiv \text{unlock } x; \text{share } x \{ P \parallel Q \} \text{ [leftU]}$$

$$\text{shareL } x \{ P \parallel Q \} \equiv \text{shareR } x \{ Q \parallel P \} \text{ [symm]}$$

Inaction Conversions

$$P \parallel 0 \equiv P \text{ [0M]} \quad 0 + 0 \equiv 0 \text{ [0Sm]}$$

Fig. 5. Selected Structural Congruence Rules $P \equiv Q$.

- laws that distribute par, cut, cut!, share, share-left and share-right over sum;
- and the conversions in Fig. 5.

N.B.: $x.\alpha$ and $x.\beta$ are read/write actions with subject x .

Basic rules of \equiv essentially reflect the expected static laws, along the lines of the structural congruences / conversions in [Caires and Pfenning 2010; Wadler 2012]. For example, the commuting laws between cut and cut and between cut and share are written as

$$\begin{aligned} P \mid x \mid (Q \mid y \mid R) &\equiv (P \mid x \mid Q) \mid y \mid R \text{ [C-CC]} \\ P \mid x \mid (\text{share } y \{ Q \parallel R \}) &\equiv \text{share } y \{ (P \mid x \mid Q) \parallel R \} \text{ [C-CSh]} \end{aligned}$$

provided $x, y \in \text{fn}(Q)$. The laws that distribute cut! over static constructors and that distribute static constructors over sum can be written in the following form

$$\begin{aligned} y.P \mid !x : A \mid (Q * R) &\equiv (y.P \mid !x : A \mid Q) * (y.P \mid !x : A \mid R) \text{ [D-Cut!]} \\ P * (Q + R) &\equiv (P * Q) + (P * R) \text{ [D-Sm]} \end{aligned}$$

where $*$ stands for any of the static constructors par, cut, cut!, share, share-left and share-right.

More interesting are the share commuting conversions of Figure 5, which commute a share with a cell action, a sum of cell actions or a share. In [FF] two concurrent free actions are merged into a single free with the continuations being executed independently. [FA] commutes a share (on x) with read/write action (of subject x) on one thread and a free on the other with the read/write action (free is postponed). Similarly, [FL] postpones a free over a lock. [AA], [LA] and [LL] capture the interleaving laws for the atomic actions read, write and lock: it commutes a share with two concurrent actions with a sum that represents the two possible interleavings, thereby expressing the fundamental interplay between concurrency and nondeterminism. Notice that when a lock is commuted, the share becomes annotated with either an L or R to indicate the component that holds the lock and then only actions from that component are commuted as expressed by [leftA]. Rule [leftU] commutes a share-left with an unlock operation on the left argument with an unlock followed by a share. Finally, rule [symm] commutes a share-left with a share-right. Notice that the argument position is swapped. [symm] allow us to derive a right-version of each share-left rule and vice-versa. For example, by composing [symm] (on both ends) with [leftA] we obtain a

right-version of rule [leftA]

$$\text{shareR } x \{P \parallel x.\alpha; Q\} \equiv \text{shareL } x \{x.\alpha; Q \parallel P\} \equiv x.\alpha; \text{shareL } x \{Q \parallel P\} \equiv x.\alpha; \text{shareR } x \{P \parallel Q\}$$

Interestingly, idempotency of inaction (Fig. 5 [0Sm]) w.r.t. sum is sufficient to derive idempotency of all processes w.r.t. sum, as we have $P \equiv P \parallel 0 \equiv P \parallel (0 + 0) \equiv (P \parallel 0) + (P \parallel 0) \equiv P + P$. Before defining reduction, we introduce static contexts, which are defined by

$$C ::= - \mid C \parallel P \mid P \parallel C \mid C \mid x \mid P \mid P \mid x \mid C \mid y.P \mid !x \mid C \mid \text{share } x \{C \parallel P\} \mid \text{share } x \{P \parallel C\} \mid C + P \mid P + C \mid \text{shareL } x \{C \parallel P\} \mid \text{shareL } x \{P \parallel C\} \mid \text{shareR } x \{P \parallel C\} \mid \text{shareR } x \{C \parallel P\}$$

A static context is a context where the hole is neither guarded by any action nor lies in the server body P of a cut $!y.P \mid x \mid Q$. We write $-$ for the empty context and $C[P]$ for the process obtained by replacing the hole in C by P (notice that in $C[P]$ the context C may bind free names of process P).

Definition 6.4 (Reduction $P \rightarrow Q$). Reduction \rightarrow is the least relation on processes defined by the previously introduced principal cut-reductions and by the rules

$$\frac{P \equiv P' \quad P' \rightarrow Q' \quad Q' \equiv Q}{P \rightarrow Q} [\equiv] \quad \frac{P \rightarrow Q}{C[P] \rightarrow C[Q]} [\text{cong}]$$

where C is an arbitrary static context. Let \Rightarrow stand for the transitive closure of $\rightarrow \cup \equiv$.

Example 6.5. We illustrate our operational semantics by deriving the reduction of Example 3.3 step-by-step

$$\begin{aligned} & \text{share } x \{R \parallel \text{send } z \ x; P\} \mid z \mid \text{recv } z(y); \text{share } y \{Q \parallel S\} && (\equiv \text{ rule [C-CSh]}) \\ & \equiv \text{share } x \{R \parallel \text{send } z \ x; P \mid z \mid \text{recv } z(y); \text{share } y \{Q \parallel S\}\} && (\text{def. free output}) \\ & = \text{share } x \{R \parallel \text{send } z(w.\text{fwd } w \ x); P \mid z \mid \text{recv } z(y); \text{share } y \{Q \parallel S\}\} && (\rightarrow \text{ rule } [\otimes \otimes]) \\ & \rightarrow \text{share } x \{R \parallel P \mid z \mid (\text{fwd } w \ x \mid w \mid \{w/y\} \text{share } y \{Q \parallel S\})\} && (\rightarrow \text{ rule [fwd]}) \\ & \rightarrow \text{share } x \{R \parallel P \mid z \mid \{x/w\}\{w/y\} \text{share } y \{Q \parallel S\}\} && (\text{name substitution}) \\ & = \text{share } x \{R \parallel P \mid z \mid \text{share } x \{\{x/y\}Q \parallel \{x/y\}S\}\} && (\equiv \text{ rule [C-CSh]}) \\ & \equiv P \mid z \mid \text{share } x \{R \parallel \text{share } x \{\{x/y\}Q \parallel \{x/y\}S\}\} \end{aligned}$$

6.1 Subject Reduction for πSSL

We establish the fundamental type safety properties: subject reduction (Theorem 6.6) and progress (Theorem 6.11). In the context of our session typed language these properties entail session fidelity and deadlock-freedom.

THEOREM 6.6 (SUBJECT CONGRUENCE AND SUBJECT REDUCTION FOR πSSL). *Assume $P \vdash \Delta; \Gamma$. Then (1) If $P \equiv Q$ then $Q \vdash \Delta; \Gamma$ and (2) If $P \rightarrow Q$ then $Q \vdash \Delta; \Gamma$.*

PROOF. We verify that all conversions included in \equiv and \rightarrow rules are type-preserving, and conclude by induction on derivations of $P \equiv Q$ and $P \rightarrow Q$. \square

6.2 Progress for πSS

To state and prove progress (Theorem 6.11) we introduce the notion of live process.

Definition 6.7 (Live). A process P is live if $P = C[\mathcal{A}]$ or $P = C[\text{fwd } x \ y]$ for some static context C and action \mathcal{A} .

Intuitively, a process is live if it presents an unguarded action prefix (or forwarder) waiting to interact. To compositionally prove progress we need to characterise the potential interactions of

(possibly open) typed processes, for which we define the following notion of interaction offering, which is akin to the π -calculus observability (cf. [Sangiorgi and Walker 2001]).

Definition 6.8 (P offers an interaction at x). $P \downarrow_x$ is defined by rules

$$\begin{array}{c} \frac{}{\text{fwd } x \ y \ \downarrow_x} \text{ [fwd]} \quad \frac{s(\mathcal{A}) = x}{\mathcal{A} \downarrow_x} \text{ [act]} \quad \frac{P \downarrow_x}{(P \parallel Q) \downarrow_x} \text{ [par]} \quad \frac{P \downarrow_y \quad y \neq x}{(P \ |x| \ Q) \downarrow_y} \text{ [cut]} \\ \\ \frac{Q \downarrow_z \quad z \neq x}{(y.P \ |!x| \ Q) \downarrow_z} \text{ [cut!]} \quad \frac{P \downarrow_y \quad y \neq x}{(\text{share } x \ \{P \parallel Q\}) \downarrow_y} \text{ [share]} \quad \frac{P \downarrow_x}{(P + Q) \downarrow_x} \text{ [sum]} \quad \frac{P \equiv Q \quad Q \downarrow_x}{P \downarrow_x} \text{ [\equiv]} \end{array}$$

The definition of $P \downarrow_x$ is explicitly closed under \equiv and propagates offers on the various operators. For example, a mix offers an interaction on a name x provided one of its arguments does. The interactions of the left argument are explicitly offered by rule [par], whereas those of the right argument are derivable through rule $[\equiv]$ followed by [par], since the mix construct is commutative.

In a share $\text{share } x \ \{P \parallel Q\}$, processes P and Q run in parallel, freely communicating with the external context, but sharing memory cell x . As a consequence, actions on names other than x will always be offered (rule [share]). Additionally, actions on x will be offered if they are offered by both P and Q (Lemma 6.9(1)). For example, $\text{share } x \ \{\text{free } x; P \parallel \text{read } x(y); Q\}$ offers an action on x , since it can be written in the equivalent form $\text{read } x(y); (\text{share } x \ \{\text{free } x; P \parallel Q\})$ by applying the \equiv rule [FA] (Fig. 5). We annotate $P \downarrow_x$ with $P \downarrow_{x:\text{fwd}}$ or $P \downarrow_{x:\text{act}}$, depending on whether the interaction is introduced by a forwarder or an action, respectively.

LEMMA 6.9. *The following properties of $P \downarrow_x$ hold*

- (1) *Let $P \vdash \Delta, x : \Box A; \Gamma, Q \vdash \Delta', x : \Box A; \Gamma, P \downarrow_{x:\text{act}}$ and $Q \downarrow_{x:\text{act}}$. Then, $\text{share } x \ \{P \parallel Q\} \downarrow_{x:\text{act}}$.*
- (2) *Let $P \vdash \Delta, x : \bar{A}; \Gamma, Q \vdash \Delta', x : A; \Gamma, P \downarrow_{x:\text{act}}$ and $Q \downarrow_{x:\text{act}}$. Then, $P \ |x| \ Q$ reduces.*
- (3) *Let $P \vdash \Delta, x : A; \Gamma, Q \vdash \Delta', x : A; \Gamma$ and $P \downarrow_{x:\text{fwd}}$. Then, $P \ |x| \ Q$ reduces.*
- (4) *Let $P \vdash y : \bar{A}; \Gamma, Q \vdash \Delta; \Gamma, x : A$ and $Q \downarrow_x$. Then, $y.P \ |!x| \ Q$ reduces.*
- (5) *Let $P \vdash \Delta, x : A; \Gamma$ and suppose that A is not of the form $\Box B$. If $P \downarrow_{x:\text{fwd}}$, then either $P \downarrow_{y:\text{fwd}}$ for some $y : \bar{A} \in \Delta$ or P reduces.*

PROOF. By induction on the derivations of $P \downarrow_x$. □

Lemma 6.9(5) describes how the interactions offered by a forwarder $\text{fwd } x \ y$ propagate in P . Either name y occurs free, and P offers a forwarder interaction at y , or lies in the scope of a cut $- \ |y| \ -$, in which case a reduction can be triggered (Lemma 6.9(3)). The typing constraint $A \neq \Box B$ excludes processes like $\text{share } y \ \{\text{fwd } x \ y \parallel \text{wait } z; Q\}$, that neither reduce nor offer an interaction at y . Intuitively, the share is suspended on the availability of cell usages at name y . We will see later that this kind of processes will play a key role in defining π SS normal forms (Section 8).

LEMMA 6.10. *Let $P \vdash \Delta; \Gamma$ be a live process. Then either $P \downarrow_x$ or P reduces.*

PROOF. By induction on the typing derivation for $P \vdash \Delta; \Gamma$ and Lemma 6.9. □

THEOREM 6.11 (PROGRESS FOR π SS). *Let $P \vdash \emptyset; \emptyset$ be a live process of π SS. Then, P reduces.*

PROOF. Follows from Lemma 6.10, since $\text{fn}(P) = \emptyset$. □

6.3 Progress for π SSL

We prove that our extension π SSL of π SS with locks also satisfies progress.

Definition 6.12 (P offers an interaction at x). We define $P \downarrow_x$ by extending Definition 6.8 with

$$\frac{P \downarrow_y \quad y \neq x}{(\text{shareL } x \{P \parallel Q\}) \downarrow_y} \text{ [shareL1]} \quad \frac{Q \downarrow_y \quad y \neq x}{(\text{shareL } x \{P \parallel Q\}) \downarrow_y} \text{ [shareL2]}$$

We show the following key properties of the interaction offering relation.

LEMMA 6.13. *The following properties of $P \downarrow_x$ hold*

- (1) *Let $P \vdash \Delta, x : \boxplus A; \Gamma, Q \vdash \Delta', x : \boxminus A; \Gamma$ and $P \downarrow_{x:\text{act}}$. Then, $\text{shareL } x \{P \parallel Q\} \downarrow_{x:\text{act}}$.*
- (2) *Let $P \vdash \Delta, x : A; \Gamma$ and suppose that A is not of the form $\boxplus B$. If $P \downarrow_{x:\text{fwd}}$, then either $P \downarrow_{y:\text{fwd}}$ for some $y : \bar{A} \in \Delta$ or P reduces.*

Actions on the left component of a share-left are always propagated (Lemma 6.13(1)), as expressed by \equiv rules [leftA] and [leftU]. From \equiv [symm] and the fact that $- \downarrow_x$ is closed by \equiv , we obtain that actions of the right component of a share-right are always propagated as well

(1') *Let $P \vdash \Delta, x : \boxminus A; \Gamma, Q \vdash \Delta', x : \boxplus A; \Gamma$ and $Q \downarrow_{x:\text{act}}$. Then, $\text{shareR } x \{P \parallel Q\} \downarrow_{x:\text{act}}$*

THEOREM 6.14 (PROGRESS FOR πSSL). *Let $P \vdash \emptyset; \emptyset$ be a live process of πSSL . Then, P reduces.*

7 CONFLUENCE

In this section we prove that the relation \Rightarrow of language πSSL satisfies the diamond property, thereby substantiating the claim that \Rightarrow can be understood as a proof equivalence relation (cf. PaT). Since $\Rightarrow \triangleq (\rightarrow \cup \equiv)^+$, a natural proof strategy would be demonstrating the diamond property for $\rightarrow \cup \equiv$, but this property fails. To see why, consider the process $P \parallel (Q_1 + Q_2 + Q_2)$ and assume that $P' \leftarrow P \rightarrow P''$. Then, we can form the \rightarrow -reductions

$$\begin{aligned} P \parallel (Q_1 + Q_2 + Q_2) &\rightarrow P' \parallel Q_1 + P' \parallel Q_2 + P \parallel Q_3 \triangleq R \\ P \parallel (Q_1 + Q_2 + Q_2) &\rightarrow P \parallel Q_1 + P'' \parallel Q_2 + P'' \parallel Q_3 \triangleq S \end{aligned}$$

Assume as well that P' and P'' reduce to a common form P^* in one single step: $P' \rightarrow P^* \leftarrow P''$. Note, however, that we need two \rightarrow -reduction steps to bring processes R and S to a common term

$$R \xrightarrow{2} P' \parallel Q_1 + P^* \parallel Q_2 + P'' \parallel Q_3 \xleftarrow{2} S$$

The solution is to allow, in one single step, to perform parallel independent \rightarrow -reductions of sum components (cf. Definition 7.1). This is a well-known technique due to Tait and Martin-Löf and which is often employed when establishing the confluence of calculi that involve nondeterministic sums (see, for example, [Ehrhard and Regnier 2003; Pagani and Tranquilli 2009]).

Definition 7.1 (*Parallel Sum Reduction \twoheadrightarrow*). Let \twoheadrightarrow be the least relation that contains \rightarrow and satisfies the rule [+par] $P \twoheadrightarrow P', Q \twoheadrightarrow Q' \supset P + Q \twoheadrightarrow P' + Q'$.

LEMMA 7.2. *The following (in)equalities hold: (1) $\rightarrow \subseteq \twoheadrightarrow$, (2) $\twoheadrightarrow \subseteq \overset{+}{\rightarrow}$ and (3) $\Rightarrow = (\twoheadrightarrow \cup \equiv)^+$.*

PROOF. (1) follows directly from Definition 7.1. (2) is by induction on \twoheadrightarrow . (1) and (2) imply (3). \square

Since $\Rightarrow = (\twoheadrightarrow \cup \equiv)^+$, we establish our main theorem by showing the diamond property for $\twoheadrightarrow \cup \equiv$ (Lemma 7.6). To handle the complexity of the \equiv -commuting conversions, we show first that we can write each process in a \equiv -normal form by interleaving all the concurrent cell actions and distributing the static operators over sums (Lemma 7.4). This essentially computes a normal form for the left-to-right oriented \equiv -rules that distribute over sum [D-Sm] and that interleave cell usages [AA], [LA] and [LL]. Each \twoheadrightarrow -reduction is then obtained by evaluating the summands of the normal form with a restricted form of reduction (Definition 7.3) that does not manipulate sums (Lemma 7.4) and for which a diamond property is straightforward to establish (Lemma 7.6).

Definition 7.3 (Relation \rightarrow_d). Let \equiv_d be defined by all the rules of \equiv except rules [D-Sm], [AA], [LA], [LL] and [0Sm]. Let \rightarrow_d be the least relation that satisfies all the rules of \rightarrow except [\equiv] and for which the rule [\equiv_d] $P \equiv_d P' \rightarrow_d Q' \equiv_d Q \supset P \rightarrow_d Q$ holds. Furthermore, in rule [cong], the hole in the context C is not guarded by a sum.

LEMMA 7.4. *For each process P there is a sum of processes $\sum_{i \in I} P_i$ s.t. $P \equiv \sum_{i \in I} P_i$ and for which the following property holds*

- (1) *If $P \rightarrow Q$, then exists $\{Q_{ij}\}_{i \in I, j \in \mathcal{J}_i}$ with $Q \equiv \sum_{i \in I, j \in \mathcal{J}_i} Q_{ij}$ and s.t. for all $i \in I, j \in \mathcal{J}_i$ either $P_i \equiv_d Q_{ij}$ or $P_i \rightarrow_d Q_{ij}$.*

PROOF. For each process P , we define its sum expansion $\mathcal{S}(P)$ inductively. In the following, \mathcal{X} stands for $\mathbf{0}$, $\mathbf{fwd} \ x \ y$ or any action. Assume $\mathcal{S}(P) = \sum_{i \in I} P_i$ and $\mathcal{S}(Q) = \sum_{j \in \mathcal{J}} Q_j$ and let $\mathcal{I}_x(P_i, Q_j)$ be an auxiliary map that computes all the interleavings of process $\mathbf{share} \ x \ \{P_i \parallel Q_j\}$. Then

$$\begin{aligned} \mathcal{S}(\mathcal{X}) &\triangleq \mathcal{X} & \mathcal{S}(P \parallel Q) &\triangleq \sum_{i \in I, j \in \mathcal{J}} P_i \parallel Q_j & \mathcal{S}(P \mid x \mid Q) &\triangleq \sum_{i \in I, j \in \mathcal{J}} P_i \mid x \mid Q_j \\ \mathcal{S}(y.P \mid x \mid Q) &\triangleq \sum_{j \in \mathcal{J}} y.P \mid x \mid Q_j & \mathcal{S}(\mathbf{shareL} \ x \ \{P \parallel Q\}) &\triangleq \sum_{i \in I, j \in \mathcal{J}} \mathbf{shareL} \ x \ \{P_i \parallel Q_j\} \\ \mathcal{S}(\mathbf{shareR} \ x \ \{P \parallel Q\}) &\triangleq \sum_{i \in I, j \in \mathcal{J}} \mathbf{shareR} \ x \ \{P_i \parallel Q_j\} \\ \mathcal{S}(\mathbf{share} \ x \ \{P \parallel Q\}) &\triangleq \sum_{i \in I, j \in \mathcal{J}} \mathcal{I}_x(P_i, Q_j) & \mathcal{S}(P + Q) &\triangleq \sum_{i \in I} P_i + \sum_{j \in \mathcal{J}} Q_j \end{aligned}$$

Sum expansions of \equiv -equivalent processes P, Q are related in the following way: for all $i \in I$ there exists $j \in \mathcal{J}$ s.t. $P_i \equiv_d Q_j$. Property (1) is established by induction on $P \rightarrow Q$. \square

COROLLARY 7.5. *Suppose $P \rightarrow Q$ and $P \rightarrow R$. There are sum of processes $\sum_{i \in I} P_i \equiv P, \sum_{i \in I} Q_i \equiv Q$ and $\sum_{i \in I} R_i \equiv R$ s.t. the following property holds*

- (1) *For all $i \in I, P_i (\rightarrow_d \cup \equiv_d) Q_i$ and $P_i (\rightarrow_d \cup \equiv_d) R_i$.*

PROOF. Compute a sum expansion $\{P'_i\}_{1 \leq i \leq n}$ for P (lemma 7.4) and repeat the terms P'_i as many times as necessary (\equiv -equivalence is preserved because sum is idempotent). \square

As opposed to \rightarrow and \Rightarrow , the reductions of \rightarrow_d cannot partially overlap, which justifies

LEMMA 7.6. *If $P \rightarrow_d Q$ and $P \rightarrow_d R$, then either $Q \equiv_d R$ or exists S s.t. $Q \rightarrow_d S$ and $R \rightarrow_d S$.*

PROOF. Write P as $P \equiv_d C[R_1] \dots [R_n]$ where R_1, \dots, R_n lists all \rightarrow_d -redexes of P . We then verify that all \rightarrow_d -reductions at the R_i commute. \square

LEMMA 7.7. *Suppose $P \rightarrow Q$ and $P \rightarrow R$. Either $Q \equiv R$ or exists S s.t. $Q \rightarrow S$ and $R \rightarrow S$.*

PROOF. By applying Corollary 7.5 to $P \rightarrow Q$ and $P \rightarrow R$. \square

THEOREM 7.8 (DIAMOND \Rightarrow). *Suppose $P \Rightarrow Q$ and $P \Rightarrow R$. There exists S s.t. $Q \Rightarrow S$ and $R \Rightarrow S$.*

PROOF. Follows from Lemma 7.7 and Lemma 7.2(3). \square

8 PROOF NORMALISATION AND CUT-ELIMINATION

In this section we study normalisation and cut-elimination for open processes $P \vdash \Delta; \Gamma$ of the language πSS without quantifiers. We show that every process can be reduced to a normal form on which there are no cuts, except on open identity axioms on shared aliases: we call open cells to such trivial cuts. Open cells have a simple form $\mathbf{cell} \ x(y.P) \mid x \mid \mathbf{share} \ x \ \{\mathbf{fwd} \ x \ z \parallel Q\}$, where the shared alias x is forwarded to a free name $z : \square A$. The share in the open cell cannot be converted to a (sum of) \square introduction forms (since $\mathbf{fwd} \ x \ z$ is not a \square introduction form, and offers no structure at z). There is no real redex in an open cell: the share is suspended on the availability of cell usages at z from the environment; justifying open cells as normal forms.

Definition 8.1 (Open Cell). An open cell is a process of the form

$$\text{cell } x(y.P) \mid x \mid \text{share } x \{ \text{fwd } x \ z \ \parallel \ Q \}$$

Definition 8.2 (Normal form). A process is a normal form if it contains no cuts except open cells.

PROPOSITION 8.3 (SUB-FORMULA PROPERTY). *If $P \vdash \Delta; \Gamma$ is normal form, then the derivation only contains sub-formulas (up to duality) of the types in Δ, Γ .*

PROOF. By induction on the typing derivation. \square

To obtain normalisation we introduce a conversion relation \approx on proofs, which includes structural congruence \equiv and reduction \rightarrow , but adds a complete set of commuting conversions for linear logic along standard lines [Caires and Pfenning 2010; Caires et al. 2016; Wadler 2012], and some specific conversions for our new constructs (full definition in the supplementary material).

THEOREM 8.4 (NORMALISATION). *If $P \vdash \Delta; \Gamma$ then there exists normal Q s.t. $P \approx Q$.*

PROOF. We extend Pfenning’s structural cut-elimination technique [Pfenning 1995] to our setting, and explicitly construct a normal form for each proof $P \vdash \Delta; \Gamma$. We show how a normal form $R \approx P \mid x \mid Q$ can be constructed from normal forms P and Q , by lexicographical induction on $(A, \#(P \mid x \mid Q))$, where A is the cut formula (we consider that $\Box B > !B$) and $\#$ is a measure on processes. Instrumentally, we first show that any $\text{share } x \{- \parallel -\}$ is \approx -equivalent to a sum of $\#$ -smaller processes or to an open cell. \square

The following corollary exposes a strong conservativeness and expressiveness result about our language, which follows from the sub-formula property.

COROLLARY 8.5 (CONSERVATIVITY). *Let process $P \vdash \Delta; \Gamma$ be a sequent in classical linear logic with mix. Then there is a cut-free process Q s.t. $P \approx Q$.*

Corollary 8.5 implies that any process in our language with shared state but that implements an interface only manifesting standard propositional linear logic based session types (that is without \boxtimes , \boxplus modalities in its typing) is equivalent to a (possibly non-deterministic and larger) process that *does not use imperative constructs at all*. This normal form expresses the externally observable behaviour of the original stateful open process. For example, consider the conversion

$$\begin{aligned} & \text{cell } x(b.\text{true}_b) \mid x \mid \text{share } x \{ \text{wrt } x(b.\text{false}_b); \text{free } x; \mathbf{0} \parallel \text{read } x(b); \text{free } x; \text{send } y \ b; \text{close } y \} \\ & \approx \text{send } y(z.!\text{z}(b); \text{true}_b); \text{close } y + \text{send } y(z.!\text{z}(b); \text{false}_b); \text{close } y \vdash y :! \text{Bool} \otimes \mathbf{1}; \emptyset \end{aligned}$$

The cut-free process on the right hand side of \approx is behaviourally equivalent to the imperative unreduced one on the left hand side, and summarises its behaviour as a nondeterministic “state-free” process. For the sake of simplicity we opted to prove normalisation of πSS , without polymorphism. Extending the proof with locks can be done along predictable lines. Extending the proof with the impredicative polymorphic types would require a different technique however, such as linear logical relations [Pérez et al. 2012].

9 TYPE CHECKER AND INTERPRETER

We developed a type checker and interpreter in Java (~ 11k loc) using the JavaCC parser generator, which was submitted as a companion artifact for this paper [Rocha and Caires 2021]. All the examples in the paper are validated by the implementation, and we also have developed many others (~ 3k loc), ranging from the definition of inductive datatypes (Naturals, Lists) using System-F style encodings, to concurrent ADTs (Counter, Stack, Queue), as well as a test suite. The supported language includes efficient pragmatic extensions (native basic datatypes int, boolean and string).

Our type checker deals with linearity and context splitting by lazy propagation of context residuals [Hodas and Miller 1994], and imperative update of the typing environments. The interpreter is a fine-grain concurrent runtime system, relying on the `java.util.concurrent.*` package. Our implementation exposes nondeterminism arising from concurrency as real committed nondeterminism, so that the sum operator introduced in the paper, while crucial to establish a PaT model and to characterise the semantics of our language, is not present in our practical runtime system, that is, the implementation commits to one of the summands in sums, while any of such may be nondeterministically picked. The share construct is simply implemented by aliasing. We use reference counting instrumented by the share constructs to garbage collect reference cells. Importantly, structural congruence does not play any explicit role in the implementation model. Types are not used at runtime, but to orient forwarders at state types, and handle polymorphic type variables.

When running complex examples involving the concurrent shareable ADTs, such as the Queue, where we intensively use session processes to implement everything down to basic inductive data types such as lists (along the lines of [Wadler 1990b]), our implementation spawns thousands of short-lived processes. In order to reduce the overhead associated with thread creation/destruction we have opted to manage the execution of concurrent tasks through a cached thread pool.

10 RELATED WORK

In this paper, we develop a propositions-as-types (PaT) interpretation connecting a programming language with concurrency and shared state constructs within a conservative extension of classical linear logic. The notion of PaT goes back to the functional interpretation of intuitionistic logic due to Brouwer, Heyting and Kolmogorov, but was only brought under the spotlight after the famous notes of Curry and Howard [Howard 1980]. It has been since then considered both an intriguing and prolific concept, with many instances and consequences (see [Wadler 2015]).

We base our development on the sessions-as-types interpretation of linear logic [Caires and Pfenning 2010; Caires et al. 2016; Wadler 2012], which yields an expressive typed programming language related to the session π -calculus, while ensuring "for-free" progress (deadlock-freedom), confluence, and normalisation as a consequence of the correspondence between computation and proof reduction. Many works have explored linearity (or affinity) and mutable state, e.g., [Ahmed et al. 2007; Caires and Seco 2013; Nanevski et al. 2008; O'Hearn and Reynolds 2000; Sunshine et al. 2011; Wadler 1990a]. Recently, Rust [Jung et al. 2018a; Matsakis and Klock 2014] has introduced affine types and forms of ownership types [Clarke et al. 1998; DeLine and Fähndrich 2001] to the world of widely adopted programming languages. In our system, a simple form of ownership and ownership transfer results naturally from the underlying linear typing discipline.

We believe that our work is the first to address the challenge of defining a PaT interpretation for shared state, which we have accomplished by internalising nondeterminism in the logic using sums, thus ensuring confluence. From the proof-theoretic side, we have built on ideas from DiLL [Ehrhard 2018] to obtain a logical perspective of the interplay between concurrency and non-determinism as captured by algebraic interleaving laws [Hennessy and Milner 1985]. In the presence of interactions between competing resources, for example, such as concurrent accesses to reference cells as in our language, or matching of quantities of resources in DiLL (e.g., in cut-reduction between co-contraction and contraction), finding an adequate model in which confluence must hold has motivated the introduction of sums (or linear combinations) $P + Q$ of objects [Ehrhard 2018], to be understood as "superposition" or nondeterministic choice of "incompatible" alternatives. The idea of using formal sums to recover, in an algebraic form, confluence and normalisation for an untyped CCS-like process calculus was also explored in [Beffara 2008]. Sums allow confluence of cut-reduction to be preserved, allowing nondeterministic proof-reductions to be understood equationally, cf. behavioural equivalence in process algebras [Hennessy and Milner 1985] or program

equivalence in power-domain denotational semantics [Plotkin 1976]. It is also used crucially in our PaT interpretation, where interleaving of concurrent imperative actions leads to sum of states.

In our system, constructs for modelling state are represented by proof terms. Particularly, our “store” is represented by proof objects itself, thus approaching a pure algebraic theory where imperative computation can be reasoned about equationally, in the spirit of the syntactic store of [Felleisen and Friedman 1989], distinct of the monadic approaches [Peyton Jones and Wadler 1993].

The works [Balzer and Pfenning 2017; Balzer et al. 2019] introduced manifest sharing, the first proposal to represent shared state on top of a session types linear logic interpretation. Although the resulting system is grounded on the Curry-Howard correspondences of [Caires and Pfenning 2010; Caires et al. 2016; Wadler 2012] it departs from a *pure* PaT interpretation in its stateful extension, unlike the work presented in this paper, and explores a different route, based on a special purpose operational semantics, designed to keep track of shared channels availability to control resource acquisition and perform context switching. Therefore, their work does not address how to achieve deadlock freedom or confluence from the basic linear logic type discipline. As a consequence manifest sharing supports programs with linear stored state, such as an imperative linked-list based queue, or with cyclic dependencies, such as the the dining philosophers. These examples are out of the scope of our PaT system, which is nevertheless expressive enough to represent imperative ADTs like stacks and queues within a pure logical approach. Thus both manifest sharing and our PaT approach tackle a common theme with different contributions, directions, and merits.

We further detail our discussion. The key idea of manifest sharing is to serialise concurrent access to linear objects by two modal operators (acquire and release), which induce a stratification [Pfenning and Griffith 2015] of session types in two layers, and provide locking / unlocking behaviour at computation points where a resource invariant holds. Reduction in [Balzer and Pfenning 2017; Balzer et al. 2019] cannot solely be seen as proof simplification, as the operational semantics relies on proof construction / deconstruction steps, where the “wait” computation states are seen as an “incomplete proof”, possibly introducing deadlock. Moreover, in manifest sharing, computation is not confluent, and thus cannot be seen as a proof simplification. This is unlike our system in which confluence holds due to the introduction of sums and co-contraction based sharing.

In [Balzer et al. 2019] the authors further extend the framework of [Balzer and Pfenning 2017] with an additional type system to enforce deadlock freedom, by relying on (extra-logical) partial orders on events to ensure acyclicity [Dezani-Ciancaglini et al. 2008; Lynch 1980]. Those partial orders on locks impose some restrictions on the type system, for example: every process must have released all its acquired resources before communicating along its offering channel and the linear forwarder cannot be typed. Furthermore, in manifest sharing, partial orders on locks have to be manually defined by the programmer. In our case, even in the presence of locks, deadlock freedom results directly from typing and the progress theorem as a consequence of acyclicity in linear logic proofs. Moreover, the partial order approach of [Balzer et al. 2019] does not type processes that spawn a statically undetermined number of shared objects, while in our work such systems are naturally allowed and intrinsically covered by PaT.

Earlier work established relationships between variants of the π -calculus and proof-net reduction in DiLL [Ehrhard and Laurent 2010]. Recently, [Atkey et al. 2016; Kokke et al. 2019] also studied non-determinism in the setting of logical interpretations of session types. The work [Atkey et al. 2016] suggests the introduction of concurrency on extensions of the system of Wadler using conflation, but this carries the cost of losing confluence and deadlock absence as present in the basic system. The work [Kokke et al. 2019] draws on bounded linear logic, by introducing two integer-subscripted modalities that keep track of the number of statically fixed client-server interactions. On the other hand, our reference cells can be shared by an arbitrary number of clients that evolves dynamically (see Example 3.3). Recently, [Qian et al. 2021] have introduced coexponentials to

Classical Linear Logic in order to model interactions between stateful servers and several clients. This work also draws inspiration on DiLL but, as opposed to DiLL and our calculus, they do not internalise non-determinism with sums. In [Caires and Pérez 2017], the authors extend the linear logic interpretation of session types [Caires and Pfenning 2010; Caires et al. 2016; Wadler 2012] with modalities to model effects and non-determinism, following a monadic approach, that excludes the emergence of non-determinism as the effect of races in memory access as we do in this paper.

11 CONCLUDING REMARKS

We introduced a PaT approach to state, in the context of linear logic interpretations of session types. Our model handles first-class mutable and shareable reference cells, and enjoys basic properties of PaT, namely proofs as programs, formulas as types, and evaluation as proof simplification, justified by key meta-theoretical results: preservation, progress, confluence and normalisation.

Our results shed light on the relationship between concurrency and nondeterminism from a logical viewpoint, and reconcile nondeterminism with proof identity by internalising choice. Our concrete implementation collapses nondeterminism into particular choices during execution, while our model still captures all possible choices, cf. the confluence property. We presented an extension that allows critical sections to be represented using locks, while keeping faithful to PaT, and preserving the crucial progress property.

We have developed a type checker and interpreter (using multi-threading), submitted as a companion artifact [Rocha and Caires 2021]. All the examples in the paper are validated by our implementation ranging from the definition of inductive datatypes to concurrent ADTs.

Currently, our approach only handles shared cells holding persistent values which do not depend on free linear names and, as such, we cannot express cyclic data structures. However, we have shown how our language is already quite expressive, see e.g. the implementation of shareable mutable ADTs, such as Stacks and Queues. Extending our framework to handle linear stored state is object of ongoing work and would require a more fine grained analysis of the state manipulation primitives, of the recursive behaviour of cells, and the consideration of sharing protocols [Jung et al. 2018b; Militão et al. 2016]. We would also like to explore how dependent types may express resource invariants and possibly notions of abstract separation [Dinsdale-Young et al. 2013; Jung et al. 2018b; Krishnaswami et al. 2012].

Acknowledgements. We would like to thank Stephanie Balzer, Bernardo Toninho, Nobuko Yoshida and Philip Wadler for insightful discussions. We would like also to thank the anonymous reviewers for their helpful comments and suggestions. This work is supported by NOVA LINES (UID/CEC/04516/2019 and UIDB/04516/2020).

REFERENCES

- Amal Ahmed, Matthew Fluet, and Greg Morrisett. 2007. L_{loc} : A Linear Language with Locations. *Fundam. Inf.* 77, 4 (Dec. 2007), 397–449.
- J.-M. Andreoli. 1992. Logic Programming with Focusing Proofs in Linear Logic. *J. Logic Comput.* 2, 3 (1992), 197–347.
- Robert Atkey, Sam Lindley, and J. Garrett Morris. 2016. *Conflation Confers Concurrency*. Springer International Publishing, Cham, 32–55. https://doi.org/10.1007/978-3-319-30936-1_2
- Stephanie Balzer and Frank Pfenning. 2017. Manifest Sharing with Session Types. *Proc. ACM Program. Lang.* 1, ICFP, Article 37 (Aug. 2017), 29 pages. <https://doi.org/10.1145/3110281>
- Stephanie Balzer, Bernardo Toninho, and Frank Pfenning. 2019. Manifest Deadlock-Freedom for Shared Session Types. In *Programming Languages and Systems*, Luís Caires (Ed.). Springer International Publishing, Cham, 611–639.
- Emmanuel Beffara. 2008. An Algebraic Process Calculus. In *Proceedings of the 2008 23rd Annual IEEE Symposium on Logic in Computer Science (LICS '08)*. IEEE Computer Society, USA, 130–141. <https://doi.org/10.1109/LICS.2008.40>
- Michele Boreale. 1996. On the Expressiveness of Internal Mobility in Name-Passing Calculi. In *Proceedings of the 7th International Conference on Concurrency Theory (CONCUR '96)*. Springer-Verlag, Berlin, Heidelberg, 163–178.

- Luís Caires and Jorge A. Pérez. 2016. Multiparty Session Types Within a Canonical Binary Theory, and Beyond. In *Formal Techniques for Distributed Objects, Components, and Systems*, Elvira Albert and Ivan Lanese (Eds.). Springer International Publishing, Cham, 74–95.
- Luís Caires and Jorge A. Pérez. 2017. Linearity, Control Effects, and Behavioral Types. In *Proceedings of the 26th European Symposium on Programming Languages and Systems - Volume 10201*. Springer-Verlag, Berlin, Heidelberg, 229–259. https://doi.org/10.1007/978-3-662-54434-1_9
- Luís Caires, Jorge A. Pérez, Frank Pfenning, and Bernardo Toninho. 2013. Behavioral Polymorphism and Parametricity in Session-Based Communication. In *Proceedings of the 22nd European Conference on Programming Languages and Systems (Rome, Italy) (ESOP'13)*. Springer-Verlag, Berlin, Heidelberg, 330–349. https://doi.org/10.1007/978-3-642-37036-6_19
- Luís Caires and Frank Pfenning. 2010. Session Types as Intuitionistic Linear Propositions. In *CONCUR 2010 - Concurrency Theory*, Paul Gastin and François Laroussinie (Eds.). Springer Berlin Heidelberg, Berlin, Heidelberg, 222–236.
- Luís Caires, Frank Pfenning, and Bernardo Toninho. 2012. Towards Concurrent Type Theory. In *Proceedings of the 8th ACM SIGPLAN Workshop on Types in Language Design and Implementation (Philadelphia, Pennsylvania, USA) (TLDI '12)*. Association for Computing Machinery, New York, NY, USA, 1–12. <https://doi.org/10.1145/2103786.2103788>
- Luís Caires, Frank Pfenning, and Bernardo Toninho. 2016. Linear logic propositions as session types. *Mathematical Structures in Computer Science* 26, 3 (2016), 367–423. <https://doi.org/10.1017/S0960129514000218>
- Luís Caires and João C. Seco. 2013. The Type Discipline of Behavioral Separation. In *Proceedings of the 40th Annual ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages (Rome, Italy) (POPL '13)*. Association for Computing Machinery, New York, NY, USA, 275–286. <https://doi.org/10.1145/2429069.2429103>
- Marco Carbone, Sam Lindley, Fabrizio Montesi, Carsten Schürmann, and Philip Wadler. 2016. Coherence Generalises Duality: a logical explanation of multiparty session types. In *27 International Conference on Concurrency Theory (CONCUR '16)*. Québec City, Canada. <https://hal.inria.fr/hal-01336600>
- Luca Cardelli. 1991. Typeful Programming. *IFIP State-of-the-Art Reports: Formal Description of Programming Concepts* (1991), 431–507.
- Luca Cardelli and Peter Wegner. 1985. On understanding types, data abstraction, and polymorphism. *ACM Computing Surveys (CSUR)* 17, 4 (1985), 471–523.
- David G. Clarke, John M. Potter, and James Noble. 1998. Ownership Types for Flexible Alias Protection. In *Proceedings of the 13th ACM SIGPLAN Conference on Object-Oriented Programming, Systems, Languages, and Applications (Vancouver, British Columbia, Canada) (OOPSLA '98)*. Association for Computing Machinery, New York, NY, USA, 48–64. <https://doi.org/10.1145/286936.286947>
- Robert DeLine and Manuel Fähndrich. 2001. Enforcing High-Level Protocols in Low-Level Software. In *Proceedings of the ACM SIGPLAN 2001 Conference on Programming Language Design and Implementation (Snowbird, Utah, USA) (PLDI '01)*. Association for Computing Machinery, New York, NY, USA, 59–69. <https://doi.org/10.1145/378795.378811>
- Mariangiola Dezani-Ciancaglini, Ugo de'Liguoro, and Nobuko Yoshida. 2008. On Progress for Structured Communications. In *Trustworthy Global Computing*, Gilles Barthe and Cédric Fournet (Eds.). Springer Berlin Heidelberg, Berlin, Heidelberg, 257–275.
- Thomas Dinsdale-Young, Lars Birkedal, Philippa Gardner, Matthew Parkinson, and Hongseok Yang. 2013. Views: Compositional Reasoning for Concurrent Programs. In *Proceedings of POPL (proceedings of popl ed.)*. <https://www.microsoft.com/en-us/research/publication/views-compositional-reasoning-for-concurrent-programs/>
- Thomas Ehrhard. 2018. An introduction to differential linear logic: proof-nets, models and antiderivatives. *Mathematical Structures in Computer Science* 28, 7 (2018), 995–1060.
- Thomas Ehrhard and Olivier Laurent. 2010. Interpreting a finitary pi-calculus in differential interaction nets. *Inf. Comput.* 208, 6 (2010), 606–633.
- Thomas Ehrhard and Laurent Regnier. 2003. The differential lambda-calculus. *Theoretical Computer Science* 309, 1-3 (2003), 1–41.
- Thomas Ehrhard and Laurent Regnier. 2006. Differential Interaction Nets. *Theor. Comput. Sci.* 364, 2 (2006), 166–195.
- Matthias Felleisen and Daniel P. Friedman. 1989. A Syntactic Theory of Sequential State. *Theor. Comput. Sci.* 69, 3 (1989), 243–287.
- Jean-Yves Girard, Paul Taylor, and Yves Lafont. 1989. *Proofs and Types*. Cambridge University Press, USA.
- Matthew Hennessy and Robin Milner. 1985. Algebraic Laws for Nondeterminism and Concurrency. *J. ACM* 32, 1 (1985), 137–161.
- Joshua S Hodas and Dale Miller. 1994. Logic programming in a fragment of intuitionistic linear logic. *Information and computation* 110, 2 (1994), 327–365.
- Kohei Honda. 1993. Types for dyadic interaction. In *CONCUR'93*, Eike Best (Ed.). Springer Berlin Heidelberg, Berlin, Heidelberg, 509–523.
- Kohei Honda, Vasco T. Vasconcelos, and Makoto Kubo. 1998. Language primitives and type discipline for structured communication-based programming. In *Programming Languages and Systems*, Chris Hankin (Ed.). Springer Berlin

- Heidelberg, Berlin, Heidelberg, 122–138.
- W. A. Howard. 1980. The formulae-as-types notion of construction. In *To H. B. Curry: Essays on Combinatory Logic, Lambda Calculus and Formalism*, J. P. Seldin and J. R. Hindley (Eds.). Academic Press, 479–490.
- Ralf Jung, Jacques-Henri Jourdan, Robbert Krebbers, and Derek Dreyer. 2018a. RustBelt: securing the foundations of the rust programming language. *Proc. ACM Program. Lang.* 2 (2018), 66:1–66:34.
- Ralf Jung, Robbert Krebbers, Jacques-Henri Jourdan, Ales Bizjak, Lars Birkedal, and Derek Dreyer. 2018b. Iris from the ground up: A modular foundation for higher-order concurrent separation logic. *Journal of Functional Programming* 28 (2018), e20. <https://doi.org/10.1017/S0956796818000151>
- Wen Kokke, J. Garrett Morris, and Philip Wadler. 2019. Towards Races in Linear Logic. In *Coordination Models and Languages*, Hanne Riis Nielson and Emilio Tuosto (Eds.). Springer International Publishing, Cham, 37–53.
- Neelakantan R. Krishnaswami, Aaron Turon, Derek Dreyer, and Deepak Garg. 2012. Superficially Substructural Types. In *Proceedings of the 17th ACM SIGPLAN International Conference on Functional Programming (Copenhagen, Denmark) (ICFP '12)*. Association for Computing Machinery, New York, NY, USA, 41–54. <https://doi.org/10.1145/2364527.2364536>
- Nancy A. Lynch. 1980. Fast Allocation of Nearby Resources in a Distributed System. In *Proceedings of the Twelfth Annual ACM Symposium on Theory of Computing (Los Angeles, California, USA) (STOC '80)*. Association for Computing Machinery, New York, NY, USA, 70–81. <https://doi.org/10.1145/800141.804654>
- Nicholas D. Matsakis and Felix S. Klock. 2014. The Rust Language. In *Proceedings of the 2014 ACM SIGAda Annual Conference on High Integrity Language Technology (Portland, Oregon, USA) (HLT '14)*. Association for Computing Machinery, New York, NY, USA, 103–104. <https://doi.org/10.1145/2663171.2663188>
- Filipe Militão, Jonathan Aldrich, and Luís Caires. 2016. Composing Interfering Abstract Protocols. In *30th European Conference on Object-Oriented Programming, ECOOP 2016, July 18–22, 2016, Rome, Italy (LIPICs, Vol. 56)*, Shriram Krishnamurthi and Benjamin S. Lerner (Eds.). Schloss Dagstuhl - Leibniz-Zentrum für Informatik, 16:1–16:26. <https://doi.org/10.4230/LIPICs.ECOOP.2016.16>
- John C Mitchell and Gordon D Plotkin. 1988. Abstract types have existential type. *ACM Transactions on Programming Languages and Systems (TOPLAS)* 10, 3 (1988), 470–502.
- Aleksandar Nanevski, J. Gregory Morrisett, and Lars Birkedal. 2008. Hoare type theory, polymorphism and separation. *J. Funct. Program.* 18, 5-6 (2008), 865–911.
- Peter W. O’Hearn and John C. Reynolds. 2000. From Algol to polymorphic linear lambda-calculus. *J. ACM* 47, 1 (2000), 167–223.
- Chris Okasaki. 1998. *Purely Functional Data Structures*. Cambridge University Press. <https://doi.org/10.1017/CBO9780511530104>
- Michele Pagani and Paolo Tranquilli. 2009. Parallel Reduction in Resource Lambda-Calculus. In *Programming Languages and Systems*, Zhenjiang Hu (Ed.). Springer Berlin Heidelberg, Berlin, Heidelberg, 226–242.
- Jorge A. Pérez, Luís Caires, Frank Pfenning, and Bernardo Toninho. 2012. Linear Logical Relations for Session-Based Concurrency. In *Programming Languages and Systems*, Helmut Seidl (Ed.). Springer Berlin Heidelberg, Berlin, Heidelberg, 539–558.
- Simon L. Peyton Jones and Philip Wadler. 1993. Imperative Functional Programming. In *Proceedings of the 20th ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages (Charleston, South Carolina, USA) (POPL '93)*. Association for Computing Machinery, New York, NY, USA, 71–84. <https://doi.org/10.1145/158511.158524>
- Frank Pfenning. 1995. Structural Cut Elimination. In *Proceedings of the 10th Annual IEEE Symposium on Logic in Computer Science (LICS '95)*. IEEE Computer Society, USA, 156.
- Frank Pfenning and Dennis Griffith. 2015. Polarized Substructural Session Types. In *Foundations of Software Science and Computation Structures*, Andrew Pitts (Ed.). Springer Berlin Heidelberg, Berlin, Heidelberg, 3–22.
- Benjamin C. Pierce. 2002. *Types and Programming Languages* (1st ed.). The MIT Press.
- Gordon D. Plotkin. 1976. A Powerdomain Construction. *SIAM J. Comput.* 5, 3 (1976), 452–487.
- Zesen Qian, G. A. Kavvos, and Lars Birkedal. 2021. Client-Server Sessions in Linear Logic. 5, ICFP, Article 62 (Aug. 2021). <https://doi.org/10.1145/3473567>
- Pedro Rocha and Luís Caires. 2021. Propositions-as-Types and Shared State (Artifact). (May 2021). <https://doi.org/10.5281/zenodo.5037493>
- Davide Sangiorgi. 1999. The Name Discipline of Uniform Receptiveness. *Theor. Comput. Sci.* 221, 1-2 (1999), 457–493.
- Davide Sangiorgi and David Walker. 2001. *PI-Calculus: A Theory of Mobile Processes*. Cambridge University Press, USA.
- Joshua Sunshine, Karl Naden, Sven Stork, Jonathan Aldrich, and Éric Tanter. 2011. First-Class State Change in Plaid. In *Proceedings of the 2011 ACM International Conference on Object Oriented Programming Systems Languages and Applications (Portland, Oregon, USA) (OOPSLA '11)*. Association for Computing Machinery, New York, NY, USA, 713–732. <https://doi.org/10.1145/2048066.2048122>
- Bernardo Toninho, Luís Caires, and Frank Pfenning. 2011. Dependent Session Types via Intuitionistic Linear Type Theory. In *Proceedings of the 13th International ACM SIGPLAN Symposium on Principles and Practices of Declarative Programming*

- (Odense, Denmark) (*PPDP '11*). Association for Computing Machinery, New York, NY, USA, 161–172. <https://doi.org/10.1145/2003476.2003499>
- Bernardo Toninho, Luis Caires, and Frank Pfenning. 2013. Higher-Order Processes, Functions, and Sessions: A Monadic Integration. In *Programming Languages and Systems*, Matthias Felleisen and Philippa Gardner (Eds.). Springer Berlin Heidelberg, Berlin, Heidelberg, 350–369.
- Bernardo Toninho and Nobuko Yoshida. 2021. On Polymorphic Sessions and Functions: A Tale of Two (Fully Abstract) Encodings. *ACM Trans. Program. Lang. Syst.* 43, 2, Article 7 (June 2021), 55 pages. <https://doi.org/10.1145/3457884>
- Philip Wadler. 1990a. Linear Types can Change the World!. In *Proceedings of the IFIP Working Group 2.2, 2.3 Working Conference on Programming Concepts and Methods, 1990*, Manfred Broy (Ed.). North-Holland, 561.
- Philip Wadler. 1990b. Recursive types for free.
- Philip Wadler. 2012. Propositions as Sessions. In *Proceedings of the 17th ACM SIGPLAN International Conference on Functional Programming* (Copenhagen, Denmark) (*ICFP '12*). Association for Computing Machinery, New York, NY, USA, 273–286. <https://doi.org/10.1145/2364527.2364568>
- Philip Wadler. 2015. Propositions as types. *Commun. ACM* 58, 12 (2015), 75–84.

SUPPLEMENTARY MATERIAL

The following sections provide supplementary definitions/proofs.

- A** Lists all the conversions of structural congruence and proves subject congruence and subject reduction for the typed calculus π SSL (Theorem 6.6).
- B** Proves properties about the relation of interaction offering (lemma 6.9) and Lemma 6.10, which entails for progress for π SS (Theorem 6.11).
- C** Extends the proof of progress to π SSL (Theorem 6.14).
- D** Proves auxiliary results necessary to establish confluence of π SSL (Theorem ??), more specifically: Lemma 7.4, Corollary 7.5 and Lemma 7.6.
- E** Proves the normalisation result (Theorem 8.4) and derives the subformula property (Proposition 8.3) and the conservation result (Corollary 8.5).
- F** Lists all the conversions of structural congruence \equiv and reduction \rightarrow with typing annotations.

$$\begin{aligned}
& \text{fwd } x \ y \equiv \text{fwd } y \ x \ [\text{C-fwd}] \quad P \parallel Q \equiv Q \parallel P \ [\text{C-M}] \quad P \ |x : A| \ Q \equiv Q \ |x : \bar{A}| \ P \ [\text{C-C}] \\
& \text{share } x \ \{P \parallel Q\} \equiv \text{share } x \ \{Q \parallel P\} \ [\text{C-Sh}] \quad P + Q \equiv Q + P \ [\text{C-Sm}] \\
& P \ |x : A| \ (Q \parallel R) \equiv (P \ |x : A| \ Q) \parallel R, \ x \in \text{fn}(Q) \ [\text{C-CM}] \\
& P \ |x : A| \ (Q \ |y : B| \ R) \equiv (P \ |x : A| \ Q) \ |y : B| \ R, \ x, y \in \text{fn}(Q) \ [\text{C-CC}] \\
& P \ |x : A| \ (y.Q \ !z : B| \ R) \equiv y.Q \ !z : B| \ (P \ |x : A| \ R), \ z \notin \text{fn}(P) \ [\text{C-CC!}] \\
& P \ |x : A| \ \text{share } y \ \{Q \parallel R\} \equiv \text{share } y \ \{P \ |x : A| \ Q \parallel R\}, \ x, y \in \text{fn}(Q) \ [\text{C-CSh}] \\
& P \ |x : A| \ \text{shareL } y \ \{Q \parallel R\} \equiv \text{shareL } y \ \{P \ |x : A| \ Q \parallel R\}, \ x, y \in \text{fn}(Q) \ [\text{C-CShL1}] \\
& P \ |x : A| \ \text{shareL } y \ \{Q \parallel R\} \equiv \text{shareL } y \ \{Q \parallel P \ |x : A| \ R\}, \ x, y \in \text{fn}(R) \ [\text{C-CShL2}] \\
& \text{share } x \ \{P \parallel (Q \parallel R)\} \equiv \text{share } x \ \{P \parallel Q\} \parallel R, \ x \in \text{fn}(Q) \ [\text{C-ShM}] \\
& \text{share } x \ \{P \parallel (y.Q \ !z : A| \ R)\} \equiv y.Q \ !z : A| \ (\text{share } x \ \{P \parallel R\}), \ z \notin \text{fn}(P) \ [\text{C-ShC!}] \\
& \text{share } x \ \{P \parallel (\text{share } y \ \{Q \parallel R\})\} \equiv \text{share } y \ \{(\text{share } x \ \{P \parallel Q\}) \parallel R\}, \ x, y \in \text{fn}(Q) \ [\text{C-ShSh}] \\
& \text{share } x \ \{P \parallel (\text{shareL } y \ \{Q \parallel R\})\} \equiv \text{shareL } y \ \{(\text{share } x \ \{P \parallel Q\}) \parallel R\}, \ x, y \in \text{fn}(Q) \ [\text{C-ShShL1}] \\
& \text{share } x \ \{P \parallel (\text{shareL } y \ \{Q \parallel R\})\} \equiv \text{shareL } y \ \{Q \parallel (\text{share } x \ \{P \parallel R\})\}, \ x, y \in \text{fn}(R) \ [\text{C-ShShL2}] \\
& y.P \ !x : A| \ (Q \parallel R) \equiv (y.P \ !x : A| \ Q) \parallel R, \ x \notin \text{fn}(R) \ [\text{C-C!M}] \\
& y.P \ !x : A| \ (w.Q \ !z : B| \ R) \equiv w.Q \ !z : B| \ (y.P \ !x : A| \ R), \ x \notin \text{fn}(Q), \ z \notin \text{fn}P \ [\text{C-C!C!}] \\
& y.P \ !x : A| \ (\text{shareL } z \ \{Q \parallel R\}) \equiv \text{shareL } z \ \{(y.P \ !x : A| \ Q) \parallel R\}, \ x \notin \text{fn}(R) \ [\text{C-C!ShL1}] \\
& y.P \ !x : A| \ (\text{shareL } z \ \{Q \parallel R\}) \equiv \text{shareL } z \ \{Q \parallel (y.P \ !x : A| \ R)\}, \ x \notin \text{fn}(Q) \ [\text{C-C!ShL2}] \\
& \text{shareL } x \ \{(P \parallel Q) \parallel R\} \equiv P \parallel (\text{shareL } x \ \{Q \parallel R\}), \ x \in \text{fn}(Q) \ [\text{C-ShLM}] \\
& \text{shareL } x \ \{(\text{shareL } y \ \{P \parallel Q\}) \parallel R\} \equiv \text{shareL } y \ \{(\text{shareL } x \ \{P \parallel R\}) \parallel Q\}, \ x, y \in \text{fn}(P) \ [\text{C-ShLShL1}] \\
& \text{shareL } x \ \{(\text{shareL } y \ \{P \parallel Q\}) \parallel R\} \equiv \text{shareL } y \ \{P \parallel (\text{shareL } x \ \{Q \parallel R\})\}, \ x, y \in \text{fn}(Q) \ [\text{C-ShLShL2}] \\
& P \parallel (Q \parallel R) \equiv (P \parallel Q) \parallel R \ [\text{C-MM}] \quad P + (Q + R) \equiv (P + Q) + R \ [\text{C-SmSm}]
\end{aligned}$$

Fig. 6. \equiv Commutative Laws and Commuting Conversions.

A REDUCTION SEMANTICS AND TYPE PRESERVATION FOR πSSL

In this Section we give a complete definition of πSSL reduction semantics by listing all structural congruence \equiv (Def. A.1) and reduction \rightarrow (Def. A.2) rules. We then prove that all of those rules are

$$\begin{aligned}
y.P \mid x : A \ (Q \parallel R) &\equiv (y.P \mid x : A \ Q) \parallel (y.P \mid x : A \ R) \text{ [D-C!M]} \\
y.P \mid x : A \ (Q \mid z : B \ R) &\equiv (y.P \mid x : A \ Q) \mid z : B \ (y.P \mid x : A \ R) \text{ [D-C!C]} \\
y.P \mid x : A \ (w.Q \mid z : B \ R) &\equiv w.(y.P \mid x : A \ Q) \mid z : B \ (y.P \mid x : A \ R) \text{ [D-C!C!]} \\
y.P \mid x : A \ \text{share } z \{Q \parallel R\} &\equiv \text{share } z \{(y.P \mid x : A \ Q) \parallel (y.P \mid x : A \ R)\} \text{ [D-C!Sh]} \\
y.P \mid x : A \ \text{shareL } z \{Q \parallel R\} &\equiv \text{shareL } z \{(y.P \mid x : A \ Q) \parallel (y.P \mid x : A \ R)\} \text{ [D-C!ShL]} \\
y.P \mid x : A \ (Q + R) &\equiv (y.P \mid x : A \ Q) + (y.P \mid x : A \ R) \text{ [D-C!Sm]} \\
P \parallel (Q + R) &\equiv (P \parallel Q) + (P \parallel R) \text{ [D-MSm]} \\
P \mid x : A \ (Q + R) &\equiv (P \mid x : A \ Q) + (P \mid x : A \ R) \text{ [D-CSm]} \\
\text{share } x \{P \parallel (Q + R)\} &\equiv \text{share } x \{P \parallel Q\} + \text{share } x \{P \parallel R\} \text{ [D-ShSm]} \\
\text{shareL } x \{(P + Q) \parallel R\} &\equiv \text{shareL } x \{P \parallel R\} + \text{shareL } x \{Q \parallel R\} \text{ [D-ShLSm1]} \\
\text{shareL } x \{P \parallel (Q + R)\} &\equiv \text{shareL } x \{P \parallel Q\} + \text{shareL } x \{P \parallel R\} \text{ [D-ShLSm2]}
\end{aligned}$$

Fig. 7. \equiv Distributive Conversions.

$$\begin{aligned}
\text{share } x \{\text{free } x; P \parallel \text{free } x; Q\} &\equiv \text{free } x; (P \parallel Q) \text{ [FF]} \\
\text{share } x \{\text{free } x; P \parallel x.\alpha; Q\} &\equiv x.\alpha; \text{share } x \{\text{free } x; P \parallel Q\} \text{ [FA]} \\
\text{share } x \{\text{free } x; P \parallel \text{lock } x; Q\} &\equiv \text{lock } x; \text{shareR } x \{\text{free } x; P \parallel Q\} \text{ [FL]} \\
\text{share } x \{x.\alpha; P \parallel x.\beta; Q\} &\equiv x.\alpha; \text{share } x \{P \parallel x.\beta; Q\} + x.\beta; \text{share } x \{x.\alpha; P \parallel Q\} \text{ [AA]} \\
\text{share } x \{\text{lock } x; P \parallel x.\alpha; Q\} &\equiv \text{lock } x; \text{shareL } x \{P \parallel \alpha; Q\} + x.\alpha; \text{share } x \{\text{lock } x; P \parallel Q\} \text{ [LA]} \\
\text{share } x \{\text{lock } x; P \parallel \text{lock } x; Q\} &\equiv \\
&\quad \text{lock } x; \text{shareL } x \{P \parallel \text{lock } x; Q\} + \text{lock } x; \text{shareR } x \{\text{lock } x; P \parallel Q\} \text{ [LL]} \\
\text{shareL } x \{x.\alpha; P \parallel Q\} &\equiv x.\alpha; \text{shareL } x \{P \parallel Q\} \text{ [leftA]} \\
\text{shareL } x \{\text{unlock } x; P \parallel Q\} &\equiv \text{unlock } x; \text{share } x \{P \parallel Q\} \text{ [leftU]} \\
\text{shareL } x \{P \parallel Q\} &\equiv \text{shareR } x \{Q \parallel P\} \text{ [symm]} \\
P \parallel \mathbf{0} &\equiv P \text{ [0M]} \quad \mathbf{0} + \mathbf{0} \equiv \mathbf{0} \text{ [0Sm]}
\end{aligned}$$

Fig. 8. \equiv Share Commuting Conversions and Inaction Conversions.

type-preserving, which entails subject reduction (Theorem 6.6). In Section F we list all the rules of \equiv and \rightarrow with type annotations.

Definition A.1 (Structural Congruence $P \equiv Q$). Structural congruence \equiv is the least congruence on processes that includes α -conversion and the rules listed in Figures 6, 7 and 8. N.B.: $x.\alpha$ and $x.\beta$ are read/write actions with subject x .

Definition A.2 (Reduction $P \rightarrow Q$). Reduction \rightarrow is the least relation on processes defined by the rules of Figure 9. N.B.: in rule [cong], C is a static context.

THEOREM 6.6 (SUBJECT CONGRUENCE AND SUBJECT REDUCTION FOR π SSL). *Assume $P \vdash \Delta; \Gamma$. Then (1) If $P \equiv Q$ then $Q \vdash \Delta; \Gamma$ and (2) If $P \rightarrow Q$ then $Q \vdash \Delta; \Gamma$.*

PROOF. (1) The proof is by structural induction on a derivation tree for $P \equiv Q$. We perform case analysis on the root rule of the tree. For each rule $P \equiv Q$, the strategy is to invert a typing derivation $P \vdash \Delta; \Gamma$, obtain the necessary hypothesis and use them to form a typing derivation for $Q \vdash \Delta; \Gamma$. And repeat this process for the symmetric conversion $Q \equiv P$. We illustrate the proof with some cases. A complete listing of the conversions of \equiv with type annotations is provided in figures 15 - 23.

Case [C-M] $P_1 \parallel P_2 \equiv P_2 \parallel P_1$.

By inspecting process $P_1 \parallel P_2$ we conclude that a typing derivation for $P_1 \parallel P_2 \vdash \Delta; \Gamma$ has the form (I)

$$\frac{P_1 \vdash \Delta_1; \Gamma \quad P_2 \vdash \Delta_2; \Gamma}{P_1 \parallel P_2 \vdash \Delta_1, \Delta_2; \Gamma} \text{ [Tmix]}$$

where $\Delta = \Delta_1, \Delta_2$.

This yields hypothesis $P_1 \vdash \Delta_1; \Gamma$ and $P_2 \vdash \Delta_2; \Gamma$.

We can therefore form the typing derivation (II)

$$\frac{P_2 \vdash \Delta_2; \Gamma \quad P_1 \vdash \Delta_1; \Gamma}{P_2 \parallel P_1 \vdash \Delta_2, \Delta_1; \Gamma} \text{ [Tmix]}$$

If we consider the symmetric version of the rule from right to left, by inverting we obtain (II) and by assembling back the hypothesis we obtain (I).

Case [C-CM] $P_1 \mid x : A \mid (P_2 \parallel P_3) \equiv (P_1 \mid x : A \mid P_2) \parallel P_3$, $x \in \text{fn}(P_2)$.

By inspecting process $P_1 \mid x \mid (P_2 \parallel P_3)$ we conclude that a typing derivation for $P_1 \mid x \mid (P_2 \parallel P_3) \vdash \Delta; \Gamma$ has the form (I)

$$\frac{\frac{P_1 \vdash \Delta_1, x : A; \Gamma \quad \frac{P_2 \vdash \Delta_2, x : \bar{A}; \Gamma \quad P_3 \vdash \Delta_3; \Gamma}{P_2 \parallel P_3 \vdash \Delta_2, \Delta_3, x : \bar{A}; \Gamma} \text{ [Tmix]}}{P_1 \mid x : A \mid (P_2 \parallel P_3) \vdash \Delta_1, \Delta_2, \Delta_3; \Gamma} \text{ [Tcut]}}$$

where $\Delta = \Delta_1, \Delta_2, \Delta_3$.

Observe that the proviso $x \in \text{fn}(P_2)$ allow us to conclude that x lies in the linear typing context of P_2 and not in the linear typing context of P_3 .

This yields hypothesis $P_1 \vdash \Delta_1, x : A; \Gamma$, $P_2 \vdash \Delta_2, x : \bar{A}; \Gamma$ and $P_3 \vdash \Delta_3; \Gamma$.

We can therefore form the typing derivation (II)

$$\frac{\frac{P_1 \vdash \Delta_1, x : A; \Gamma \quad \frac{P_2 \vdash \Delta_2, x : \bar{A}; \Gamma}{P_2 \parallel P_3 \vdash \Delta_2, \Delta_3, x : \bar{A}; \Gamma} \text{ [Tcut]}}{P_1 \mid x : A \mid (P_2 \parallel P_3) \vdash \Delta_1, \Delta_2, \Delta_3; \Gamma} \text{ [Tcut]}}{\frac{P_1 \mid x : A \mid (P_2 \parallel P_3) \vdash \Delta_1, \Delta_2, \Delta_3; \Gamma \quad P_3 \vdash \Delta_3; \Gamma}{(P_1 \mid x : A \mid P_2) \parallel P_3 \vdash \Delta_1, \Delta_2, \Delta_3; \Gamma} \text{ [Tmix]}}$$

If we consider the symmetric version of the rule, from right to left, by inverting we obtain (II) and by assembling back the hypothesis we obtain (I). Observe that, in this case, the proviso is this direction the proviso is superfluous.

Case [D-C!M] $y.P \text{!}x : A \mid (Q_1 \parallel Q_2) \equiv (y.P \text{!}x : A \mid Q_1) \parallel (y.P \text{!}x : A \mid Q_2)$.

We analyse first the conversion from left to right.

By inspecting process $y.P \text{!}x : A \mid (Q_1 \parallel Q_2)$ we conclude that a typing derivation for $y.P \text{!}x : A \mid (Q_1 \parallel Q_2) \vdash \Delta; \Gamma$ has the form (I)

$$\frac{P \vdash y : A; \Gamma \quad \frac{Q_1 \vdash \Delta_1; \Gamma, x : \bar{A} \quad Q_2 \vdash \Delta_2; \Gamma, x : \bar{A}}{Q_1 \parallel Q_2 \vdash \Delta_1, \Delta_2; \Gamma, x : \bar{A}} \text{[Tmix]}}{y.P \text{!}x : A \mid (Q_1 \parallel Q_2) \vdash \Delta_1, \Delta_2; \Gamma} \text{[Tcut!]}$$

where $\Delta = \Delta_1, \Delta_2$.

This yields hypothesis $P \vdash y : A; \Gamma, Q_1 \vdash \Delta_1; \Gamma, x : \bar{A}$ and $Q_2 \vdash \Delta_2; \Gamma, x : \bar{A}$.

We can therefore form the typing derivation (II)

$$\frac{\frac{P \vdash y : A; \Gamma \quad Q_1 \vdash \Delta_1; \Gamma, x : \bar{A}}{y.P \text{!}x : A \mid Q_1 \vdash \Delta_1; \Gamma} \quad \frac{P \vdash yA; \Gamma \quad Q_2 \vdash \Delta_2; \Gamma, x : \bar{A}}{y.P \text{!}x : A \mid Q_2 \vdash \Delta_2; \Gamma}}{(y.P \text{!}x : A \mid Q_1) \parallel (y.P \text{!}x : A \mid Q_2) \vdash \Delta_1, \Delta_2; \Gamma}$$

Now, we analyse the conversion from right to left.

By inspecting process $(y.P \text{!}x : A \mid Q_1) \parallel (y.P \text{!}x : A \mid Q_2)$ we conclude that a typing derivation for $(y.P \text{!}x : A \mid Q_1) \parallel (y.P \text{!}x : A \mid Q_2) \vdash \Delta; \Gamma$ has the form (III), where $\Delta = \Delta_1, \Delta_2$. This yields hypothesis $P \vdash y : A; \Gamma, Q_1 \vdash \Delta_1; \Gamma, x : \bar{A}$ and $Q_2 \vdash \Delta_2; \Gamma, x : \bar{A}$. We can therefore from the typing derivation (I). Notice that, in the right-hand-side of the equation, the type annotations of the two unrestricted cuts agree. This is crucial for ensuring type preservation of the conversion from right to left.

Case [AA] share $x \{x.\alpha; P \parallel x.\beta; Q\} \equiv x.\alpha; \text{share } x \{P \parallel \beta; Q\} + x.\beta; \text{share } x \{\alpha; P \parallel Q\}$.

We show that commuting a read or write prefix of subject x with a share $\text{share } x \{x.\alpha; P \parallel Q\} \vdash \Delta; \Gamma \supset x.\alpha; \text{share } x \{P \parallel Q\} \vdash \Delta; \Gamma$ is type-preserving. This justifies automatically conversion [AA] (and also [FA]).

Assume w.l.o.g. $x.\alpha = \text{read } x(y)$. By inspecting process $\text{share } x \{\text{read } x(y); P \parallel Q\}$ we conclude that a typing derivation for $\text{share } x \{\text{read } x(y); P \parallel Q\} \vdash \Delta; \Gamma$ has the form (I)

$$\frac{\frac{P \vdash \Delta_1, y : ?A, x : \Box A; \Gamma}{\text{read } x(y); P \vdash \Delta_1, x : \Box A; \Gamma} \quad Q \vdash \Delta_2, x : \Box A; \Gamma}{\text{share } x \{\text{read } x(y); P \parallel Q\} \vdash \Delta_1, \Delta_2, x : \Box A; \Gamma}$$

where $\Delta = \Delta_1, \Delta_2, x : \Box A$.

We can therefore form the typing derivation (II)

$$\frac{\frac{P \vdash \Delta_1, y : ?A, x : \Box A; \Gamma \quad Q \vdash \Delta_2, x : \Box A; \Gamma}{\text{share } x \{P \parallel Q\} \vdash \Delta_1, \Delta_2, y : ?A, x : \Box A; \Gamma}}{\text{read } x(y); \text{share } x \{P \parallel Q\} \vdash \Delta_1, \Delta_2, x : \Box A; \Gamma}$$

If we consider the symmetric version of the rule from right to left, by inverting we obtain (II) and by assembling back the hypothesis we obtain (I).

(2) The proof is by structural induction on a derivation tree for $P \rightarrow Q$. We perform case analysis on the root rule. For each rule $P \rightarrow Q$, the strategy is to invert the typing derivation $P \vdash \Delta; \Gamma$, obtain the necessary hypothesis and use them to form a typing derivation for $Q \vdash \Delta; \Gamma$. We list the conversions on typing derivations thus obtained in figures 24-26. We illustrate the proof with following cases

Case $[1\perp]$ $\text{close } x \mid x \mid \text{wait } x; P \rightarrow P$

By inspecting process $\text{close } x \mid x \mid \text{wait } x; P$ we conclude that a typing derivation tree for $\text{close } x \mid x \mid \text{wait } x; P \vdash \Delta; \Gamma$ has the form

$$\frac{\frac{}{\text{close } x \vdash x : \mathbf{1}; \Gamma} [\text{T1}] \quad \frac{P \vdash \Delta; \Gamma}{\text{wait } x; P \vdash \Delta, x : \perp; \Gamma} [\text{T}\perp]}{\text{close } x \mid x \mid \text{wait } x; P \vdash \Delta; \Gamma} [\text{Tcut}]$$

This implies that $P \vdash \Delta; \Gamma$.

Case $[\exists\forall]$ $\text{send } x A; P \mid x \mid \text{recv } x(X); Q \rightarrow P \mid x \mid (\{A/X\}Q)$.

By inversion on typing we conclude that

$$\frac{\frac{P \vdash \Delta_1, x : \{A/X\}\bar{B}; \Gamma}{\text{send } x A; P \vdash \Delta_1, x : \exists X.\bar{B}; \Gamma} \quad \frac{Q \vdash \Delta_2, x : B; \Gamma}{\text{recv } x(X); Q \vdash \Delta_2, x : \forall X.B; \Gamma}}{\text{send } x A; P \mid x \mid \text{recv } x(X); Q \vdash \Delta_1, \Delta_2; \Gamma}$$

where $\Delta = \Delta_1, \Delta_2$.

Hence, we obtain the hypothesis $P \vdash \Delta_1, x : \{A/X\}\bar{B}; \Gamma$ and $Q \vdash \Delta_2, x : B; \Gamma$.

We have $\{A/X\}Q \vdash \{A/X\}\Delta_2, x : \{A/X\}B; \{A/X\}\Gamma$. However, the proviso of rule $[\text{TV}]$ ensures that $X \notin \text{fv}(\Delta_2), \text{fv}(\Gamma)$. Hence, $\{A/X\}\Delta_2 = \Delta_2$ and $\{A/X\}\Gamma = \Gamma$.

Therefore

$$\frac{P \vdash \Delta_1, x : \{A/X\}\bar{B}; \Gamma \quad \{A/X\}Q \vdash \Delta_2, x : \{A/X\}B; \Gamma}{P \mid x \mid \{A/X\}Q \vdash \Delta_1, \Delta_2; \Gamma}$$

Case $[\square\square\text{r}]$ $\text{cell } x(y.P) \mid x \mid \text{read } x(z); Q \rightarrow \{z/y\}P \mid z \mid (\text{cell } x(y.P) \mid x \mid Q)$.

By inspecting process $\text{cell } x(y.P) \mid x \mid \text{read } x(z); Q$ we conclude that a typing derivation tree for $\text{cell } x(y.P) \mid x \mid \text{read } x(z); Q \vdash \Delta; \Gamma$ has the form

$$\frac{\frac{P \vdash y : \bar{A}; \Gamma}{\text{cell } x(y.P) \vdash x : \square\bar{A}; \Gamma} [\text{Tcell}] \quad \frac{Q \vdash \Delta, z : ?A, x : \square A; \Gamma}{\text{read } x(z); Q \vdash \Delta, x : \square A; \Gamma} [\text{Tread}]}{\text{cell } x(y.P) \mid x \mid \text{read } x(z); Q \vdash \Delta; \Gamma} [\text{Tcut}]$$

from which we obtain the hypothesis $P \vdash y : \bar{A}; \Gamma$ and $Q \vdash \Delta, z : ?A, x : \square A; \Gamma$.

Then

$$\frac{\frac{P \vdash y : \bar{A}; \Gamma}{\text{cell } x(y.P) \vdash x : \square\bar{A}; \Gamma} [\text{Tcell}] \quad \frac{Q \vdash \Delta, z : ?A, x : \square A; \Gamma}{\text{cell } x(y.P) \mid x \mid Q \vdash \Delta, z : ?A; \Gamma} [\text{Tcut}]}{\frac{\{z/y\}P \vdash z : \bar{A}; \Gamma}{\{z/y\}P \mid z \mid (\text{cell } x(y.P) \mid x \mid Q) \vdash \Delta; \Gamma} [\text{Tcut}]}$$

Case $[\equiv]$ $P \equiv P' \quad P' \rightarrow Q' \quad Q' \equiv Q \quad \supset \quad P \rightarrow Q$.

$$\begin{aligned}
& \text{fwd } x \ y \ |y : A| \ P \rightarrow \{x/y\}P \ [\text{fwd}] \quad \text{close } x \ |x : \mathbf{1}| \ \text{wait } x; P \rightarrow P \ [\mathbf{1}\perp] \\
& \text{send } x(y.P); Q \ |x : A \otimes B| \ \text{recv } x(z); R \rightarrow Q \ |x : B| \ (P \ |y : A| \ \{y/z\}R) \ [\otimes\otimes] \\
& \text{case } x \ \{|inl : P \ |inr : Q\} \ |x : A \ \& \ B| \ x.inl; R \rightarrow P \ |x : A| \ R \ [\&\oplus_l] \\
& \text{case } x \ \{|inl : P \ |inr : Q\} \ |x : A \ \& \ B| \ x.inr; R \rightarrow Q \ |x : B| \ R \ [\&\oplus_r] \\
& !x(y); P \ |x : !A| \ ?x; Q \rightarrow y.P \ !x : A| \ Q \ [!?] \\
& y.P \ !x : A| \ \text{call } x(z); Q \rightarrow \{z/y\}P \ |z : A| \ (y.P \ !x : A| \ Q) \ [\text{call}] \\
& \text{send } x \ A; P \ |x : \exists X. B| \ \text{recv } x(X); Q \rightarrow P \ |x : \{A/X\}B| \ \{A/X\}Q \ [\exists\forall] \\
& \text{cell } x(y.P) \ |x : \boxplus A| \ \text{free } x; Q \rightarrow Q \ [\boxplus\boxminus f] \\
& \text{cell } x(y.P) \ |x : \boxplus A| \ \text{read } x(z); Q \rightarrow \{z/y\}P \ |z : !A| \ ((\text{cell } x(y.P)) \ |x : \boxplus A| \ Q) \ [\boxplus\boxminus r] \\
& \text{cell } x(y.P) \ |x : \boxplus A| \ \text{wrt } x(z.Q); R \rightarrow \text{cell } x(z.Q) \ |x : \boxplus A| \ R \ [\boxplus\boxminus w] \\
& \text{cell } x(y.P) \ |x : \boxplus A| \ \text{lock } x; Q \rightarrow \text{cell } x(y.P) \ |x : \boxtimes A| \ Q \ [\boxtimes\boxminus] \\
& \text{cell } x(y.P) \ |x : \boxtimes A| \ \text{unlock } x; Q \rightarrow \text{cell } x(y.P) \ |x : \boxplus A| \ Q \ [\boxtimes\boxplus u] \\
& \text{cell } x(y.P) \ |x : \boxtimes A| \ \text{read } x(z); Q \rightarrow \{z/y\}P \ |z : !A| \ ((\text{cell } x(y.P)) \ |x : \boxtimes A| \ Q) \ [\boxtimes\boxtimes r] \\
& \text{cell } x(y.P) \ |x : \boxtimes A| \ \text{wrt } x(z.Q); R \rightarrow \text{cell } x(z.Q) \ |x : \boxtimes A| \ R \ [\boxtimes\boxtimes w] \\
& P \equiv \Rightarrow Q \supset P \rightarrow Q \ [\equiv] \quad P \rightarrow Q \supset C[P] \rightarrow C[Q] \ [\text{cong}]
\end{aligned}$$
Fig. 9. Reduction $P \rightarrow Q$.

(1) applied to $P \vdash \Delta; \Gamma$ and $P \equiv P'$ yields $P' \vdash \Delta; \Gamma$.

By induction on $P' \rightarrow Q'$ we conclude that $Q' \vdash \Delta; \Gamma$.

By applying (1) again, this time to $Q' \vdash \Delta; \Gamma$ and $Q' \equiv Q$, we obtain $Q \vdash \Delta; \Gamma$. □

B PROGRESS

The goal of this section is to prove the progress property for the language πSS . We prove lemma 6.10 in B.3, from which progress follows as a direct consequence. The proof of lemma 6.10 relies on some auxiliary properties about liveness (section B.1) and interaction offering (section B.2).

B.1 Liveness

LEMMA B.1. *If $P \vdash \Delta; \Gamma$ and $\Delta \neq \emptyset$, then P is live.*

PROOF. The proof is by induction on the depth of the derivation tree $P \vdash \Delta; \Gamma$. We perform case analysis on the root rule.

Case [T0]

By inversion

$$\frac{}{\mathbf{0} \vdash \emptyset; \Gamma}$$

where $P = \mathbf{0}$ and $\Delta = \emptyset$.

Holds vacuously because $\Delta = \emptyset$.

Case [Tmix]

By inversion

$$\frac{P_1 \vdash \Delta_1; \Gamma \quad P_2 \vdash \Delta_2; \Gamma}{P_1 \parallel P_2 \vdash \Delta_1, \Delta_2; \Gamma}$$

where $P = P_1 \parallel P_2$ and $\Delta = \Delta_1, \Delta_2$.

Since $\Delta \neq \emptyset$, then either $\Delta_1 \neq \emptyset$ or $\Delta_2 \neq \emptyset$.

Assume w.l.o.g. that $\Delta_1 \neq \emptyset$.

By induction on $P_1 \vdash \Delta_1; \Gamma$ we conclude that P_1 is live. Hence, $P_1 \parallel P_2$ is live.

Case [Tfwd]

By inversion

$$\overline{\text{fwd } x \ y \vdash x : A, y : \bar{A}; \Gamma}$$

where $P = \text{fwd } x \ y$ and $\Delta = x : A, y : \bar{A}$.

Observe that $P = C[\text{fwd } x \ y]$, where C is the empty context. Hence, P is live.

Cases [T1], [T \perp], [T \otimes], [T \otimes], [T \otimes_r], [T \oplus_l], [T \oplus_r], [T $\&$], [T $?$], [Tcopy], [T!], [T \exists], [TV], [Tcell], [Tfree], [Tread] and [Twrite] are handled similarly to case [Tfwd].

Case [Tcut]

By inversion

$$\frac{P_1 \vdash \Delta_1, x : \bar{A}; \Gamma \quad P_2 \vdash \Delta_2, x : A; \Gamma}{P_1 \ |x| P_2 \vdash \Delta_1, \Delta_2; \Gamma}$$

where $P = P_1 \ |x| P_2$ and $\Delta = \Delta_1, \Delta_2$.

Observe that both P_1 and P_2 have a nonempty linear typing context. Hence, by induction, both P_1 and P_2 are live.

However, we just need to assume one of them to be live, in order to infer liveness of $P_1 \ |x| P_2$.

Case [Tcut!]

By inversion

$$\frac{P_1 \vdash y : \bar{A}; \Gamma \quad P_2 \vdash \Delta; \Gamma, x : A}{y.P_1 \ |!x| P_2 \vdash \Delta; \Gamma}$$

where $P = y.P_1 \ |!x| P_2$.

By induction on $P_2 \vdash \Delta; \Gamma, x : A$ we conclude that P_2 is live.

Hence, $y.P_1 \ |!x| P_2$ is live.

Case [Tshare] is handled similarly to case [Tcut].

Case [Tsum]

By inversion

$$\frac{P_1 \vdash \Delta; \Gamma \quad P_2 \vdash \Delta; \Gamma}{P_1 + P_2 \vdash \Delta; \Gamma}$$

where $P = P_1 + P_2$.

By induction on $P_1 \vdash \Delta; \Gamma$ and $P_2 \vdash \Delta; \Gamma$ we conclude that both P_1 and P_2 are live.

However, we just need to assume one of them to be live, in order to infer liveness of $P_1 + P_2$. \square

B.2 Action Offering $P \downarrow_x$

After recalling the relation of interaction offering $P \downarrow_{x:\sigma}$ (definition 6.8), we prove the following properties

- Let $P \vdash \Delta, x : \boxplus A; \Gamma$ and $Q \vdash \Delta', x : \boxplus A; \Gamma$ be processes for which $P \downarrow_{x:\text{act}}$ and $Q \downarrow_{x:\text{act}}$. Then, $\text{share } x \{P \parallel Q\} \downarrow_{x:\text{act}}$ (lemma 6.9(1)).
- Let $P \vdash \Delta, x : \bar{A}; \Gamma$ and $Q \vdash \Delta', x : A; \Gamma$ be processes for which $P \downarrow_{x:\text{act}}$ and $Q \downarrow_{x:\text{act}}$. Then, $P \ |x| Q$ reduces (lemma 6.9(2)).

$$\begin{array}{c}
\frac{}{\text{fwd } x \ y \downarrow_{x:\text{fwd}}} \text{ [fwd]} \quad \frac{s(\mathcal{A}) = x}{\mathcal{A} \downarrow_{x:\text{act}}} \text{ [act]} \quad \frac{P \downarrow_{x:\sigma}}{(P \parallel Q) \downarrow_{x:\sigma}} \text{ [par]} \\
\\
\frac{P \downarrow_{y:\sigma} \quad y \neq x}{(P \mid x \mid Q) \downarrow_{y:\sigma}} \text{ [cut]} \quad \frac{Q \downarrow_{z:\sigma} \quad z \neq x}{(y.P \mid !x \mid Q) \downarrow_{z:\sigma}} \text{ [cut!]} \quad \frac{P \downarrow_{x:\sigma}}{(P + Q) \downarrow_{x:\sigma}} \text{ [sum]} \\
\\
\frac{P \downarrow_{y:\sigma} \quad y \neq x}{(\text{share } x \{P \parallel Q\}) \downarrow_{y:\sigma}} \text{ [share]} \quad \frac{P \equiv Q \quad Q \downarrow_{x:\sigma}}{P \downarrow_{x:\sigma}} \text{ [\equiv]}
\end{array}$$

Fig. 10. $P \downarrow_{x:\sigma}$, $\sigma \in \{\text{fwd}, \text{act}\}$

- Let $P \vdash \Delta, x : A; \Gamma$, $Q \vdash \Delta', x : A; \Gamma$ be processes for which $P \downarrow_{x:\text{fwd}}$. Then, $P \mid x \mid Q$ reduces (lemma 6.9(3)).
- Let $P \vdash y : \bar{A}; \Gamma$ and $Q \vdash \Delta; \Gamma, x : A$ be processes for which $Q \downarrow_x$. Then, $y.P \mid !x \mid Q$ reduces (lemma []).
- Let $P \vdash \Delta, x : A; \Gamma$ and suppose that $A \neq \boxplus B$. If $P \downarrow_{x:\text{fwd}}$, then either (i) $P \downarrow_{y:\text{fwd}}$ for some $y : \bar{A} \in \Delta$ or (ii) P reduces (lemma 6.9(5)).

Definition B.2 ($P \downarrow_{x:\sigma}$). The relation $P \downarrow_{x:\sigma}$ is defined by the rules of figure 10. We read $P \downarrow_{x:\text{act}}$ (resp., $P \downarrow_{x:\text{fwd}}$) as P offers an action (resp. a link) at name x . Define $P \downarrow_x$ as the union of $P \downarrow_{x:\text{act}}$ and $P \downarrow_{x:\text{fwd}}$.

LEMMA 6.9(1). Let $P \vdash \Delta, x : \boxplus A; \Gamma$ and $Q \vdash \Delta', x : \boxplus A; \Gamma$ be processes for which $P \downarrow_{x:\text{act}}$ and $Q \downarrow_{x:\text{act}}$. Then, $\text{share } x \{P \parallel Q\} \downarrow_{x:\text{act}}$

PROOF. The proof is by induction on the sum of the depths of derivation trees for $P \downarrow_{x:\text{act}}$ and $Q \downarrow_{x:\text{act}}$. We perform case analysis on the root rule of each tree. The cases are organised in the following groups

Group A The root rule of both $P \downarrow_{x:\text{act}}$ and $Q \downarrow_{x:\text{act}}$ is [act].

Group B Either the root rule of $P \downarrow_{x:\text{act}}$ or of $Q \downarrow_{x:\text{act}}$ is a [par], [cut], [cut!], [share] or [sum].

Group C Either the root rule of $P \downarrow_{x:\text{act}}$ or of $Q \downarrow_{x:\text{act}}$ is [\equiv].

For cases of group A, we apply one of the share commuting conversions [FF], [FA] or [AA].

As for group B, the strategy is to first distribute the share and then apply the inductive hypothesis. We analyse the root rule of $P \downarrow_{x:\text{act}}$. The argument goes by symmetry to the root rule of $Q \downarrow_{x:\text{act}}$. Similarly, for group C, we consider only the case in which the root rule of $P \downarrow_{x:\text{act}}$ is [\equiv].

Group A We have

$$\frac{s(\mathcal{A}) = x}{\mathcal{A} \downarrow_{x:\text{act}}} \text{ [act]} \quad \frac{s(\mathcal{B}) = x}{\mathcal{B} \downarrow_{x:\text{act}}} \text{ [act]}$$

where $P = \mathcal{A}$ and $Q = \mathcal{B}$.

Since the subject of both actions, x , has the type $\boxplus A$ (in the linear typing context), we conclude that $P = \alpha; P'$ and $Q = \beta; Q'$, where the prefixes α and β are free, read or write prefixes with subject x . These are the cases to consider

Case $\alpha = \beta = x.\text{free}$

Observe that

$$\begin{aligned} \text{share } x \{P \parallel Q\} &= \text{share } x \{\text{free } x; P' \parallel \text{free } x; Q'\} \\ &\equiv \text{free } x; \underbrace{(P' \parallel Q')}_R \end{aligned} \quad (\equiv [\text{FF}])$$

Hence

$$\frac{\text{share } x \{P \parallel Q\} \equiv \text{free } x; R \quad \frac{s(\text{free } x; R) = x}{\text{free } x; R \downarrow_{x:\text{act}}} [\text{act}]}{\text{share } x \{P \parallel Q\} \downarrow_{x:\text{act}}} [\equiv]$$

Case $\alpha = x.\text{free}$ and $\beta \neq x.\text{free}$

Observe that

$$\text{share } x \{\text{free } x; P' \parallel \beta; Q'\} \equiv \beta; \underbrace{\text{share } x \{\text{free } x; P' \parallel Q'\}}_R \quad (\equiv [\text{FA}])$$

Hence

$$\frac{\text{share } x \{P \parallel Q\} \equiv \beta; R \quad \frac{s(\beta; R) = x}{\beta; R \downarrow_{x:\text{act}}} [\text{act}]}{\text{share } x \{P \parallel Q\} \downarrow_{x:\text{act}}} [\equiv]$$

Case $\alpha, \beta \neq x.\text{free}$

Observe that

$$\begin{aligned} \text{share } x \{\alpha; P' \parallel \beta; Q'\} &\equiv \alpha; R_1 + \beta; R_2, \text{ where} \\ R_1 &= \text{share } x \{P' \parallel \beta; Q'\} \\ R_2 &= \text{share } x \{\alpha; P' \parallel Q'\} \end{aligned} \quad (\equiv [\text{AA}])$$

Hence

$$\frac{\text{share } x \{P \parallel Q\} \equiv \alpha; R_1 + \beta; R_2 \quad \frac{\frac{s(\alpha; R_1) = x}{\alpha; R_1 \downarrow_{x:\text{act}}} [\text{act}]}{(\alpha; R_1 + \beta; R_2) \downarrow_{x:\text{act}}} [\text{sum}]}{\text{share } x \{P \parallel Q\} \downarrow_{x:\text{act}}} [\equiv]$$

In fact, there is other possible derivation for $\text{share } x \{P \parallel Q\} \downarrow_{x:\text{act}}$

$$\frac{\text{share } x \{P \parallel Q\} \equiv \beta; R_2 + \alpha; R_1 \quad \frac{\frac{s(\beta; R_2) = x}{\beta; R_2 \downarrow_{x:\text{act}}} [\text{act}]}{(\beta; R_2 + \alpha; R_1) \downarrow_{x:\text{act}}} [\text{sum}]}{\text{share } x \{P \parallel Q\} \downarrow_{x:\text{act}}} [\equiv]$$

Group B Case [par]

We have

$$\frac{P_1 \downarrow_{x:\text{act}}}{(P_1 \parallel P_2)x : \text{act}} [\text{par}]$$

where $P = P_1 \parallel P_2$.

Since $P_1 \parallel P_2 \vdash \Delta, x : \Box A; \Gamma$ we conclude that exists a partition Δ_1, Δ_2 of Δ for which $P_1 \vdash \Delta_1, x : \Box A; \Gamma$ and $P_2 \vdash \Delta_2; \Gamma$. Observe that x lies in the linear typing context of P_1 and not of P_2 , because $P_1 \downarrow_{x:\text{act}}$.

We have

$$\begin{aligned} \text{share } x \{P \parallel Q\} &= \text{share } x \{(P_1 \parallel P_2) \parallel Q\} \\ &\equiv \underbrace{\text{share } x \{P_1 \parallel Q\}}_R \parallel P_2 \end{aligned} \quad (\equiv [\text{C-ShM}], x \in \text{fn}(P_1))$$

By induction on $P_1 \downarrow_x$ and $Q \downarrow_x$ we conclude that $R \downarrow_{x:\text{act}}$.
Hence

$$\frac{\text{share } x \{P \parallel Q\} \equiv R \parallel P_2 \quad \frac{R \downarrow_{x:\text{act}}}{(R \parallel P_2) \downarrow_{x:\text{act}}} [\text{par}]}{(\text{share } x \{P \parallel Q\}) \downarrow_{x:\text{act}}} [\equiv]$$

Case [cut]

We have

$$\frac{P_1 \downarrow_{x:\text{act}} \quad y \neq x}{(P_1 \mid y \mid P_2)x : \text{act}} [\text{cut}]$$

where $P = P_1 \mid y \mid P_2$.

Since $P_1 \mid y \mid P_2 \vdash \Delta, x : \Box A; \Gamma$ we conclude that exists a partition Δ_1, Δ_2 of Δ and a type B for which $P_1 \vdash \Delta_1, y : \bar{B}, x : \Box A; \Gamma$ and $P_2 \vdash \Delta_2, y : B; \Gamma$. Observe that x lies in the linear typing context of P_1 and not of P_2 , because $P_1 \downarrow_{x:\text{act}}$.

We have

$$\begin{aligned} \text{share } x \{P \parallel Q\} &= \text{share } x \{(P_1 \mid y \mid P_2) \parallel Q\} \\ &\equiv \underbrace{\text{share } x \{P_1 \parallel Q\}}_R \mid y \mid P_2 \end{aligned} \quad (\equiv [\text{C-CSh}], x, y \in \text{fn}(P_1))$$

By induction on $P_1 \downarrow_{x:\text{act}}$ and $Q \downarrow_{x:\text{act}}$ we conclude that $(\text{share } x \{P_1 \parallel Q\}) \downarrow_{x:\text{act}}$.
Hence

$$\frac{\text{share } x \{P \parallel Q\} \equiv R \mid y \mid P_2 \quad \frac{R \downarrow_x \quad y \neq x}{(R \mid y \mid P_2) \downarrow_{x:\text{act}}} [\text{cut}]}{(\text{share } x \{P \parallel Q\}) \downarrow_{x:\text{act}}} [\equiv]$$

Case [cut!]

We have

$$\frac{P_2 \downarrow_{x:\text{act}} \quad z \neq x}{(y.P_1 \mid !z \mid P_2)x : \text{act}} [\text{cut!}]$$

where $P = y.P_1 \mid !z \mid P_2$.

Since $y.P_1 \mid !z \mid P_2 \vdash \Delta, x : \Box A; \Gamma$ we conclude that exists a type B for which $P_1 \vdash y : \bar{B}; \Gamma$ and $P_2 \vdash \Delta, x : \Box A; \Gamma, z : B$.

We have

$$\begin{aligned} \text{share } x \{P \parallel Q\} &= \text{share } x \{(y.P_1 \mid !z \mid P_2) \parallel Q\} \\ &\equiv y.P_1 \mid !z \mid \underbrace{(\text{share } x \{P_2 \parallel Q\})}_R \end{aligned} \quad (\equiv [\text{C-ShC!}] z \notin \text{fn}(Q))$$

By induction on $P_2 \downarrow_{x:\text{act}}$ and $Q \downarrow_{x:\text{act}}$ we conclude that $R \downarrow_{x:\text{act}}$.
Hence

$$\frac{\text{share } x \{P \parallel Q\} \equiv y.P_1 !z.R \quad \frac{R \downarrow_{x:\text{act}} \quad z \neq x}{(y.P_1 !z.R) \downarrow_{x:\text{act}}} [\text{cut!}]}{(\text{share } x \{P \parallel Q\}) \downarrow_{x:\text{act}}} [\equiv]$$

Case [share]

We have

$$\frac{P_1 \downarrow_{x:\text{act}} \quad y \neq x}{(\text{share } y \{P_1 \parallel P_2\})x : \text{act}} [\text{share}]$$

where $P = \text{share } y \{P_1 \parallel P_2\}$.

Since $\text{share } y \{P_1 \parallel P_2\} \vdash \Delta, x : \Box A; \Gamma$ we conclude that exists a partition Δ_1, Δ_2 of Δ and a type B for which $P_1 \vdash \Delta_1, y : \Box B, x : \Box A; \Gamma$ and $P_2 \vdash \Delta_2, y : \Box B; \Gamma$. Observe that x lies in the linear typing context of P_1 and not of P_2 , because $P_1 \downarrow_{x:\text{act}}$.

We have

$$\begin{aligned} \text{share } x \{P \parallel Q\} &= \text{share } x \{\text{share } y \{P_1 \parallel P_2\} \parallel Q\} \\ &\equiv \text{share } y \underbrace{\{\text{share } x \{P_1 \parallel Q\} \parallel P_2\}}_R \quad (\equiv [\text{C-ShSh}], x, y \in \text{fn}(P_2)) \end{aligned}$$

By induction on $P_1 \downarrow_{x:\text{act}}$ and $Q \downarrow_{x:\text{act}}$ we conclude that $(\text{share } x \{P_1 \parallel Q\}) \downarrow_{x:\text{act}}$. Hence

$$\frac{\text{share } x \{P \parallel Q\} \equiv \text{share } y \{R \parallel P_2\} \quad \frac{R \downarrow_{x:\text{act}} \quad y \neq x}{(\text{share } y \{R \parallel P_2\}) \downarrow_{x:\text{act}}} [\text{share}]}{(\text{share } x \{P \parallel Q\}) \downarrow_{x:\text{act}}} [\equiv]$$

Case [sum]

We have

$$\frac{P_1 \downarrow_{x:\text{act}}}{(P_1 + P_2)x : \text{act}} [\text{sum}]$$

where $P = P_1 + P_2$.

Since $P_1 + P_2 \vdash \Delta, x : \Box A; \Gamma$ we conclude that $P_1 \vdash \Delta, x : \Box A; \Gamma$ and $P_2 \vdash \Delta, x : \Box A; \Gamma$.

We have

$$\begin{aligned} \text{share } x \{P \parallel Q\} &= \text{share } x \{(P_1 + P_2) \parallel Q\} \\ &\equiv \underbrace{\text{share } x \{P_1 \parallel Q\} + \text{share } x \{P_2 \parallel Q\}}_R \quad (\equiv [\text{D-ShSm}]) \end{aligned}$$

By induction on $P_1 \downarrow_{x:\text{act}}$ and $Q \downarrow_{x:\text{act}}$ we conclude that $R \downarrow_{x:\text{act}}$.

Hence

$$\frac{\text{share } x \{P \parallel Q\} \equiv R + \text{share } x \{P_2 \parallel Q\} \quad \frac{R \downarrow_{x:\text{act}}}{(R + \text{share } x \{P_2 \parallel Q\}) \downarrow_{x:\text{act}}} [\text{sum}]}{(\text{share } x \{P \parallel Q\}) \downarrow_{x:\text{act}}} [\equiv]$$

Group C We have

$$\frac{P \equiv P' \quad P' \downarrow_{x:\text{act}}}{P \downarrow_{x:\text{act}}} [\equiv]$$

Since $P \vdash \Delta, x : \Box A; \Gamma$, $P \equiv P'$ and structural congruence preserves typing, then $P' \vdash \Delta, x : \Box A; \Gamma$.

By induction on $P' \downarrow_{x:\text{act}}, Q \downarrow_{x:\text{act}}$, we conclude that $\text{share } x \{P' \parallel Q\} \downarrow_{x:\text{act}}$. Observe that

$$\text{share } x \{P \parallel Q\} \equiv \text{share } x \{P' \parallel Q\}$$

Hence

$$\frac{\text{share } x \{P \parallel Q\} \equiv \text{share } x \{P' \parallel Q\} \quad \text{share } x \{P' \parallel Q\} \downarrow_{x:\text{act}}}{\text{share } x \{P \parallel Q\} \downarrow_{x:\text{act}}} [\equiv]$$

□

LEMMA 6.9(2). Let $P \vdash \Delta, x : \bar{A}; \Gamma$ and $Q \vdash \Delta', x : A; \Gamma$ be processes for which $P \downarrow_{x:\text{act}}$ and $Q \downarrow_{x:\text{act}}$. Then, $P \mid x \mid Q$ reduces.

PROOF. The proof is by induction on the sum of the depths of derivation trees $P \downarrow_x$ and $Q \downarrow_x$. We perform case analysis on the root rule of each tree. The cases are organised in the following groups

Group A Both the root rules of $P \downarrow_x$ and $Q \downarrow_x$ is [act].

Group C Either the root rule of $P \downarrow_x$ or of $Q \downarrow_x$ is [par], [cut], [cut!], [share] or [sum].

Group D Either the root rule of $P \downarrow_x$ or of $Q \downarrow_x$ is [\equiv].

The cases of group A are handled by applying one of the principal cut reductions.

As for group B, the strategy is do distribute the cut and then apply the inductive hypothesis. We perform case analysis on the root rule of $P \downarrow_x$. The argument goes by symmetry for $Q \downarrow_x$.

For C, we consider the case in which the root rule of $P \downarrow_x$ is [\equiv]. This is handled trivially since reduction is closed by structural congruence. The argument goes by symmetry for $Q \downarrow_x$.

Group A Case The root rule of both $P \downarrow_x$ and $Q \downarrow_x$ is [act].

We have

$$\frac{s(\mathcal{A}) = x}{\mathcal{A} \downarrow_x} [\text{act}] \quad \frac{s(\mathcal{B}) = x}{\mathcal{B} \downarrow_x} [\text{act}]$$

where $P = \mathcal{A}$ and $Q = \mathcal{B}$.

Since $\mathcal{A} \vdash \Delta, x : \bar{A}; \Gamma$ and $\mathcal{B} \vdash \Delta, x : A; \Gamma$ we conclude that \mathcal{A}, \mathcal{B} is a pair of dual actions with the same subject. Hence, $P \mid x \mid Q$ reduces by applying one of the principal cut reductions.

For example, if $A = \perp$, we have

$$\mathcal{A} = \text{close } x \text{ and } \mathcal{B} = \text{wait } x; Q'$$

Consequently

$$\text{close } x \mid x \mid \text{wait } x; Q' \rightarrow Q' \quad (\rightarrow [1\perp])$$

Group B Case [par]

We have

$$\frac{P_1 \downarrow_x}{(P_1 \parallel P_2) \downarrow_x} [\text{par}]$$

where $P = P_1 \parallel P_2$.

Since $P_1 \parallel P_2 \vdash \Delta, x : \bar{A}; \Gamma$ we conclude that there exists a partition Δ_1, Δ_2 of Δ s.t. $P_1 \vdash \Delta_1, x : \bar{A}; \Gamma$ and $P_2 \vdash \Delta_2; \Gamma$. Observe that x lies in the linear typing context of P_1 and not of P_2 , because $P_1 \downarrow_x$.

Then

$$\begin{aligned} P \ |x| \ Q &= (P_1 \ || \ P_2) \ |x| \ Q \\ &\equiv (P_1 \ |x| \ Q) \ || \ P_2 && (\equiv [\text{C-CM}], x \in \text{fn}(P_1)) \end{aligned}$$

By induction on $P_1 \downarrow_x$ and $Q \downarrow_x$ we conclude that $P_1 \ |x| \ Q$, and hence $(P_1 \ |x| \ Q) \ || \ P_2$, reduces.

Case [cut]

We have

$$\frac{P_1 \downarrow_x \quad y \neq x}{(P_1 \ |y| \ P_2) \downarrow_x} \text{ [cut]}$$

where $P = P_1 \ |y| \ P_2$.

Since $P_1 \ |y| \ P_2 \vdash \Delta, x : \bar{A}; \Gamma$ we conclude that there exists a partition Δ_1, Δ_2 of Δ and a type B s.t. $P_1 \vdash \Delta_1, x : \bar{A}, y : \bar{B}; \Gamma$ and $P_2 \vdash \Delta_2, y : B; \Gamma$. Observe that x lies in the linear typing context of P_1 and not of P_2 , because $P_1 \downarrow_x$.

Then

$$\begin{aligned} P \ |x| \ Q &= (P_1 \ |y| \ P_2) \ |x| \ Q \\ &\equiv (P_1 \ |x| \ Q) \ |y| \ P_2 && (\equiv [\text{C-CC}], x, y \in \text{fn}(P_1)) \end{aligned}$$

By induction on $P_1 \downarrow_x$ and $Q \downarrow_x$ we conclude that $P_1 \ |x| \ Q$, and hence $(P_1 \ |x| \ Q) \ |y| \ P_2$, reduces.

Case [cut!]

We have

$$\frac{P_2 \downarrow_x \quad z \neq x}{(y.P_1 \ !z| \ P_2) \downarrow_x} \text{ [cut]}$$

where $P = y.P_1 \ !z| \ P_2$.

Since $y.P_1 \ !z| \ P_2 \vdash \Delta, x : \bar{A}; \Gamma$ we conclude that there exists a type B s.t. $P_1 \vdash y : \bar{B}; \Gamma$ and $P_2 \vdash \Delta, x : \bar{A}; \Gamma, z : B$.

Then

$$\begin{aligned} P \ |x| \ Q &= (y.P_1 \ !z| \ P_2) \ |x| \ Q \\ &\equiv y.P_1 \ !z| \ (P_2 \ |x| \ Q) && (\equiv [\text{C-CC!}], z \notin \text{fn}(Q)) \end{aligned}$$

By induction on $P_2 \downarrow_x$ and $Q \downarrow_x$ we conclude that $P_2 \ |x| \ Q$, and hence $y.P_1 \ !z| \ (P_2 \ |x| \ Q)$, reduces.

Case [share]

We have

$$\frac{P_1 \downarrow_x \quad y \neq x}{(\text{share } y \ \{P_1 \ || \ P_2\}) \downarrow_x} \text{ [share]}$$

where $P = \text{share } y \ \{P_1 \ || \ P_2\}$.

Since $\text{share } y \ \{P_1 \ || \ P_2\} \vdash \Delta, x : \bar{A}; \Gamma$ we conclude that there exists a partition $\Delta_1, \Delta_2, y : \Box B$ of Δ s.t. $P_1 \vdash \Delta_1, x : \bar{A}, y : \Box B; \Gamma$ and $P_2 \vdash \Delta_2, y : \Box B; \Gamma$. Observe that x lies in the linear typing context of P_1 and not of P_2 because $P_1 \downarrow_x$.

Then

$$\begin{aligned} P \ |x| \ Q &= (\text{share } y \ \{P_1 \ || \ P_2\}) \ |x| \ Q \\ &\equiv \text{share } y \ \{(P_1 \ |x| \ Q) \ || \ P_2\} && (\equiv [\text{C-CSh}], x, y \in \text{fn}(P_1)) \end{aligned}$$

By induction on $P_1 \downarrow_x$ and $Q \downarrow_x$ we conclude that $P_1 \mid x \mid Q$, and hence $\text{share } y \{(P_1 \mid x \mid Q) \parallel P_2\}$, reduces.

Case [sum]

We have

$$\frac{P_1 \downarrow_x}{(P_1 + P_2) \downarrow_x} \text{ [sum]}$$

where $P = P_1 + P_2$.

Since $P_1 + P_2 \vdash \Delta, x : \bar{A}; \Gamma$ we conclude that $P_1 \vdash \Delta, x : \bar{A}; \Gamma$ and $P_2 \vdash \Delta, x : \bar{A}; \Gamma$.

Then

$$\begin{aligned} P \mid x \mid Q &= (P_1 + P_2) \mid x \mid Q \\ &\equiv (P_1 \mid x \mid Q) + (P_2 \mid x \mid Q) \quad (\equiv [\text{D-CSm}]) \end{aligned}$$

By induction on $P_1 \downarrow_x$ and $Q \downarrow_x$ we conclude that $P_1 \mid x \mid Q$, and hence $(P_1 \mid x \mid Q) + (P_2 \mid x \mid Q)$, reduces.

Group C We have

$$\frac{P \equiv P' \quad P' \downarrow_x}{P \downarrow_x}$$

Observe that since $P \vdash \Delta, x : \bar{A}; \Gamma$, $P \equiv P'$ and structural congruence preserves typing, then $P' \vdash \Delta, x : \bar{A}; \Gamma$.

By induction on $P' \downarrow_x$, $Q \downarrow_x$ we conclude that $P' \mid x \mid Q$ reduces. Since $P \mid x \mid Q \equiv P' \mid x \mid Q$, $P \mid x \mid Q$ reduces as well.

□

LEMMA 6.9(3). *Let $P \vdash \Delta, x : A; \Gamma$, $Q \vdash \Delta', x : A; \Gamma$ be processes for which $P \downarrow_{x:\text{fwd}}$. Then, $P \mid x \mid Q$ reduces.*

PROOF. The proof is by induction on the depth of the derivation tree $P \downarrow_x$. We perform case analysis on the root rule of the tree.

We handle case [fwd] below. For the remaining cases, see the proof of lemma 6.9(2), groups B and C.

Case [fwd]

We have

$$\frac{}{\text{fwd } x \ y \ \downarrow_x} \text{ [fwd]}$$

where $P = \text{fwd } x \ y$.

Then

$$\begin{aligned} \text{fwd } x \ y \ \mid x \mid Q &\equiv \text{fwd } y \ x \ \mid x \mid Q && (\equiv [\text{C-fwd}]) \\ &\rightarrow \{y/x\}Q && (\rightarrow [\text{fwd}]) \end{aligned}$$

□

LEMMA [6.9(4)] *Let $P \vdash y : \bar{A}; \Gamma$ and $Q \vdash \Delta; \Gamma, x : A$ be processes for which $Q \downarrow_x$. Then, $y.P \mid !x \mid Q$ reduces.*

PROOF. The proof is by structural induction on the derivation tree $Q \downarrow_x$. We perform case analysis on the root rule of the tree. The cases are organised in the following groups

Group A The root rule of $Q \downarrow_x$ is [act].

Group B The root rule of $Q \downarrow_x$ is either [par], [cut], [cut!], [share] or [sum].

Group C The root rule of $Q \downarrow_x$ is [≡].

Group A has one case, which is handled by applying a principal cut conversion.

For group B, the strategy is to distribute the replicated server and then apply the inductive hypothesis.

The only case of group C follows trivially because reduction is closed by structural congruence. Observe that case [fwd] is excluded because x lies in the unrestricted typing context.

Group A We have

$$\frac{s(\mathcal{A}) = x}{\mathcal{A} \downarrow_x}$$

where $Q = \mathcal{A}$.

Since $\mathcal{A} \vdash \Delta; \Gamma, x : A$, we have $\mathcal{A} = \text{call } x(z); Q'$, for some Q' . Hence

$$y.P \mid !x \mid \text{call } x(z); Q' \rightarrow \{z/y\}P \mid z \mid (y.P \mid !x \mid Q') \quad (\rightarrow [\text{call}])$$

Group B Case [par]

We have

$$\frac{Q_1 \downarrow_x}{(Q_1 \parallel Q_2) \downarrow_x}$$

where $Q = Q_1 \parallel Q_2$.

Since $Q_1 \parallel Q_2 \vdash \Delta; \Gamma, x : A$, there exists a partition Δ_1, Δ_2 of Δ for which $Q_1 \vdash \Delta_1; \Gamma, x : A$ and $Q_2 \vdash \Delta_2; \Gamma, x : A$.

We have

$$\begin{aligned} y.P \mid !x \mid Q &= y.P \mid !x \mid (Q_1 \parallel Q_2) \\ &\equiv (y.P \mid !x \mid Q_1) \parallel (y.P \mid !x \mid Q_2) \quad (\equiv [\text{D-C!M}]) \end{aligned}$$

By induction on $Q_1 \downarrow_x$ we conclude that $y.P \mid !x \mid Q_1$, and hence $y.P \mid !x \mid Q$, reduces.

Case [cut]

We have

$$\frac{Q_1 \downarrow_x \quad z \neq x}{(Q_1 \mid z \mid Q_2) \downarrow_x}$$

where $Q = Q_1 \mid z \mid Q_2$.

Since $Q_1 \mid z \mid Q_2 \vdash \Delta; \Gamma, x : A$, there exists a partition Δ_1, Δ_2 of Δ and a type B for which $Q_1 \vdash \Delta_1, z : \bar{B}; \Gamma, x : A$ and $Q_2 \vdash \Delta_2, z : B; \Gamma, x : A$.

We have

$$\begin{aligned} y.P \mid !x \mid Q &= y.P \mid !x \mid (Q_1 \mid z \mid Q_2) \\ &\equiv (y.P \mid !x \mid Q_1) \mid z \mid (y.P \mid !x \mid Q_2) \quad (\equiv [\text{D-C!C}]) \end{aligned}$$

By induction on $Q_1 \downarrow_x$ we conclude that $y.P \mid !x \mid Q_1$, and hence $y.P \mid !x \mid Q$, reduces.

Case [cut!]

We have

$$\frac{Q_2 \downarrow_x \quad z \neq x}{(w.Q_1 \mid !z \mid Q_2) \downarrow_x}$$

where $Q = w.Q_1 \mid!z \mid Q_2$.

Since $w.Q_1 \mid!z \mid Q_2 \vdash \Delta; \Gamma, x : A$, we conclude that exists a type B for which $Q_1 \vdash w : \bar{B}; \Gamma, x : A$ and $Q_2 \vdash \Delta; \Gamma, z : B, x : A$.

We have

$$\begin{aligned} y.P \mid!x \mid Q &= y.P \mid!x \mid (w.Q_1 \mid!z \mid Q_2) \\ &\equiv w.(y.P \mid!x \mid Q_1) \mid!z \mid (y.P \mid!x \mid Q_2) \quad (\equiv [\text{D-C!C!}]) \end{aligned}$$

By induction on $Q_2 \downarrow_x$ we conclude that $y.P \mid!x \mid Q_2$, and hence $y.P \mid!x \mid Q$, reduces.

Case [share]

We have

$$\frac{Q_1 \downarrow_x \quad z \neq x}{(\text{share } z \{Q_1 \parallel Q_2\}) \downarrow_x}$$

where $Q = \text{share } z \{Q_1 \parallel Q_2\}$.

Since $\text{share } z \{Q_1 \parallel Q_2\} \vdash \Delta; \Gamma, x : A$, there exists a partition $\Delta_1, \Delta_2, z : \Box B$ of Δ for which $Q_1 \vdash \Delta_1, z : \Box B; \Gamma, x : A$ and $Q_2 \vdash \Delta_2, z : \Box B; \Gamma, x : A$.

We have

$$\begin{aligned} y.P \mid!x \mid Q &= y.P \mid!x \mid (\text{share } z \{Q_1 \parallel Q_2\}) \\ &\equiv \text{share } z \{(y.P \mid!x \mid Q_1) \parallel (y.P \mid!x \mid Q_2)\} \quad (\equiv [\text{D-C!Sh}]) \end{aligned}$$

By induction on $Q_1 \downarrow_x$ we conclude that $y.P \mid!x \mid Q_1$, and hence $y.P \mid!x \mid Q$ reduces.

Case [sum]

We have

$$\frac{Q_1 \downarrow_x}{(Q_1 + Q_2) \downarrow_x}$$

where $Q = Q_1 + Q_2$.

Since $Q_1 \parallel Q_2 \vdash \Delta; \Gamma, x : A$, then $Q_1 \vdash \Delta; \Gamma, x : A$ and $Q_2 \vdash \Delta; \Gamma, x : A$.

We have

$$\begin{aligned} y.P \mid!x \mid Q &= y.P \mid!x \mid (Q_1 + Q_2) \\ &\equiv (y.P \mid!x \mid Q_1) + (y.P \mid!x \mid Q_2) \quad (\equiv [\text{D-C!Sm}]) \end{aligned}$$

By induction on $Q_1 \downarrow_x$ we conclude that $y.P \mid!x \mid Q_1$, and hence $y.P \mid!x \mid Q$, reduces.

Group C We have

$$\frac{Q \equiv Q' \quad Q' \downarrow_x}{Q \downarrow_x}$$

Observe that since $Q \vdash \Delta; \Gamma, x : A$, $Q \equiv Q'$ and structural congruence preserves typing, we have $Q' \vdash \Delta; \Gamma, x : A$.

By induction on $Q' \downarrow_x$ we conclude that $y.P \mid!x \mid Q'$ reduces. Since $y.P \mid!x \mid Q \equiv y.P \mid!x \mid Q'$, $y.P \mid!x \mid Q$ reduces as well.

□

LEMMA 6.9(5). *Let $P \vdash \Delta, x : A; \Gamma$ and suppose that $A \neq \Box B$. If $P \downarrow_{x:\text{fwd}}$, then either (i) $P \downarrow_{y:\text{fwd}}$ for some $y : \bar{A} \in \Delta$ or (ii) P reduces.*

PROOF. The proof is by structural induction on the derivation tree $P \downarrow_{x:\text{fwd}}$. We perform case analysis on the root rule of the tree.

Case [fwd]

We have

$$\frac{}{\text{fwd } x \ y \ \downarrow_{x:\text{fwd}}} \text{ [fwd]}$$

where $P = \text{fwd } x \ y$.

By inversion on $\text{fwd } x \ y \vdash \Delta, x : A; \Gamma$ we conclude that $\Delta = y : \bar{A}$.

Observe that

$$\text{fwd } x \ y \equiv \text{fwd } y \ x \quad (\equiv [\text{C-fwd}])$$

Then

$$\frac{\text{fwd } x \ y \equiv \text{fwd } y \ x \quad \frac{}{\text{fwd } y \ x \ \downarrow_{y:\text{fwd}}} \text{ [fwd]}}{\text{fwd } x \ y \ \downarrow_{x:\text{fwd}}} \text{ [\equiv]}$$

Case [par]

We have

$$\frac{P_1 \downarrow_{x:\text{fwd}}}{(P_1 \parallel P_2) \downarrow_{x:\text{fwd}}} \text{ [par]}$$

where $P = P_1 \parallel P_2$.

By inversion on the typing judgment $P_1 \parallel P_2 \vdash \Delta, x : A; \Gamma$ we conclude that exists a partition Δ_1, Δ_2 of Δ s.t. $P_1 \vdash \Delta_1, x : A; \Gamma$ and $P_2 \vdash \Delta_2; \Gamma$. Observe that x lies in the linear typing context of P_1 and not of P_2 because $P_1 \downarrow_x$.

By induction on $P_1 \downarrow_{x:\text{fwd}}$, we conclude that either (i) $P_1 \downarrow_{y:\text{fwd}}$ for some $y : \bar{A} \in \Delta_1$ or (ii) P_1 reduces.

Case (i) $P_1 \downarrow_{y:\text{fwd}}$ for some $y : \bar{A} \in \Delta_1$.

Then

$$\frac{P_1 \downarrow_{y:\text{fwd}}}{(P_1 \parallel P_2) \downarrow_{y:\text{fwd}}} \text{ [par]}$$

Furthermore, since $y : \bar{A} \in \Delta_1$ and $\Delta = \Delta_1, \Delta_2$, then $y : \bar{A} \in \Delta$.

Case (ii) P_1 reduces.

Since reduction is a congruence, then $P_1 \parallel P_2$ reduces as well.

Case [cut]

We have

$$\frac{P_1 \downarrow_{x:\text{fwd}} \quad z \neq x}{(P_1 \mid z \mid P_2) \downarrow_{x:\text{fwd}}} \text{ [cut]}$$

where $P = P_1 \mid z \mid P_2$.

By inversion on the typing judgment $P_1 \mid z \mid P_2 \vdash \Delta, x : A; \Gamma$ we conclude that exists a partition Δ_1, Δ_2 of Δ and a type B s.t. $P_1 \vdash \Delta_1, x : A, z : \bar{B}; \Gamma$ and $P_2 \vdash \Delta_2, z : B; \Gamma$. Observe that x lies in the linear typing context of P_1 and not of P_2 because $P_1 \downarrow_x$.

By induction on $P_1 \downarrow_{x:\text{fwd}}$, we conclude that either (i) $P_1 \downarrow_{y:\text{fwd}}$ for some $y : \bar{A} \in \Delta_1, z : \bar{B}$ or (ii) P_1 reduces. There are three cases to consider, depending on whether (i-i) $y \neq z$ or (i-ii) $y = z$.

Case (i-i) $P_1 \downarrow_{y:\text{fwd}}$ for some $y : \bar{A} \in \Delta_1$.

Then

$$\frac{P_1 \downarrow_{y:\text{fwd}} \quad y \neq z}{(P_1 \mid z \mid P_2) \downarrow_{y:\text{fwd}}} \text{ [cut]}$$

Furthermore, since $y : \bar{A} \in \Delta_1$ and $\Delta = \Delta_1, \Delta_2$, then $y : \bar{A} \in \Delta$.

Case (i-ii) $P_1 \downarrow_{z:\text{fwd}}$ and $y = z$.

By lemma 6.9(3), we conclude that $P_1 \mid z \mid P_2$ reduces.

Case (ii) P_1 reduces.

Since reduction is a congruence, then $P_1 \mid z \mid P_2$ reduces as well.

Case [cut!]

We have

$$\frac{P_1 \downarrow_{x:\text{fwd}} \quad z \neq x}{(w.P_1 \mid!z \mid P_2) \downarrow_{x:\text{fwd}}} \text{ [cut!]}$$

where $P = w.P_1 \mid!z \mid P_2$.

By inversion on the typing judgment $w.P_1 \mid!z \mid P_2 \vdash \Delta, x : A; \Gamma$ we conclude that exists a type B s.t. $P_1 \vdash w : \bar{B}; \Gamma$ and $P_2 \vdash \Delta, x : A; \Gamma, z : B$.

By induction on $P_2 \downarrow_{x:\text{fwd}}$, we conclude that either (i) $P_2 \downarrow_{y:\text{fwd}}$ for some $y : \bar{A} \in \Delta$ or (ii) P_2 reduces.

Case (i) $P_2 \downarrow_{y:\text{fwd}}$ for some $y : \bar{A} \in \Delta$. Then

$$\frac{P_2 \downarrow_{y:\text{fwd}} \quad y \neq z}{(w.P_1 \mid!z \mid P_2) \downarrow_{y:\text{fwd}}} \text{ [cut!]}$$

Case (ii) P_2 reduces.

Since reduction is a congruence, then $w.P_1 \mid!z \mid P_2$ reduces as well.

Case [share]

We have

$$\frac{P_1 \downarrow_{x:\text{fwd}} \quad z \neq x}{(\text{share } z \{P_1 \parallel P_2\}) \downarrow_{x:\text{fwd}}} \text{ [share]}$$

where $P = \text{share } z \{P_1 \parallel P_2\}$.

By inversion on the typing judgment $\text{share } z \{P_1 \parallel P_2\} \vdash \Delta, x : A; \Gamma$ we conclude that exists a partition Δ_1, Δ_2 of Δ and a type B s.t. $P_1 \vdash \Delta_1, x : A, z : \Box B; \Gamma$ and $P_2 \vdash \Delta_2, z : \Box B; \Gamma$. Observe that x lies in the linear typing context of P_1 and not of P_2 because $P_1 \downarrow_x$.

By induction on $P_1 \downarrow_{x:\text{fwd}}$, we conclude that either (i) $P_1 \downarrow_{y:\text{fwd}}$ for some $y : \bar{A} \in \Delta_1, z : \Box B$ or (ii) P_1 reduces.

Notice that, by hypothesis, $\bar{A} \neq \Box B$. Hence, $y : \bar{A} \in \Delta_1$.

There are then two cases to consider.

Case (i) $P_1 \downarrow_{y:\text{fwd}}$ for some $y : \bar{A} \in \Delta_1$.

Then

$$\frac{P_1 \downarrow_{y:\text{fwd}} \quad y \neq z}{(\text{share } z \{P_1 \parallel P_2\}) \downarrow_{y:\text{fwd}}} \text{ [share]}$$

Case (ii) P_1 reduces

Since reduction is a congruence, then $\text{share } z \{P_1 \parallel P_2\}$ reduces as well.

Case [sum]

We have

$$\frac{P_1 \downarrow_{x:\text{fwd}}}{(P_1 \parallel P_2) \downarrow_{x:\text{fwd}}} \text{ [sum]}$$

where $P = P_1 + P_2$.

By inversion on the typing judgment $P_1 + P_2 \vdash \Delta, x : A; \Gamma$ we conclude that $P_1 \vdash \Delta, x : A; \Gamma$ and $P_2 \vdash \Delta, x : A; \Gamma$.

By induction on $P_1 \downarrow_{x:\text{fwd}}$, we conclude that either (i) $P_1 \downarrow_{y:\text{fwd}}$ for some $y : \bar{A} \in \Delta$ or (ii) P_1 reduces.

Case (i) $P_1 \downarrow_{y:\text{fwd}}$ for some $y : \bar{A} \in \Delta$.

Then

$$\frac{P_1 \downarrow_{y:\text{fwd}}}{(P_1 + P_2) \downarrow_{y:\text{fwd}}} \text{ [sum]}$$

Case (ii) P_1 reduces.

Since reduction is a congruence, then $P_1 + P_2$ reduces as well.

Case [≡]

We have

$$\frac{P \equiv Q \quad Q \downarrow_{x:\text{fwd}}}{P \downarrow_{x:\text{fwd}}} \text{ [≡]}$$

Since $P \vdash \Delta, x : A; \Gamma$ and $P \equiv Q$, then $Q \vdash \Delta, x : A; \Gamma$.

By induction on $Q \downarrow_{x:\text{fwd}}$ we conclude that either (i) $Q \downarrow_{y:\text{fwd}}$ for some $y : \bar{A} \in \Delta$ or (ii) Q reduces.

Case (i) $Q \downarrow_{y:\text{fwd}}$ for some $y : \bar{A} \in \Delta$.

Then

$$\frac{P \equiv Q \quad Q \downarrow_{y:\text{fwd}}}{P \downarrow_{y:\text{fwd}}} \text{ [≡]}$$

Case (ii) Q reduces.

Since reduction is closed by structural congruence, then P reduces as well.

□

B.3 Progress Lemma

LEMMA 6.10. *Let $P \vdash \Delta; \Gamma$ be such that P is live. Either $P \downarrow_x$ or P reduces.*

PROOF. The proof is by structural induction a derivation tree for $P \vdash \Delta; \Gamma$. We perform case analysis on the root rule of the tree.

Case [T0]

We have

$$\frac{}{\mathbf{0} \vdash \emptyset; \Gamma} \text{ [T0]}$$

where $P = \mathbf{0}$. Holds vacuously because $\mathbf{0}$ is not live.

Case [Tfwd]

We have

$$\frac{}{\text{fwd } x \vdash x : \bar{A}, y : A; \Gamma} \text{ [Tfwd]}$$

Then

$$\frac{}{(\text{fwd } x \ y) \downarrow_x} \text{ [fwd]}$$

Case [T1]

We have

$$\frac{}{\text{close } x \vdash x : 1; \Gamma} \text{ [T1]}$$

where $P = \text{close } x$. Observe that $\text{close } x$ is an action. Then

$$\frac{s(\text{close } x) = x}{\text{close } x \downarrow_x} \text{ [act]}$$

Similarly for the the other rules which introduce an action: [T \perp], [T \otimes], [T \wp], [T \oplus_l], [T \oplus_r], [T $\&$], [T $?$], [T $!$], [Tcopy], [T \exists], [TV], [Tcell], [Tfree], [Tread] and [Twrite].

Case [Tmix]

We have

$$\frac{P_1 \vdash \Delta_1; \Gamma \quad P_2 \vdash \Delta_2; \Gamma}{P_1 \parallel P_2 \vdash \Delta_1, \Delta_2; \Gamma} \text{ [Tmix]}$$

where $P = P_1 \parallel P_2$ and $\Delta = \Delta_1, \Delta_2$.

Since $P_1 \parallel P_2$ is live, then either P_1 is live or P_2 is live.

Suppose w.l.o.g. that P_1 is live. By induction on $P_1 \vdash \Delta_1; \Gamma$ we conclude that either $P_1 \downarrow_x$ or P_1 reduces.

Case $P_1 \downarrow_x$

Then

$$\frac{P_1 \downarrow_x}{(P_1 \parallel P_2) \downarrow_x} \text{ [par]}$$

Case P_1 reduces

Then, $P_1 \parallel P_2$ reduces because reduction is a congruence.

Case [Tcut]

We have

$$\frac{P_1 \vdash \Delta_1, x : \bar{A}; \Gamma \quad P_2 \vdash \Delta_2, x : A; \Gamma}{P_1 \mid x \mid P_2 \vdash \Delta_1, \Delta_2; \Gamma} \text{ [cut]}$$

where $P = P_1 \mid x \mid P_2$ and $\Delta = \Delta_1, \Delta_2$.

Since both P_1 and P_2 have a nonempty linear typing context, we conclude that both P_1 and P_2 are live (lemma B.1).

By applying the i.h. to $P_1 \vdash \Delta_1, x : \bar{A}; \Gamma$ and $P_2 \vdash \Delta_2, x : A; \Gamma$ we conclude that

- $P_1 \downarrow_y$ or P_1 reduces, and
- $P_2 \downarrow_z$ or P_2 reduces

We have the following cases to consider

Case ($P_1 \downarrow_y$ and $y \neq x$) or ($P_2 \downarrow_z$ and $z \neq x$)

Suppose w.l.o.g. that $P_1 \downarrow_y$ and $y \neq x$.

Then

$$\frac{P_1 \downarrow_y \quad y \neq x}{(P_1 \mid x \mid P_2) \downarrow_y} \text{ [cut]}$$

Case $P_1 \downarrow_x$ and $P_2 \downarrow_x$

We have the following two cases

Case $P_1 \downarrow_{x:\text{fwd}}$ or $P_2 \downarrow_{x:\text{fwd}}$

Suppose w.l.o.g. that $P_1 \downarrow_{x:\text{fwd}}$.

Then, by lemma 6.9(3), we conclude that $P_1 \mid x \mid P_2$ reduces.

Case $P_1 \downarrow_{x:\text{act}}$ and $P_2 \downarrow_{x:\text{act}}$

Then, by lemma 6.9(2), we conclude that $P_1 \mid x \mid P_2$ reduces.

Case P_1 reduces or P_2 reduces

Because reduction is a congruence, $P_1 \mid x \mid P_2$ reduces.

Case [Tcut!]

We have

$$\frac{P_1 \vdash y : \bar{B}; \Gamma \quad P_2 \vdash \Delta; \Gamma, x : A}{y.P_1 \mid !x \mid P_2 \vdash \Delta; \Gamma} \text{ [cut!]}$$

where $P = y.P_1 \mid !x \mid P_2$.

Since $y.P_1 \mid !x \mid P_2$ is live, then P_2 is live.

By induction on $P_2 \vdash \Delta; \Gamma, x : A$ we conclude that either $P_2 \downarrow_z$ or P_2 reduces.

Case $P_2 \downarrow_z$ and $z \neq x$

Then

$$\frac{P_2 \downarrow_z \quad z \neq x}{(y.P_1 \mid !x \mid P_2) \downarrow_z} \text{ [cut!]}$$

Case $P_2 \downarrow_x$

Then, $y.P_1 \mid !x \mid P_2$ reduces (lemma []).

Case P_2 reduces

Because reduction is a congruence, $y.P_1 \mid !x \mid P_2$ reduces.

Case [Tshare]

We have

$$\frac{P_1 \vdash \Delta_1, x : \Box A; \Gamma \quad P_2 \vdash \Delta_2, x : \Box A; \Gamma}{\text{share } x \{P_1 \parallel P_2\} \vdash \Delta_1, \Delta_2, x : \Box A; \Gamma} \text{ [Tshare]}$$

where $P = \text{share } x \{P_1 \parallel P_2\}$ and $\Delta = \Delta_1, \Delta_2, x : \Box A$.

Since both P_1 and P_2 have a nonempty linear context, then both P_1 and P_2 are live (lemma B.1).

By applying the i.h. to $P_1 \vdash \Delta_1, x : \Box A; \Gamma$ and $P_2 \vdash \Delta_2, x : \Box A; \Gamma$ we conclude both

- $P_1 \downarrow_y$ or P_1 reduces, and
- $P_2 \downarrow_z$ or P_2 reduces

We have the following cases to consider.

Case A ($P_1 \downarrow_y$ and $y \neq x$) or ($P_2 \downarrow_z$ and $z \neq x$)

Suppose w.l.o.g. that $P_1 \downarrow_y$ and $y \neq x$.

Then

$$\frac{P_1 \downarrow_y \quad y \neq x}{(\text{share } x \{P_1 \parallel P_2\}) \downarrow_y} \text{ [share]}$$

Case B $P_1 \downarrow_x$ and $P_2 \downarrow_x$

We have the following two cases.

Case B1 $P_1 \downarrow_{x:\text{fwd}}$ or $P_2 \downarrow_{x:\text{fwd}}$

Suppose w.l.o.g. that $P_1 \downarrow_{x:\text{fwd}}$.

Observe that x occurs typed by $\Box A$ in the linear typing context of P_1 . Hence, we can apply lemma 6.9(5) in order to conclude that either (i) $P_1 \downarrow_y$ for $y \neq x$ or (ii) P_1 reduces.

If (i) go to case A. If (ii), go to case C.

Case B2 $P_1 \downarrow_{x:\text{act}}$ and $P_2 \downarrow_{x:\text{act}}$.

Then $(\text{share } x \{P_1 \parallel P_2\}) \downarrow_x$ (lemma 6.9(1)).

Case C P_1 reduces or P_2 reduces

Because reduction is a congruence, $\text{share } x \{P_1 \parallel P_2\}$ reduces.

Case [Tsum]

We have

$$\frac{P_1 \vdash \Delta; \Gamma \quad P_2 \vdash \Delta; \Gamma}{P_1 + P_2 \vdash \Delta; \Gamma} \text{ [Tsum]}$$

where $P = P_1 + P_2$.

Since $P_1 + P_2$ is live, then either P_1 is live or P_2 is live.

Assume w.l.o.g. that P_1 is live. By induction on $P_1 \vdash \Delta; \Gamma$ we conclude that either $P_1 \downarrow_x$ or P_1 reduces.

Case $P_1 \downarrow_x$

Then

$$\frac{P_1 \downarrow_x}{(P_1 + P_2) \downarrow_x} \text{ [sum]}$$

Case P_1 reduces

Then, $P_1 + P_2$ reduces because reduction is a congruence.

□

C PROGRESS FOR πSSL

In this section we extend the proof of deadlock-freedom to the language πSSL with locks.

Definition C.1 ($P \downarrow_x$ (Locks)). We extend $P \downarrow_x$ (definition B.2) with the following rules

$$\frac{P \downarrow_y \quad y \neq x}{\text{shareL } x \{P \parallel Q\} \downarrow_y} \text{ [shareL1]} \quad \frac{Q \downarrow_y \quad y \neq x}{\text{shareL } x \{P \parallel Q\} \downarrow_y} \text{ [shareL2]}$$

LEMMA [. 6.13(1)] Let $P \vdash \Delta, x : \Box A; \Gamma, Q \vdash \Delta, x : \Box A; \Gamma$. If $P \downarrow_{x:\text{act}}$, then $\text{shareL } x \{P \parallel Q\} \downarrow_{x:\text{act}}$.

PROOF. The proof is by induction on the derivation tree $P \downarrow_{x:\text{act}}$. We perform case analysis on the root rule. The cases are organised in the following groups

Group A The root rule is [act].

Group B The root rule is either a [par], [cut], [cut!], [share], [sum], [shareL] or [shareR].

Group C The root rule is [\equiv].

Group A We have

$$\frac{s(\mathcal{A}) = x}{\mathcal{A} \downarrow_{x:\text{act}}} \text{ [act]}$$

where $P = \mathcal{A}$.

Since $x : \Box A$ (in the linear typing context) we conclude that $P = \alpha; P'$, where α is either a read, write or unlock prefix.

Case α is either a read or write prefix

Observe that

$$\text{shareL } x \{ \alpha; P' \parallel Q \} \equiv \alpha; \underbrace{\text{shareL } x \{ P \parallel Q \}}_R \quad (\equiv [\text{leftA}])$$

Hence

$$\frac{\text{shareL } x \{ P \parallel Q \} \equiv \alpha; R \quad \frac{s(\alpha; R) = x}{\alpha; R \downarrow_{x:\text{act}}} [\text{act}]}{\text{shareL } x \{ P \parallel Q \} \downarrow_{x:\text{act}}} [\equiv]$$

Case $\alpha = x.\text{unlock}$. Observe that

$$\text{shareL } x \{ \text{unlock } x; P' \parallel Q \} \equiv \text{unlock } x; \underbrace{\text{share } x \{ P' \parallel Q \}}_R \quad (\equiv [\text{leftU}])$$

Hence

$$\frac{\text{share } x \{ P \parallel Q \} \equiv \text{unlock } x; R \quad \frac{s(\text{unlock } x; R) = x}{\text{unlock } x; R \downarrow_{x:\text{act}}} [\text{act}]}{\text{shareL } x \{ P \parallel Q \} \downarrow_{x:\text{act}}} [\equiv]$$

Group B Case [par]

We have

$$\frac{P_1 \downarrow_{x:\text{act}}}{(P_1 \parallel P_2) \downarrow_{x:\text{act}}} [\text{par}]$$

where $P = P_1 \parallel P_2$.

Since $P_1 \parallel P_2 \vdash \Delta, x : \boxtimes A; \Gamma$ we conclude that exists a partition Δ_1, Δ_2 of Δ for which $P_1 \vdash \Delta_1, x : \boxtimes A; \Gamma$ and $P_2 \vdash \Delta_2; \Gamma$. Observe that x lies in the linear typing context of P_1 and not of P_2 , because $P_1 \downarrow_{x:\text{act}}$.

We have

$$\begin{aligned} \text{shareL } x \{ P \parallel Q \} &= \text{shareL } x \{ (P_1 \parallel P_2) \parallel Q \} \\ &\equiv \underbrace{\text{shareL } x \{ P_1 \parallel Q \}}_R \parallel P_2 \quad (\equiv [\text{C-ShLM}]) \end{aligned}$$

By induction on $P_1 \downarrow_{x:\text{act}}$ we conclude that $R \downarrow_{x:\text{act}}$.

Hence

$$\frac{\text{shareL } x \{ P \parallel Q \} \equiv R \parallel P_2 \quad \frac{R \downarrow_{x:\text{act}}}{(R \parallel P_2) \downarrow_{x:\text{act}}} [\text{par}]}{(\text{shareL } x \{ P \parallel Q \}) \downarrow_{x:\text{act}}} [\equiv]$$

Case [cut]

We have

$$\frac{P_1 \downarrow_{x:\text{act}} \quad y \neq x}{(P_1 \mid y \mid P_2) \downarrow_{x:\text{act}}} [\text{cut}]$$

where $P = P_1 \mid y \mid P_2$.

Since $P_1 \mid y \mid P_2 \vdash \Delta, x : \boxtimes A; \Gamma$ we conclude that exists a partition Δ_1, Δ_2 of Δ and a type B for which $P_1 \vdash \Delta_1, y : \bar{B}, x : \boxtimes A; \Gamma$ and $P_2 \vdash \Delta_2, y : B; \Gamma$. Observe that x lies in the linear typing context of P_1 and not of P_2 , because $P_1 \downarrow_{x:\text{act}}$.

We have

$$\begin{aligned} \text{shareL } x \{P \parallel Q\} &= \text{shareL } x \{(P_1 \mid y \mid P_2) \parallel Q\} \\ &\equiv \underbrace{\text{shareL } x \{P_1 \parallel Q\}}_R \mid y \mid P_2 \end{aligned} \quad (\equiv [\text{C-CSHL1}])$$

By induction on $P_1 \downarrow_{x:\text{act}}$ we conclude that $R \downarrow_{x:\text{act}}$.

Hence

$$\frac{\text{shareL } x \{P \parallel Q\} \equiv R \mid y \mid P_2 \quad \frac{R \downarrow_x \quad y \neq x}{(R \mid y \mid P_2) \downarrow_{x:\text{act}}} [\text{cut}]}{(\text{shareL } x \{P \parallel Q\}) \downarrow_{x:\text{act}}} [\equiv]$$

Case [cut!]

We have

$$\frac{P_2 \downarrow_{x:\text{act}} \quad z \neq x}{(y.P_1 \mid !z \mid P_2) \downarrow_{x:\text{act}}} [\text{cut!}]$$

where $P = y.P_1 \mid !z \mid P_2$.

Since $y.P_1 \mid !z \mid P_2 \vdash \Delta, x : \boxtimes A; \Gamma$ we conclude that exists a type B for which $P_1 \vdash y : \bar{B}; \Gamma$ and $P_2 \vdash \Delta, x : \boxtimes A; \Gamma, z : B$.

We have

$$\begin{aligned} \text{shareL } x \{P \parallel Q\} &= \text{shareL } x \{(y.P_1 \mid !z \mid P_2) \parallel Q\} \\ &\equiv y.P_1 \mid !z \mid \underbrace{(\text{shareL } x \{P_2 \parallel Q\})}_R \end{aligned} \quad (\equiv [\text{C-C!ShL1}])$$

By induction on $P_2 \downarrow_{x:\text{act}}$ we conclude that $R \downarrow_{x:\text{act}}$.

Hence

$$\frac{\text{shareL } x \{P \parallel Q\} \equiv y.P_1 \mid !z \mid R \quad \frac{R \downarrow_{x:\text{act}} \quad z \neq x}{(y.P_1 \mid !z \mid R) \downarrow_{x:\text{act}}} [\text{cut!}]}{(\text{shareL } x \{P \parallel Q\}) \downarrow_{x:\text{act}}} [\equiv]$$

Case [share]

We have

$$\frac{P_1 \downarrow_{x:\text{act}} \quad y \neq x}{(\text{share } y \{P_1 \parallel P_2\}) \downarrow_{x:\text{act}}} [\text{share}]$$

where $P = \text{share } y \{P_1 \parallel P_2\}$.

Since $\text{share } y \{P_1 \parallel P_2\} \vdash \Delta, x : \boxtimes A; \Gamma$ we conclude that exists a partition Δ_1, Δ_2 of Δ and a type B for which $P_1 \vdash \Delta_1, y : \boxplus B, x : \boxtimes A; \Gamma$ and $P_2 \vdash \Delta_2, y : \boxplus B; \Gamma$. Observe that x lies in the linear typing context of P_1 and not of P_2 , because $P_1 \downarrow_{x:\text{act}}$.

We have

$$\begin{aligned} \text{shareL } x \{P \parallel Q\} &= \text{shareL } x \{\text{share } y \{P_1 \parallel P_2\} \parallel Q\} \\ &\equiv \text{share } y \underbrace{\{\text{shareL } x \{P_1 \parallel Q\} \parallel P_2\}}_R \end{aligned} \quad (\equiv [\text{C-ShShL1}])$$

By induction on $P_1 \downarrow_{x:\text{act}}$ we conclude that $R \downarrow_{x:\text{act}}$. Hence

$$\frac{\text{shareL } x \{P \parallel Q\} \equiv \text{shareL } y \{R \parallel P_2\} \quad \frac{R \downarrow_{x:\text{act}} \quad y \neq x}{(\text{shareL } y \{R \parallel P_2\}) \downarrow_{x:\text{act}}} \text{ [shareL1]}}{(\text{shareL } x \{P \parallel Q\}) \downarrow_{x:\text{act}}} \text{ [\equiv]}$$

Case [shareL1]

We have

$$\frac{P_1 \downarrow_{x:\text{act}} \quad y \neq x}{(\text{shareL } y \{P_1 \parallel P_2\}) \downarrow_{x:\text{act}}} \text{ [shareL1]}$$

where $P = \text{shareL } y \{P_1 \parallel P_2\}$.

Since $\text{shareL } y \{P_1 \parallel P_2\} \vdash \Delta, x : \boxtimes A; \Gamma$ we conclude that exists a partition Δ_1, Δ_2 of Δ and a type B for which $P_1 \vdash \Delta_1, y : \boxtimes B, x : \boxtimes A; \Gamma$ and $P_2 \vdash \Delta_2, y : \square B; \Gamma$. Observe that x lies in the linear typing context of P_1 and not of P_2 , because $P_1 \downarrow_{x:\text{act}}$.

We have

$$\begin{aligned} \text{shareL } x \{P \parallel Q\} &= \text{shareL } x \{\text{shareL } y \{P_1 \parallel P_2\} \parallel Q\} \\ &\equiv \text{shareL } y \underbrace{\{\text{shareL } x \{P_1 \parallel Q\} \parallel P_2\}}_R \end{aligned} \quad (\equiv \text{ [C-ShLShL1]})$$

By induction on $P_1 \downarrow_{x:\text{act}}$ we conclude that $R \downarrow_{x:\text{act}}$. Hence

$$\frac{\text{shareL } x \{P \parallel Q\} \equiv \text{shareL } y \{R \parallel P_2\} \quad \frac{R \downarrow_{x:\text{act}} \quad y \neq x}{(\text{shareL } y \{R \parallel P_2\}) \downarrow_{x:\text{act}}} \text{ [shareL1]}}{(\text{shareL } x \{P \parallel Q\}) \downarrow_{x:\text{act}}} \text{ [\equiv]}$$

Case [shareL2]

We have

$$\frac{P_2 \downarrow_{x:\text{act}} \quad y \neq x}{(\text{shareL } y \{P_1 \parallel P_2\}) \downarrow_{x:\text{act}}} \text{ [shareL2]}$$

where $P = \text{shareL } y \{P_1 \parallel P_2\}$.

Since $\text{shareL } y \{P_1 \parallel P_2\} \vdash \Delta, x : \boxtimes A; \Gamma$ we conclude that exists a partition Δ_1, Δ_2 of Δ and a type B for which $P_1 \vdash \Delta_1, y : \boxtimes B; \Gamma$ and $P_2 \vdash \Delta_2, y : \square B, x : \boxtimes A; \Gamma$. Observe that x lies in the linear typing context of P_2 and not of P_1 , because $P_2 \downarrow_{x:\text{act}}$.

We have

$$\begin{aligned} \text{shareL } x \{P \parallel Q\} &= \text{shareL } x \{\text{shareL } y \{P_1 \parallel P_2\} \parallel Q\} \\ &\equiv \text{shareL } y \{P_1 \parallel \underbrace{\text{shareL } x \{P_2 \parallel Q\}}_R\} \end{aligned} \quad (\equiv \text{ [C-ShLShL2]})$$

By induction on $P_2 \downarrow_{x:\text{act}}$ we conclude that $R \downarrow_{x:\text{act}}$. Hence

$$\frac{\text{shareL } x \{P \parallel Q\} \equiv \text{shareL } y \{P_1 \parallel R\} \quad \frac{R \downarrow_{x:\text{act}} \quad y \neq x}{(\text{shareL } y \{P_1 \parallel R\}) \downarrow_{x:\text{act}}} \text{ [shareL2]}}{(\text{shareL } x \{P \parallel Q\}) \downarrow_{x:\text{act}}} \text{ [\equiv]}$$

Case [sum]

We have

$$\frac{P_1 \downarrow_{x:\text{act}}}{(P_1 + P_2) \downarrow_{x:\text{act}}} \text{ [sum]}$$

where $P = P_1 + P_2$.

Since $P_1 + P_2 \vdash \Delta, x : \boxtimes A; \Gamma$ we conclude that $P_1 \vdash \Delta, x : \boxtimes A; \Gamma$ and $P_2 \vdash \Delta, x : \boxtimes A; \Gamma$.

We have

$$\begin{aligned} \text{shareL } x \{P \parallel Q\} &= \text{shareL } x \{(P_1 + P_2) \parallel Q\} \\ &\equiv \underbrace{\text{shareL } x \{P_1 \parallel Q\} + \text{shareL } x \{P_2 \parallel Q\}}_R \quad (\equiv [\text{D-ShLSm1}]) \end{aligned}$$

By induction on $P_1 \downarrow_{x:\text{act}}$ we conclude that $R \downarrow_{x:\text{act}}$.

Hence

$$\frac{\text{shareL } x \{P \parallel Q\} \equiv R + \text{shareL } x \{P_2 \parallel Q\} \quad \frac{(\text{shareL } x \{P_1 \parallel Q\}) \downarrow_{x:\text{act}}}{(R + \text{shareL } x \{P_2 \parallel Q\}) \downarrow_{x:\text{act}}} \text{ [sum]}}{(\text{shareL } x \{P \parallel Q\}) \downarrow_{x:\text{act}}} \text{ [\equiv]}$$

Group C We have

$$\frac{P \equiv P' \quad P' \downarrow_{x:\text{act}}}{P \downarrow_{x:\text{act}}} \text{ [\equiv]}$$

Since $P \vdash \Delta, x : \boxtimes A; \Gamma$, $P \equiv P'$ and structural congruence preserves typing, then $P' \vdash \Delta, x : \boxtimes A; \Gamma$.

By induction on $P' \downarrow_{x:\text{act}}$ we conclude that $\text{shareL } x \{P' \parallel Q\} \downarrow_{x:\text{act}}$.

Observe that

$$\text{shareL } x \{P \parallel Q\} \equiv \text{shareL } x \{P' \parallel Q\}$$

Hence

$$\frac{\text{shareL } x \{P \parallel Q\} \equiv \text{shareL } x \{P' \parallel Q\} \quad \text{shareL } x \{P' \parallel Q\} \downarrow_{x:\text{act}}}{\text{shareL } x \{P \parallel Q\} \downarrow_{x:\text{act}}} \text{ [\equiv]}$$

□

LEMMA [. 6.13(2)] *Let $P \vdash \Delta, x : A; \Gamma$ and suppose that $A \neq \boxtimes B$. If $P \downarrow_{x:\text{fwd}}$, then either (i) $P \downarrow_{y:\text{fwd}}$ for some $y : \bar{A} \in \Delta$ or (ii) P reduces.*

PROOF. The proof is by structural induction on the derivation tree $P \downarrow_{x:\text{fwd}}$. We perform case analysis on the root rule of the tree. We cover case [shareL1]. The argument is similar for [shareL2]. For the remaining cases see proof of lemma 6.9(5).

Case [shareL1]

We have

$$\frac{P_1 \downarrow_{x:\text{fwd}} \quad z \neq x}{(\text{share } z \{P_1 \parallel P_2\}) \downarrow_{x:\text{fwd}}} \text{ [shareL1]}$$

where $P = \text{shareL } z \{P_1 \parallel P_2\}$.

By inversion on the typing judgment $\text{shareL } z \{P_1 \parallel P_2\} \vdash \Delta, x : A; \Gamma$ we conclude that exists a partition Δ_1, Δ_2 of Δ and a type B s.t. $P_1 \vdash \Delta_1, x : A, z : \boxtimes B; \Gamma$ and $P_2 \vdash \Delta_2, z : \boxplus B; \Gamma$. Observe that x lies in the linear typing context of P_1 and not of P_2 because $P_1 \downarrow_x$.

By induction on $P_1 \downarrow_{x:\text{fwd}}$, we conclude that either (i) $P_1 \downarrow_{y:\text{fwd}}$ for some $y : \bar{A} \in \Delta_1, z : \boxtimes B$ or (ii) P_1 reduces.

Notice that, by hypothesis, $\bar{A} \neq \boxtimes B$. Hence, $y : \bar{A} \in \Delta_1$.

There are then two cases to consider.

Case (i) $P_1 \downarrow_{y:\text{fwd}}$ for some $y : \bar{A} \in \Delta_1$.

Then

$$\frac{P_1 \downarrow_{y:\text{fwd}} \quad y \neq z}{(\text{shareL } z \{P_1 \parallel P_2\}) \downarrow_{y:\text{fwd}}} \text{ [shareL1]}$$

Case (ii) P_1 reduces

Since reduction is a congruence, then $\text{shareL } z \{P_1 \parallel P_2\}$ reduces as well. \square

LEMMA C.2. *If $P \vdash \Delta; \Gamma$ and $\Delta \neq \emptyset$, then P is live.*

PROOF. The proof is by induction on the depth of the derivation tree $P \vdash \Delta; \Gamma$ and by case analysis on the root rule. It extends the proof of lemma B.1. The additional cases to analyse are [Tlock], [Tunlock], [TshareL], [TshareR], [TcellL], [TreadL] and [Twritel].

Cases [Tlock], [Tunlock], [TcellL], [TreadL] and [Twritel] are handled similarly to case [Tfwd].

Cases [TshareL] and [TshareR] are handled similarly to case [Tcut]. \square

LEMMA C.3. *Let $P \vdash \Delta; \Gamma$ be such that P is live. Either $P \downarrow_x$ or P reduces.*

PROOF. The proof is by structural induction on the derivation tree $P \vdash \Delta; \Gamma$. It remains to check cases [TshareL] and [TshareR]. We handle case [TshareL]. The analysis is symmetric for case [TshareR].

Case [TshareL]

We have

$$\frac{P_1 \vdash \Delta_1, x : \boxtimes A; \Gamma \quad P_2 \vdash \Delta_2, x : \boxtimes A; \Gamma}{\text{shareL } x \{P_1 \parallel P_2\} \vdash \Delta_1, \Delta_2, x : \boxtimes A; \Gamma} \text{ [TshareL]}$$

where $P = \text{shareL } x \{P_1 \parallel P_2\}$ and $\Delta = \Delta_1, \Delta_2, x : \boxtimes A$.

Since both P_1 and P_2 have a nonempty linear context, then both P_1 and P_2 are live (lemma C.2).

By applying the i.h. to $P_1 \vdash \Delta_1, x : \boxtimes A; \Gamma$ we conclude that either $P_1 \downarrow_y$ or P_1 reduces.

Case A $P_1 \downarrow_y$ and $y \neq x$ Then

$$\frac{P_1 \downarrow_y \quad y \neq x}{(\text{shareL } x \{P_1 \parallel P_2\}) \downarrow_y} \text{ [shareL1]}$$

Case B $P_1 \downarrow_x$

We have the following two cases.

Case B1 $P_1 \downarrow_{x:\text{fwd}}$.

Observe that x occurs typed by $\boxtimes A$ in the linear typing context of P_1 . Hence, we can apply lemma [] in order to conclude that either (i) $P_1 \downarrow_y$ for $y \neq x$ or (ii) P_1 reduces. If (i) go to case A. If (ii) go to case C.

Case B2 $P_1 \downarrow_{x:\text{act}}$.

Then $(\text{shareL } x \{P_1 \parallel P_2\}) \downarrow_x$ (lemma []).

Case C P_1 reduces or P_2 reduces

Because reduction is a congruence, $\text{shareL } x \{P_1 \parallel P_2\}$ reduces.

□

THEOREM (6.14 PROGRESS FOR π SSL). *Let $P \vdash \emptyset; \emptyset$ be a live process of π SSL. Then, P reduces.*

PROOF. Follows from lemma C.3. □

D CONFLUENCE

In this section we prove the auxiliary results necessary to establish confluence (theorem 7.8).

In subsection D.1 we define the interleaving $\mathcal{I}_x(-, -)$ (definition D.2) and the sum expansion $\mathcal{S}(-)$ (definition D.4) maps. We then prove a series of auxiliary results that establish lemma 7.4 and corollary 7.5 from the main body:

- $\mathcal{I}_x(P, Q) \equiv \text{share } x \{P \parallel Q\}$, for all P, Q . (lemma D.3).
- $\mathcal{S}(P) \equiv P$, for all P . (lemma D.5).
- Let $\mathcal{S}(P) = \sum_{i \in \mathcal{I}} P_i$ and $\mathcal{S}(Q) = \sum_{j \in \mathcal{J}} Q_j$. If $P \equiv Q$, then for all $i \in \mathcal{I}$, there exists $j \in \mathcal{J}$ s.t. $P_i \equiv_d Q_j$ and for all $j \in \mathcal{J}$, there exists $i \in \mathcal{I}$ s.t. $Q_j \equiv_d P_i$. (lemma D.6).
- Let $\mathcal{S}(P) = \sum_{i \in \mathcal{I}} P_i$. If $P \rightarrow Q$, then exists $\{Q_{ij}\}_{i \in \mathcal{I}, j \in \mathcal{J}_i}$ s.t. $Q \equiv \sum_{i \in \mathcal{I}, j \in \mathcal{J}_i} Q_{ij}$ and for all $i \in \mathcal{I}, j \in \mathcal{J}_i$, either $P_i \equiv_d Q_{ij}$ or $P_i \rightarrow_d Q_{ij}$. (lemma 7.4).

Subsection D.2 is then devoted to the proof of the diamond property for \rightarrow_d .

D.1 Sum Expansion

Definition D.1 (Sums). Given a nonempty indexed collection of processes $\{P_i\}_{i \in \mathcal{I}}$, we define $\sum_{i \in \mathcal{I}} P_i$ inductively on \mathcal{I} by

$$\sum_{i \in \{j\}} P_j \triangleq P_j \quad \sum_{i \in \mathcal{I} \cup \{j\}} P_i \triangleq \left(\sum_{i \in \mathcal{I}} P_i \right) + P_j$$

Definition D.2 (Interleaving Map). The interleaving map $\mathcal{I}_x(-, -)$, which takes two processes $P \vdash \Delta, x : \Box A; \Gamma, Q \vdash \Delta', x : \Box A; \Gamma$ and outputs sum of processes $\mathcal{I}_x(P, Q)$ is defined by cases on whether the proposition

- $\text{inter}(x, P, Q) \triangleq P = C[\alpha; P']$ and $Q = \mathcal{D}[\beta; Q']$, for some static contexts C, \mathcal{D} where the hole is not guarded by a sum and read, write or lock action prefixes α, β with subject x .

holds or not.

If $\text{inter}(x, P, Q)$ does not hold, then

$$\mathcal{I}_x(P, Q) \triangleq \text{share } x \{P \parallel Q\}$$

If $\text{inter}(x, P, Q)$ holds, then is defined by cases on the action prefixes α and β :

Case $\alpha = \text{lock } x$ and $\beta = \text{lock } x$.

$$\mathcal{I}_x(C[\text{lock } x; P'], \mathcal{D}[\text{lock } x; Q']) \triangleq$$

$$C[\mathcal{D}[\text{lock } x; (\text{shareL } x \{P' \parallel \text{lock } x; Q\})]] + C[\mathcal{D}[\text{lock } x; (\text{shareR } x \{\text{lock } x; P' \parallel Q'\})]]$$

Case $\alpha = \text{lock } x$ and β is a read/write action.

$$\mathcal{I}_x(C[\text{lock } x; P'], \mathcal{D}[\beta; Q']) \triangleq$$

$$C[\mathcal{D}[\text{lock } x; (\text{share } x \{P' \parallel \beta; Q'\})]] + C[\mathcal{D}[\beta; (\text{shareR } x \{\text{lock } x; P' \parallel Q'\})]]$$

Case α is a read/write action and $\beta = \text{lock } x$.

$$\begin{aligned} \mathcal{I}_x(C[\alpha; P'], \mathcal{D}[\text{lock } x; Q']) &\triangleq \\ &C[\mathcal{D}[\alpha; (\text{share } x \{P' \parallel \text{lock } x; Q\})]] + C[\mathcal{D}[\text{lock } x; (\text{shareR } x \{\alpha; P' \parallel Q'\})]] \end{aligned}$$

Case α and β are both read/write actions.

$$\begin{aligned} \mathcal{I}_x(C[\alpha; P'], \mathcal{D}[\beta; Q']) &\triangleq \\ &C[\mathcal{D}[\alpha; (\text{share } x \{P' \parallel \text{lock } x; Q\})]] + C[\mathcal{D}[\beta; (\text{share } x \{\text{lock } x; P' \parallel Q'\})]] \end{aligned}$$

LEMMA D.3. $\mathcal{I}_x(P, Q) \equiv \text{share } x \{P \parallel Q\}$, for all P, Q .

PROOF. The definition of the interleaving map is split into two cases, whether the predicate $\text{inter}(x, P, Q)$ holds or not.

Case $\neg \text{inter}(x, P, Q)$

By definition, $\mathcal{I}_x(P, Q) = \text{share } x \{P \parallel Q\}$.

Case $\text{inter}(x, P, Q)$

Then $P = C[\alpha; P']$ and $Q = \mathcal{D}[\beta; Q']$, form some static contexts C, \mathcal{D} where the hole is not guarded by a sum and read, write or lock action prefixes α, β with subject x . We perform case analysis on the action prefixes α and β . We cover the two illustrative cases.

Case $\alpha = \text{lock } x$ and $\beta = \text{lock } x$.

We have

$$\begin{aligned} \mathcal{I}_x(C[\text{lock } x; P'], \mathcal{D}[\text{lock } x; Q']) &= C[\mathcal{D}[\text{lock } x; (\text{shareL } x \{P' \parallel \beta; Q'\})]] + C[\mathcal{D}[\text{lock } x; (\text{shareR } x \{\alpha; P' \parallel Q'\})]] \\ &\equiv C[\mathcal{D}[\text{lock } x; (\text{shareL } x \{P' \parallel Q\}) + \text{lock } x; (\text{shareR } x \{P \parallel Q'\})]] \\ & \hspace{15em} (\equiv \text{distributive laws over sum}) \\ &\equiv C[\mathcal{D}[\text{share } x \{\text{lock } x; P' \parallel \text{lock } x; Q'\}]] \hspace{10em} (\equiv \text{share comm. conv. [LL]}) \\ &\equiv \text{share } x \{C[\text{lock } x; P'] \parallel \mathcal{D}[\text{lock } x; Q']\} \hspace{10em} (\equiv \text{comm. conv.}) \\ &= \text{share } x \{P \parallel Q\} \end{aligned}$$

Case α and β are both read/write actions.

We have

$$\begin{aligned} \mathcal{I}_x(C[\alpha; P'], \mathcal{D}[\beta; Q']) &= C[\mathcal{D}[\alpha; (\text{share } x \{P' \parallel \beta; Q'\})]] + C[\mathcal{D}[\beta; (\text{share } x \{\alpha; P' \parallel Q'\})]] \\ &\equiv C[\mathcal{D}[\alpha; (\text{share } x \{P' \parallel Q\}) + \beta; (\text{share } x \{P \parallel Q'\})]] \hspace{5em} (\equiv \text{distributive laws over sum}) \\ &\equiv C[\mathcal{D}[\text{share } x \{\alpha; P' \parallel \beta; Q'\}]] \hspace{10em} (\equiv \text{share comm. conv. [AA]}) \\ &\equiv \text{share } x \{C[\alpha; P'] \parallel \mathcal{D}[\beta; Q']\} \hspace{10em} (\equiv \text{comm. conv.}) \\ &= \text{share } x \{P \parallel Q\} \end{aligned}$$

□

Definition D.4 (Sum Expansion). Let \mathcal{X} stand for $\mathbf{0}$, $\text{fwd } x \ y$ or any action. Assume $\mathcal{S}(P) = \sum_{i \in \mathcal{I}} P_i$ and $\mathcal{S}(Q) = \sum_{j \in \mathcal{J}} Q_j$. Then

$$\begin{aligned} \mathcal{S}(\mathcal{X}) &\triangleq \mathcal{X} & \mathcal{S}(P \parallel Q) &\triangleq \sum_{i \in \mathcal{I}, j \in \mathcal{J}} P_i \parallel Q_j & \mathcal{S}(P \mid x \mid Q) &\triangleq \sum_{i \in \mathcal{I}, j \in \mathcal{J}} P_i \mid x \mid Q_j \\ \mathcal{S}(y.P \mid!x \mid Q) &\triangleq \sum_{j \in \mathcal{J}} y.P \mid!x \mid Q_j & \mathcal{S}(\text{shareL } x \{P \parallel Q\}) &\triangleq \sum_{i \in \mathcal{I}, j \in \mathcal{J}} \text{shareL } x \{P_i \parallel Q_j\} \\ \mathcal{S}(\text{shareR } x \{P \parallel Q\}) &\triangleq \sum_{i \in \mathcal{I}, j \in \mathcal{J}} \text{shareR } x \{P_i \parallel Q_j\} \\ \mathcal{S}(\text{share } x \{P \parallel Q\}) &\triangleq \sum_{i \in \mathcal{I}, j \in \mathcal{J}} \mathcal{I}_x(P_i, Q_j) & \mathcal{S}(P + Q) &\triangleq \sum_{i \in \mathcal{I}} P_i + \sum_{j \in \mathcal{J}} Q_j \end{aligned}$$

LEMMA D.5. $\mathcal{S}(P) \equiv P$, for all P .

PROOF. By induction on P . We perform case analysis on its principal form and handle some illustrative cases.

Case \mathcal{X} , where \mathcal{X} is either $\mathbf{0}$, forwarder or an action.

Then $\mathcal{S}(\mathcal{X}) = \mathcal{X}$.

Case $P \parallel Q$.

Suppose $\mathcal{S}(P) = \sum_{i \in \mathcal{I}} P_i$ and $\mathcal{S}(Q) = \sum_{j \in \mathcal{J}} Q_j$.

By induction on P and Q we conclude that $\sum_{i \in \mathcal{I}} P_i \equiv P$ and $\sum_{j \in \mathcal{J}} Q_j \equiv Q$.

Then

$$\mathcal{S}(P \parallel Q) = \sum_{i \in \mathcal{I}, j \in \mathcal{J}} P_i \parallel Q_j \equiv \left(\sum_{i \in \mathcal{I}} P_i \right) \parallel \left(\sum_{j \in \mathcal{J}} Q_j \right) \equiv P \parallel Q$$

Case $\text{share } x \{P \parallel Q\}$.

Suppose $\mathcal{S}(P) = \sum_{i \in \mathcal{I}} P_i$ and $\mathcal{S}(Q) = \sum_{j \in \mathcal{J}} Q_j$.

By induction on P and Q we conclude that $\sum_{i \in \mathcal{I}} P_i \equiv P$ and $\sum_{j \in \mathcal{J}} Q_j \equiv Q$.

Then

$$\begin{aligned} \mathcal{S}(\text{share } x \{P \parallel Q\}) &= \sum_{i \in \mathcal{I}, j \in \mathcal{J}} \mathcal{I}_x(P_i, Q_j) \\ &\equiv \sum_{i \in \mathcal{I}, j \in \mathcal{J}} \text{share } x \{P_i \parallel Q_j\} && \text{(by lemma D.3)} \\ &\equiv \text{share } x \left\{ \left(\sum_{i \in \mathcal{I}} P_i \right) \parallel \left(\sum_{j \in \mathcal{J}} Q_j \right) \right\} \\ &\equiv \text{share } x \{P \parallel Q\} \end{aligned}$$

Case $P + Q$.

Suppose $\mathcal{S}(P) = \sum_{i \in \mathcal{I}} P_i$ and $\mathcal{S}(Q) = \sum_{j \in \mathcal{J}} Q_j$.

By induction on P and Q we conclude that $\sum_{i \in \mathcal{I}} P_i \equiv P$ and $\sum_{j \in \mathcal{J}} Q_j \equiv Q$.

Then

$$\mathcal{S}(P + Q) = \left(\sum_{i \in \mathcal{I}} P_i \right) + \left(\sum_{j \in \mathcal{J}} Q_j \right) \equiv P + Q$$

□

LEMMA D.6. Let $\mathcal{S}(P) = \sum_{i \in \mathcal{I}} P_i$ and $\mathcal{S}(Q) = \sum_{j \in \mathcal{J}} Q_j$. If $P \equiv Q$, then

- for all $i \in \mathcal{I}$, there exists $j \in \mathcal{J}$ s.t. $P_i \equiv_d Q_j$; and
- for all $j \in \mathcal{J}$, there exists $i \in \mathcal{I}$ s.t. $Q_j \equiv_d P_i$.

PROOF. By induction on the structure of the derivation tree $P \equiv Q$. We perform case analysis on the root rule. We handle some representative cases.

Case congruence rule for mix, $P \equiv P', Q \equiv Q' \supset P \parallel Q \equiv P' \parallel Q'$.

Suppose $\mathcal{S}(P) = \sum_{i \in \mathcal{I}} P_i$, $\mathcal{S}(Q) = \sum_{j \in \mathcal{J}} Q_j$, $\mathcal{S}(P') = \sum_{i' \in \mathcal{I}'} P'_{i'}$ and $\mathcal{S}(Q') = \sum_{j' \in \mathcal{J}'} Q'_{j'}$.

Then $\mathcal{S}(P \parallel Q) = \sum_{i \in \mathcal{I}, j \in \mathcal{J}} P_i \parallel Q_j$ and $\mathcal{S}(P' \parallel Q') = \sum_{i' \in \mathcal{I}', j' \in \mathcal{J}'} P'_{i'} \parallel Q'_{j'}$.

Let $i \in \mathcal{I}$ and $j \in \mathcal{J}$.

By induction on $P \equiv P'$, there exists $i' \in \mathcal{I}'$ s.t. $P_i \equiv_d P'_{i'}$.

By induction on $Q \equiv Q'$, there exists $j' \in \mathcal{J}'$ s.t. $Q_j \equiv_d Q'_{j'}$.

Since \equiv_d is a congruence, then $P_i \parallel Q_j \equiv_d P'_{i'} \parallel Q'_{j'}$.

Similarly, for all $i' \in \mathcal{I}'$, $j' \in \mathcal{J}'$, there exists $i \in \mathcal{I}$, $j \in \mathcal{J}$ s.t. $P'_{i'} \parallel Q'_{j'} \equiv_d P_i \parallel Q_j$.

The other congruence laws are handled similarly.

Case commutativity mix, $P \parallel Q \equiv Q \parallel P$. Suppose $\mathcal{S}(P) = \sum_{i \in \mathcal{I}} P_i$ and $\mathcal{S}(Q) = \sum_{j \in \mathcal{J}} Q_j$.

Then $\mathcal{S}(P \parallel Q) = \sum_{i \in \mathcal{I}, j \in \mathcal{J}} P_i \parallel Q_j$ and $\mathcal{S}(Q \parallel P) = \sum_{i \in \mathcal{I}, j \in \mathcal{J}} Q_j \parallel P_i$.

Notice that for all $i \in \mathcal{I}$, $j \in \mathcal{J}$, $P_i \parallel Q_j \equiv_d Q_j \parallel P_i$.

Case [CSm] $P \mid x \mid (Q + R) \equiv (P \mid x \mid Q) + (P \mid x \mid R)$.

Notice that $\mathcal{S}(P \mid x \mid (Q + R)) = \mathcal{S}((P \mid x \mid Q) + (P \mid x \mid R))$.

Case [0Sm] $\mathbf{0} + \mathbf{0} \equiv \mathbf{0}$.

Notice that $\mathcal{S}(\mathbf{0} + \mathbf{0}) = \mathbf{0} + \mathbf{0}$ and $\mathcal{S}(\mathbf{0}) = \mathbf{0}$.

□

LEMMA 7.4. Let $\mathcal{S}(P) = \sum_{i \in \mathcal{I}} P_i$. If $P \rightarrow Q$, then exists $\{Q_{ij}\}_{i \in \mathcal{I}, j \in \mathcal{J}_i}$ s.t. $Q \equiv \sum_{i \in \mathcal{I}, j \in \mathcal{J}_i} Q_{ij}$ and for all $i \in \mathcal{I}$, $j \in \mathcal{J}_i$, either $P_i \equiv_d Q_{ij}$ or $P_i \rightarrow_d Q_{ij}$.

PROOF. By induction on the structure of the derivation. We perform case analysis on the root rule.

Case [1⊥] `close x |x| wait x; P' → P'`.

We have $\mathcal{S}(\text{close } x \mid x \mid \text{wait } x; P') = \text{close } x \mid x \mid \text{wait } x; P'$.

Notice that `close x |x| wait x; P' →d P'`.

Case [fwd], [⊗⊗], [⊗⊕], [⊗⊗_r], [!], [C!], [∃V] [⊗⊗f], [⊗⊗r], [⊗⊗w], [⊗⊗l], [⊗⊗u], [⊗⊗r], [⊗⊗w].

Similar to case [1⊥].

Case [cong].

Suppose that [cong] is applied to a mix constructor. The analysis is similar for the other static operators.

We have

$$\frac{P \rightarrow P'}{P \parallel Q \rightarrow P' \parallel Q}$$

Suppose $\mathcal{S}(P) = \sum_{i \in \mathcal{I}} P_i$ and $\mathcal{S}(Q) = \sum_{j \in \mathcal{J}} Q_j$.

By induction on $P \rightarrow P'$ we conclude that exists $\{P'_{ik}\}_{i \in \mathcal{I}, k \in \mathcal{K}_i}$ s.t. $P' \equiv \sum_{i \in \mathcal{I}, k \in \mathcal{K}_i} P'_{ik}$ and for all $i \in \mathcal{I}$, $k \in \mathcal{K}_i$, $P_i (\rightarrow_d \cup \equiv_d) P'_{ik}$.

Consider the collection $\{P'_{ik} \parallel Q_j\}_{i \in \mathcal{I}, k \in \mathcal{K}_i, j \in \mathcal{J}}$.

Notice that

$$\begin{aligned} \sum_{i \in \mathcal{I}, k \in \mathcal{K}_i, j \in \mathcal{J}} P_{ik} \parallel Q_j &\equiv \left(\sum_{i \in \mathcal{I}, k \in \mathcal{K}_i} P_{ik} \right) \parallel \left(\sum_{j \in \mathcal{J}} Q_j \right) \\ &\equiv P' \parallel Q \end{aligned}$$

Furthermore, for all $i \in \mathcal{I}$, $k \in \mathcal{K}_i$, $j \in \mathcal{J}$, $P_i \parallel Q_j (\rightarrow_d \cup \equiv_d) P'_{ik} \parallel Q_j$.

Case [+par] $P \twoheadrightarrow P' \quad Q \twoheadrightarrow Q' \supset P + Q \twoheadrightarrow P' + Q'$.

Suppose $\mathcal{S}(P) = \sum_{i \in \mathcal{I}} P_i$ and $\mathcal{S}(Q) = \sum_{j \in \mathcal{J}} Q_j$.

Then $\mathcal{S}(P + Q) = (\sum_{i \in \mathcal{I}} P_i) + (\sum_{j \in \mathcal{J}} Q_j)$.

By induction on $P \twoheadrightarrow P'$ we conclude that exists $\{P'_{ik}\}_{i \in \mathcal{I}, k \in \mathcal{K}_i}$ s.t. $P' \equiv \sum_{i \in \mathcal{I}, k \in \mathcal{K}_i} P'_{ik}$ and $P_i (\equiv_d \cup \rightarrow_d) P'_{ik}$, for all $i \in \mathcal{I}, k \in \mathcal{K}_i$.

By induction on $Q \twoheadrightarrow Q'$ we conclude that exists $\{Q'_{jl}\}_{j \in \mathcal{J}, l \in \mathcal{L}_j}$ s.t. $Q' \equiv \sum_{j \in \mathcal{J}, l \in \mathcal{L}_j} Q'_{jl}$ and $Q_j (\equiv_d \cup \rightarrow_d) Q'_{jl}$, for all $j \in \mathcal{J}, l \in \mathcal{L}_j$.

Notice that

$$\left(\sum_{i \in \mathcal{I}, k \in \mathcal{K}_i} P'_{ik} \right) + \left(\sum_{j \in \mathcal{J}, l \in \mathcal{L}_j} Q'_{jl} \right) \equiv P' + Q'$$

Case [=] $P \equiv P' \twoheadrightarrow Q' \equiv Q \supset P \twoheadrightarrow Q$.

Suppose $\mathcal{S}(P) = \sum_{i \in \mathcal{I}} P_i$ and $\mathcal{S}(P') = \sum_{i' \in \mathcal{I}'} P'_{i'}$.

By induction on $P' \twoheadrightarrow Q'$ we conclude that exists $\{Q'_{i'j'}\}_{i' \in \mathcal{I}', j' \in \mathcal{J}'_{i'}}$ s.t. $Q' \equiv \sum_{i' \in \mathcal{I}', j' \in \mathcal{J}'_{i'}} Q'_{i'j'}$ and $P'_{i'} (\rightarrow_d \cup \equiv_d) Q'_{i'j'}$, for all $i' \in \mathcal{I}', j' \in \mathcal{J}'_{i'}$.

Define $\mathcal{K}_i = \{i' \in \mathcal{I}' \mid P_i \equiv_d P'_{i'}\}$ and $\mathcal{K}_i^{-1} = \{i \in \mathcal{I} \mid i' \in \mathcal{K}_i\}$.

Since $P \equiv P'$, lemma ?? implies that each \mathcal{K}_i and \mathcal{K}_i^{-1} is nonempty.

Define the collection $\{R_{ii'j'}\}_{i \in \mathcal{I}, i' \in \mathcal{K}_i, j' \in \mathcal{J}'_{i'}}$ by $R_{ii'j'} \triangleq Q'_{i'j'}$.

Notice that for all $i \in \mathcal{I}, i' \in \mathcal{K}_i, j' \in \mathcal{J}'_{i'}$ we have $P_i \equiv_d P'_{i'}$ and $P'_{i'} (\rightarrow_d \cup \equiv_d) Q'_{i'j'} = R_{ii'j'}$, hence $P_i (\rightarrow_d \cup \equiv_d) R_{ii'j'}$.

Furthermore

$$\begin{aligned} \sum_{i \in \mathcal{I}, i' \in \mathcal{K}_i, j' \in \mathcal{J}'_{i'}} R_{ii'j'} &= \sum_{i' \in \mathcal{I}', i \in \mathcal{K}_i^{-1}, j' \in \mathcal{J}'_{i'}} R_{ii'j'} \\ &= \sum_{i' \in \mathcal{I}', j' \in \mathcal{J}'_{i'}} \left(\sum_{i \in \mathcal{K}_i^{-1}} R_{ii'j'} \right) \\ &\equiv \sum_{i' \in \mathcal{I}', j' \in \mathcal{J}'_{i'}} Q'_{i'j'} && \text{(idempotency of sum)} \\ &\equiv Q' \equiv Q \end{aligned}$$

□

COROLLARY 7.5. *Suppose $P \twoheadrightarrow Q$ and $P \twoheadrightarrow R$. There are sum of processes $\sum_{i \in \mathcal{I}} P_i \equiv P$, $\sum_{i \in \mathcal{I}} Q_i \equiv Q$ and $\sum_{i \in \mathcal{I}} R_i \equiv R$ s.t. the following property holds*

(1) *For all $i \in \mathcal{I}$, $P_i (\rightarrow_d \cup \equiv_d) Q_i$ and $P_i (\rightarrow_d \cup \equiv_d) R_i$.*

PROOF. Let $\mathcal{S}(P) = \{P'_i\}_{1 \leq i \leq n}$. By applying lemma 7.4 to $P \twoheadrightarrow Q$ and $P \twoheadrightarrow R$ we conclude that exists $\{Q'_{ij}\}_{1 \leq i \leq n, 1 \leq j \leq n_i}$ and $\{R'_{ik}\}_{1 \leq i \leq n, 1 \leq k \leq m_i}$ s.t. $Q \equiv \sum_{1 \leq i \leq n, 1 \leq j \leq n_i} Q'_{ij}$, $R \equiv \sum_{1 \leq i \leq n, 1 \leq k \leq m_i} R'_{ik}$, $P_i (\rightarrow_d \cup \equiv_d) Q'_{ij}$, for all $1 \leq i \leq n, 1 \leq j \leq n_i$ and $P_i (\rightarrow_d \cup \equiv_d) R'_{ik}$, for all $1 \leq i \leq n, 1 \leq k \leq m_i$.

Define the collections $\{P_{ix}\}_{1 \leq i \leq n, 1 \leq x \leq \max(m_i, l_i)}$, $\{Q_{ix}\}_{1 \leq i \leq n, 1 \leq x \leq \max(m_i, l_i)}$ and $\{R_{ix}\}_{1 \leq i \leq n, 1 \leq x \leq \max(m_i, l_i)}$ by

$$P_{ix} \triangleq P'_i \quad Q_{ix} \triangleq \begin{cases} Q'_{ij}, & x \leq m_i \\ Q'_{im_i}, & \text{otherwise} \end{cases} \quad R_{ix} \triangleq \begin{cases} R'_{ij}, & x \leq l_i \\ R'_{il_i}, & \text{otherwise} \end{cases}$$

$$\begin{array}{c}
\frac{}{\lambda x. P \in \text{Ctxt}} \text{ [cons]} \quad \frac{}{\lambda x. x \in \text{Ctxt}} \text{ [id]} \\
\\
\frac{\lambda x_1 \dots x_n. f \in \text{Ctxt} \quad \lambda y_1 \dots y_m. g \in \text{Ctxt}}{\lambda x_1 \dots x_n y_1, \dots y_m. (f \parallel g) \in \text{Ctxt}} \text{ [mix]} \\
\\
\frac{\lambda x_1 \dots x_n. f \in \text{Ctxt} \quad \lambda y_1 \dots y_m. g \in \text{Ctxt}}{\lambda x_1 \dots x_n y_1 \dots y_m. (f \mid z \mid g) \in \text{Ctxt}} \text{ [cut]} \\
\\
\frac{\lambda y_1 \dots y_m. g \in \text{Ctxt}}{\lambda y_1 \dots y_m. (x.P \mid z \mid g) \in \text{Ctxt}} \text{ [cut!]} \\
\\
\frac{\lambda x_1 \dots x_n. f \in \text{Ctxt} \quad \lambda y_1 \dots y_m. g \in \text{Ctxt}}{\lambda x_1 \dots x_n y_1 \dots y_m. (\text{share } z \{f \parallel g\}) \in \text{Ctxt}} \text{ [share]} \\
\\
\frac{\lambda x_1 \dots x_n. f \in \text{Ctxt} \quad \lambda y_1 \dots y_m. g \in \text{Ctxt}}{\lambda x_1 \dots x_n y_1 \dots y_m. (\text{shareL } z \{f \parallel g\}) \in \text{Ctxt}} \text{ [shareL]} \\
\\
\frac{\lambda x_1 \dots x_n. f \in \text{Ctxt} \quad \lambda y_1 \dots y_m. g \in \text{Ctxt}}{\lambda x_1 \dots x_n y_1 \dots y_m. (\text{shareR } z \{f \parallel g\}) \in \text{Ctxt}} \text{ [shareR]} \\
\\
\frac{\lambda x_1 \dots x_n. f \in \text{Ctxt} \quad \lambda y_1 \dots y_m. g \in \text{Ctxt}}{\lambda x_1 \dots x_n y_1, \dots y_m. (f + g) \in \text{Ctxt}} \text{ [sum]}
\end{array}$$

Fig. 11. n -ary Static Contexts

Notice that

$$\begin{aligned}
\sum_{1 \leq i \leq n, 1 \leq x \leq \max(m_i, l_i)} P_{ix} &= \sum_{1 \leq i \leq n} \left(\sum_{1 \leq x \leq \max(m_i, l_i)} P_{ix} \right) \\
&\equiv \sum_{1 \leq i \leq n} P'_i && \text{(idempotency of sum)} \\
&\equiv P
\end{aligned}$$

Similarly, one may derive $\sum_{1 \leq i \leq n, 1 \leq x \leq \max(m_i, l_i)} Q_{ix} \equiv Q$ and $\sum_{1 \leq i \leq n, 1 \leq x \leq \max(m_i, l_i)} R_{ix} \equiv R$. \square

D.2 Diamond \rightarrow_d

Definition D.7. The set Ctxt of n -ary ($n \geq 1$) static contexts is the subset of n -ary maps $\text{Proc}^n \rightarrow \text{Proc}$ inductively defined by the rules of figure 11.

We use the letters $C, \mathcal{D}, \mathcal{E}, \dots$ to denote elements of Ctxt and $C[P_1, \dots, P_n]$ to denote the application of the context C to the arguments P_1, \dots, P_n .

If a context C does not reduce, we write $C \rightarrow_d$.

Definition D.8 (Predex). The set of predexes is defined by

$$\begin{aligned}
R & ::= \mathcal{A} \mid x \mid \mathcal{B}, s(\mathcal{A}) = s(\mathcal{B}) = x \\
& \mid y.P \mid !x \mid \text{call } x(y); Q \\
& \mid \text{fwd } x \ y \\
& \mid \text{fwd } x \ y \mid y \mid \mathcal{D}[R_1, \dots, R_n] \\
& \mid C[R_1, \dots, R_m] \mid x \mid \text{fwd } x \ y \mid y \mid \mathcal{D}[R'_1, \dots, R'_n]
\end{aligned}$$

where $C, \mathcal{D} \rightarrow_d$.

LEMMA D.9 (PREDEX DECOMPOSITION). *For each process $P \vdash \Delta; \Gamma$ there are predexes R_1, \dots, R_k and a static context C such that $P \equiv_d C[R_1, \dots, R_k]$ and $C \rightarrow$.*

PROOF. By induction on the structure of the typing derivation tree for $P \vdash \Delta; \Gamma$. We perform case analysis on the root rule.

Case [T0]

Then $C = -$ and $k = 0$.

Similar analysis for the rules which introduce an action or a forwarder.

Case [Tmix]

Let $P = P_1 \parallel P_2$.

By i.h., $P_1 \equiv_d C_1[R_1, \dots, R_p]$ and $P_2 \equiv_d C_2[S_1, \dots, S_q]$.

Let $C = C_1 \parallel C_2$.

Observe that $P \equiv_d C[R_1, \dots, R_p, S_1, \dots, S_q]$, with $k = p + q$.

Case [Tsum]

Let $P = P_1 + P_2$.

By i.h., $P_1 \equiv_d C_1[R_1, \dots, R_p]$ and $P_2 \equiv_d C_2[S_1, \dots, S_q]$.

Let $C = C_1 + C_2$.

Observe that $P \equiv_D C[R_1, \dots, R_p, S_1, \dots, S_q]$, with $k = p + q$.

Case [Tshare]

Let $P = \text{share } x \{P_1 \parallel P_2\}$.

By i.h., $P_1 \equiv_d C_1[R_1, \dots, R_p]$ and $P_2 \equiv_d C_2[S_1, \dots, S_q]$.

Let $C = \text{share } x \{C_1 \parallel C_2\}$.

Observe that $P \equiv_d C[R_1, \dots, R_p, S_1, \dots, S_q]$, with $k = p + q$.

Case [TshareL]

Let $P = \text{shareL } x \{P_1 \parallel P_2\}$.

By i.h., $P_1 \equiv_d C_1[R_1, \dots, R_p]$ and $P_2 \equiv_d C_2[S_1, \dots, S_q]$.

Let $C = \text{shareL } x \{C_1 \parallel C_2\}$.

Observe that $P \equiv_d C[R_1, \dots, R_p, S_1, \dots, S_q]$, with $k = p + q$.

Case [TshareR]

Similar to case [TshareL].

Case [Tcut]

Let $P = P_1 \mid x \mid P_2$.

By i.h., $P_1 \equiv_d C_1[R_1, \dots, R_p]$ and $P_2 \equiv_d C_2[S_1, \dots, S_q]$.

We have the following cases to consider.

Case Either $R_i = \text{fwd } x \ z$ for some $1 \leq i \leq p$ or $Q_j = \text{fwd } x \ z$ for some $1 \leq j \leq q$.

Suppose w.l.o.g. that $R_i = \text{fwd } x \ z$.

We have two cases to consider, depending on whether (i) $\text{fwd } x \ z$ is guarded by either a share, share-left or share-right on x or a sum in C_1 or (ii) not.

If (i), then cut $P_1 \mid x \mid P_2$ does not yield a predex. Let $C = C_1 \mid x \mid C_2$.

Suppose (ii). Then

$$\begin{aligned} P &= P_1 \mid x \mid P_2 \\ &\equiv_d C_1[R_1, \dots, \text{fwd } x \ z, \dots, R_p] \mid x \mid C_2[S_1, \dots, S_q] \\ &\equiv_d C_1[R_1, \dots, \text{fwd } x \ z \mid x \mid C_2[S_1, \dots, S_q], \dots, R_p] \end{aligned}$$

with $k = p$.

Observe that $\text{fwd } x \ z \mid x \mid C_2[S_1, \dots, S_q]$ is a predex.

Case Either $R_i = \text{fwd } x \ z \mid z \mid \mathcal{D}[M_1, \dots, M_n]$ or $Q_j = \text{fwd } x \ z \mid z \mid \mathcal{D}[M_1, \dots, M_n]$ for some $1 \leq i \leq p, 1 \leq j \leq q$.

Suppose w.l.o.g. that $R_i = \text{fwd } x \ z \mid z \mid \mathcal{D}[M_1, \dots, M_n]$

We have two cases to consider, depending on whether (i) $\text{fwd } x \ z$ is guarded by either a share, share-left or share-right on x or a sum in C_1 or (ii) not.

If (i), then cut $P_1 \mid x \mid P_2$ does not yield a predex. Let $C = C_1 \mid x \mid C_2$.

Suppose (ii). Then

$$\begin{aligned} P &= P_1 \mid x \mid P_2 \\ &\equiv_d C_1[R_1, \dots, \text{fwd } x \ z \mid z \mid \mathcal{D}[M_1, \dots, M_n], \dots, R_p] \mid x \mid C_2[S_1, \dots, S_q] \\ &\equiv_D C_1[R_1, \dots, \text{fwd } x \ z \mid z \mid \mathcal{D}[M_1, \dots, M_n] \mid x \mid C_2[S_1, \dots, S_q], \dots, R_p] \end{aligned}$$

with $k = p$.

Observe that $\text{fwd } x \ z \mid z \mid \mathcal{D}[M_1, \dots, M_n] \mid x \mid C_2[S_1, \dots, S_q]$ is a predex.

Case There is no C'_1 s.t. $C_1 \equiv_d C'_1[\mathcal{A}]$, for some static context where $s(\mathcal{A}) = x$ and \mathcal{A} is neither guarded by share, share-left or share-right on x nor by a sum.

Then, the cut $P_1 \mid x \mid P_2$ does not yield a predex.

Case There is no C'_2 s.t. $C_2 \equiv_d C'_2[\mathcal{B}]$, for some static context where $s(\mathcal{B}) = x$ and \mathcal{B} is neither guarded by share, share-left or share-right on x nor by a sum.

Case $C_1 \equiv_d C'_1[\mathcal{A}], C_2 \equiv_d C'_2[\mathcal{B}], s(\mathcal{A}) = s(\mathcal{B}) = x, C'_1, C'_2$ are static contexts in which \mathcal{A}, \mathcal{B} are neither guarded by share, share-left or share-right on x nor by a sum.

Then

$$\begin{aligned} P &= P_1 \mid x \mid P_2 \\ &\equiv_d C'_1[\mathcal{A}, R_1, \dots, R_p] \mid x \mid C'_2[\mathcal{B}, S_1, \dots, S_q] \\ &\equiv_d C'_1[\mathcal{A} \mid x \mid C'_2[\mathcal{B}, S_1, \dots, S_q], R_1, \dots, R_p] \\ &\equiv_d C'_1[C'_2[\mathcal{A} \mid x \mid \mathcal{B}, S_1, \dots, S_q], R_1, \dots, R_p] \end{aligned}$$

Let $C = \lambda x y_1 \dots, y_q z_1 \dots z_p. C'_1[C'_2[x, y_1, \dots, y_q], z_1, \dots, z_p]$.

Case [Tcut!]

Let $P = y.P_1 \mid x \mid P_2$.

By i.h., $P_2 \equiv C_2[S_1, \dots, S_q]$.

Observe that x occurs guarded in S_i , for all $1 \leq i \leq q$.

We have two cases to consider, depending on whether (i) x does not occur unguarded in C_2 or (ii) x occurs unguarded in C_2 .

Suppose (i). Then

$$\begin{aligned} P &= y.P_1 \mid x \mid P_2 \\ &\equiv y.P_1 \mid x \mid C_2[S_1, \dots, S_q] \end{aligned}$$

Let $C = y.P_1 \mid !x \mid C_2$.

Suppose (ii). Then

$$\begin{aligned}
P &= y.P_1 \mid !x \mid P_2 \\
&\equiv_d y.P_1 \mid !x \mid C_2[S_1, \dots, S_q] \\
&= y.P_1 \mid !x \mid C'_2[\text{call } x(y_1); Q_1, \dots, \text{call } x(y_n); Q_n, M_1, \dots, M_m, S_1, \dots, S_q] \quad (\text{where } x \notin n(C'_2)) \\
&\equiv_d C'_2[Q'_1, \dots, Q'_n, M'_1, \dots, M'_m, S'_1, \dots, S'_q]
\end{aligned}$$

where $Q'_i = y.P_1 \mid !x \mid Q_i$, $M'_i = y.P_1 \mid !x \mid M_i$ and $S'_i = y.P_1 \mid !x \mid S_i$.

Let $C = \lambda x_1 \dots x_n y_1 \dots y_q. C'_2[x_1, \dots, x_n, M'_1, \dots, M'_m, y.P_1 \mid !x \mid y_1, \dots, y.P_1 \mid !x \mid y_q]$.

□

LEMMA D.10 (*n*-WAY DIAMOND PROPERTY FOR PREDEXES). *If P is a predex and $P \rightarrow_d Q_1, \dots, Q_k$ there exists R s.t. for all $1 \leq i \leq k$, either $Q_i \equiv_d R$ or $Q_i \xrightarrow{m}_d R$ where $1 \leq m < k$.*

PROOF. By induction on the structure of the predex P .

Case $\mathcal{A} \mid x \mid \mathcal{B}$.

There is an unique \rightarrow_d -reduction modulo congruence, hence the conclusion is immediate.

Case $y.P \mid !x \mid \text{call } x(y); Q$.

There is an unique \rightarrow_d -reduction modulo congruence, hence the conclusion is immediate.

Case $\text{fwd } x \ y$.

There is no \rightarrow_d -reduction, trivial.

Case $\text{fwd } x \ y \mid y \mid C[R_1, \dots, R_n]$.

Define the subsets $\mathcal{I}_1, \dots, \mathcal{I}_n, \mathcal{I}_{\text{fwd } x \ y}$ of $\mathcal{I} = \{1, \dots, k\}$ by

$$\begin{aligned}
\mathcal{I}_j &\triangleq \{i \in \mathcal{I} \mid Q_i = \text{fwd } x \ y \mid y \mid C[R_1, \dots, R'_{ij}, \dots, R_n] \text{ and } R_j \rightarrow R'_{ij}, 1 \leq j \leq n \\
\mathcal{I}_{\text{fwd } x \ y} &\triangleq \{i \in \mathcal{I} \mid Q_i = \{x/y\}(C[R_1, \dots, R_n])\}
\end{aligned}$$

Observe that since $C \rightarrow_d$, then $\mathcal{I}_1 \cup \dots \cup \mathcal{I}_n \cup \mathcal{I}_{\text{fwd } x \ y} = \mathcal{I}$. Furthermore, the subsets $\mathcal{I}_1, \dots, \mathcal{I}_n, \mathcal{I}_{\text{fwd } x \ y}$ are pairwise disjoint.

Suppose \mathcal{I}_j is nonempty, for some $1 \leq j \leq n$. By induction on R_j we conclude that exists R_j^* s.t. either $R'_{ij} \equiv_d R_j^*$ or $R'_{ij} \xrightarrow{m}_d R_j^*$ where $1 \leq m < |\mathcal{I}_j|$.

If \mathcal{I}_j is empty, define $R_j^* = R_j$. Observe that in either case either $R_j = R_j^*$ or $R_j \xrightarrow{m}_d R_j^*$, where $1 \leq m \leq |\mathcal{I}_j|$.

We perform case analysis on whether (i) $\mathcal{I}_{\text{fwd } x \ y} = \emptyset$ or (ii) not.

Case (i) $\mathcal{I}_{\text{fwd } x \ y} = \emptyset$

Let $i \in \mathcal{I}$.

Then, $i \in \mathcal{I}_j$ for some $1 \leq j \leq n$.

Therefore

$$\begin{aligned}
Q_i &= \text{fwd } x \ y \mid y \mid C[R_1, \dots, R'_{ij}, \dots, R_n] \\
&\xrightarrow{*}_d \text{fwd } x \ y \mid y \mid C[R_1^*, \dots, R_i^*, \dots, R_n^*]
\end{aligned}$$

For each $1 \leq j \leq n$ with $j \neq i$, we have that either $R_i \equiv_d R_i^*$ or $R_i \xrightarrow{m_j}_d R_i^*$ where $1 \leq m_j \leq |\mathcal{I}_j|$. Additionally, either $R'_{ij} \equiv_d R_i^*$ or $R'_{ij} \xrightarrow{m_i}_d R_i^*$ where $1 \leq m_i < |\mathcal{I}_i|$. Therefore, either $Q_i \equiv_d \text{fwd } x \ y \mid y \mid C[R_1^*, \dots, R_i^*, \dots, R_n^*]$ or $Q_i \xrightarrow{m}_d \text{fwd } x \ y \mid y \mid C[R_1^*, \dots, R_i^*, \dots, R_n^*]$

where $1 \leq m$ and

$$\begin{aligned}
m &= \sum_{1 \leq j \leq n} m_j \\
&= \left(\sum_{1 \leq j \leq n, j \neq i} m_j \right) + m_i \\
&\leq \left(\sum_{1 \leq j \leq n, j \neq i} |\mathcal{I}_j| \right) + m_i \\
&< \left(\sum_{1 \leq j \leq n, j \neq i} |\mathcal{I}_j| \right) + |\mathcal{I}_i| \\
&= \sum_{1 \leq j \leq n} |\mathcal{I}_j| \\
&= k \qquad \text{(since } \{\mathcal{I}_j\}_{1 \leq j \leq n} \text{ is a partition of } \{1, \dots, k\})
\end{aligned}$$

Case (ii) $\mathcal{I}_{\text{fwd } x \ y} \neq \emptyset$

Let $i \in \mathcal{I}$. Either $i \in \mathcal{I}_j$ for some $1 \leq j \leq n$ or $i \in \mathcal{I}_{\text{fwd } x \ y}$.

Suppose $i \in \mathcal{I}_j$. Then

$$\begin{aligned}
Q_i &= \text{fwd } x \ y \ |y| \ C[R_1, \dots, R'_{ij}, \dots, R_n] \\
&\xrightarrow{*}_d \text{fwd } x \ y \ |y| \ C[R_1^*, \dots, R_i^*, \dots, R_n^*] \\
&= \{x/y\}(C[R_1^*, \dots, R_i^*, \dots, R_n^*]) \\
&\rightarrow_d (\{x/y\}C)[\{x/y\}R_1^*, \dots, \{x/y\}R_i^*, \dots, \{x/y\}R_n^*]
\end{aligned}$$

Suppose $i \in \mathcal{I}_{\text{fwd } x \ y}$. Then

$$\begin{aligned}
Q_i &= \{x/y\}(C[R_1, \dots, R_n]) \\
&= (\{x/y\}C)[\{x/y\}R_1, \dots, \{x/y\}R_n] \\
&\xrightarrow{*}_d (\{x/y\}C)[\{x/y\}R_1^*, \dots, \{x/y\}R_n^*]
\end{aligned}$$

By an argument similar to case (i), we may conclude that Q_i converges with less than k steps.

Case $C[R_1] \dots [R_m] \ |x| \ \text{fwd } x \ y \ |y| \ D[R_1] \dots [R_n]$.

Similar to previous case. □

LEMMA 7.6 (DIAMOND \rightarrow_d). *Suppose $P \rightarrow_d Q$ and $P \rightarrow_d R$. Either $Q \equiv_d R$ or exists S s.t. $Q \rightarrow_d S$ and $R \rightarrow_d S$.*

PROOF. Apply lemma D.9 to obtain predexes R_1, \dots, R_k and a static k -hole context C such that $P \equiv C[R_1] \dots [R_k]$ and $C \rightarrow$. All the \rightarrow_d reductions from P are obtained by reducing one of the predexes $R_j \rightarrow R'_j$.

The result follows by applying Lemma D.10 to the reductions originating in each R_i . The proof uses a strategy similar to the one used in the proof of Lemma D.10. □

E PROOF NORMALISATION AND CUT-ELIMINATION

In this section we prove normalisation π SS without polymorphism (Theorem 8.4). We start by proving some properties concerning normal processes (definition 8.2), among which is the subformula property (proposition 8.3).

Then, we define the relation \approx which extends structural congruence \equiv and reduction \rightarrow with commuting principles between actions and share constructs and between actions and cuts, as well as a garbage collection conversion (definition E.3).

After, we introduce a measure $\#$ on processes which will play a key role in normalisation (definition E.5). Then, we prove some key lemmas E.8 and E.10, which entail normalisation (theorem 8.4). We conclude with the proof of the conservation result (corollary 8.5).

E.1 Normal Processes

PROPOSITION 8.3 (SUBFORMULA PROPERTY). *If $P \vdash \Delta; \Gamma$ is normal form, then the derivation only contains subformulas (up to duality) of the types in Δ and Γ .*

PROOF. The proof is by induction on the typing derivation $P \vdash \Delta; \Gamma$. We perform case analysis on the root rule.

We analyse the case [Tcut]. The other cases are handled trivially. Observe that [Tcut!] is excluded since P is normal.

Case [Tcut]. Since P is normal, the cut must be an open cell. Therefore,

$$P = \text{cell } x(y.Q) \mid x \mid \text{share } x \{ \text{fwd } x z \parallel R \}$$

and

$$\frac{\frac{\vdots}{Q \vdash y : \bar{A}; \Gamma} \quad \frac{\text{fwd } x z \vdash x : \Box A, z : \Box \bar{A}; \Gamma \quad \frac{\vdots}{R \vdash \Delta', x : \Box A; \Gamma}}{\text{share } x \{ \text{fwd } x z \parallel R \} \vdash \Delta', x : \Box A, z : \Box \bar{A}; \Gamma}}{\text{cell } x(y.Q) \mid x \mid \text{share } x \{ \text{fwd } x z \parallel R \} \vdash \Delta', z : \Box \bar{A}; \Gamma}$$

where $\Delta = \Delta', z : \Box \bar{A}$. By induction on $Q \vdash y : \bar{A}; \Gamma$ and $R \vdash \Delta, x : \Box A; \Gamma$ we conclude that those derivations enjoy the subformula property.

Observe that this entails the subformula property of $P \vdash \Delta; \Gamma$. Notice that the formula occurrences in $y : \bar{A}, x : \Box \bar{A}, x : \Box A$ are subformulas (up to duality) of the occurrence $z : \Box \bar{A}$. \square

Definition E.1 (\Box -free). A type A is \Box -free if it does not have occurrences of the modality \Box . A typing context is \Box -free if its channels are typed by \Box -free types.

LEMMA E.2. *Let $P \vdash \Delta; \Gamma$ a normal process such that Δ is \Box -free. Then, P does not have cuts.*

PROOF. The proof is by induction on the derivation tree $P \vdash \Delta; \Gamma$. We perform case analysis on the root rule.

We argue that case [Tcut] cannot occur. For suppose $P = P_1 \mid x \mid P_2$. Since the cut is open, then either P_1 or P_2 is a sharing of the form $\text{share } x \{ \text{fwd } x y \parallel Q \}$, which implies that $y : \Box A \in \Delta$, contradicting the hypothesis that Δ is \Box -free.

We illustrate with case [T \otimes].

Case [T \otimes]

We have

$$\frac{P_1 \vdash \Delta_1, y : A; \Gamma \quad P_2 \vdash \Delta_2, x : B; \Gamma}{\text{send } x(y.P_1); P_2 \vdash \Delta_1, \Delta_2, x : A \otimes B; \Gamma}$$

where $P = \text{send } x(y.P_1); P_2$ and $\Delta = \Delta_1, \Delta_2, x : A \otimes B$.

Since $\Delta_1, \Delta_2, x : A \otimes B$ is \Box -free, then both $\Delta_1, y : A$ and $\Delta_2, x : B$ are \Box -free.

$$\begin{aligned}
& \text{share } x \{ \text{wait } y; P \parallel Q \} \approx \text{wait } y; \text{share } x \{ P \parallel Q \} \text{ [share-}\perp\text{]} \\
& \text{share } x \{ P \parallel \text{send } y(z.Q_1); Q_2 \} \approx \text{send } y(z.(\text{share } x \{ P \parallel Q_1 \})); Q_2, x \notin \text{fn}(Q_2) \text{ [share-}\otimes_1\text{]} \\
& \text{share } x \{ P \parallel \text{send } y(z.Q_1); Q_2 \} \approx \text{send } y(z.Q_1); \text{share } x \{ P \parallel Q_2 \}, x \notin \text{fn}(Q_1) \text{ [share-}\otimes_2\text{]} \\
& \text{share } x \{ P \parallel \text{recv } y(z); Q \} \approx \text{recv } y(z); \text{share } x \{ P \parallel Q \} \text{ [share-}\wp\text{]} \\
& \text{share } x \{ P \parallel y.\text{inl}; Q \} \approx y.\text{inl}; \text{share } x \{ P \parallel Q \} \text{ [share-}\oplus_l\text{]} \\
& \text{share } x \{ P \parallel y.\text{inr}; Q \} \approx y.\text{inr}; \text{share } x \{ P \parallel Q \} \text{ [share-}\oplus_r\text{]} \\
& \text{share } x \{ P \parallel \text{case } y \{ |\text{inl} : Q_1 | \text{inr} : Q_2 \} \} \approx \text{case } y \{ |\text{inl} : \text{share } x \{ P \parallel Q_1 \} | \text{inr} : \text{share } x \{ P \parallel Q_2 \} \} \text{ [share-}\&\text{]} \\
& \text{share } x \{ P \parallel ?y; Q \} \approx ?y; \text{share } x \{ P \parallel Q \} \text{ [share-?]} \\
& \text{share } x \{ P \parallel \text{call } y(z); Q \} \approx \text{call } y(z); \text{share } x \{ P \parallel Q \} \text{ [share-copy]} \\
& \text{share } x \{ P \parallel \text{free } y; Q \} \approx \text{free } y; \text{share } x \{ P \parallel Q \} \text{ [share-free]} \\
& \text{share } x \{ P \parallel \text{read } y(z); Q \} \approx \text{read } y(z); \text{share } x \{ P \parallel Q \} \text{ [share-read]} \\
& \text{share } x \{ P \parallel \text{wrt } y(z.Q_1); Q_2 \} \approx \text{wrt } y(z.Q_1); \text{share } x \{ P \parallel Q_2 \} \text{ [share-write]}
\end{aligned}$$

Fig. 12. Action-Share Commuting Rules \approx

By induction on $P_1 \vdash \Delta_1, y : A; \Gamma$ and $P_2 \vdash \Delta_2, x : B; \Gamma$ we conclude that P_1 and P_2 does not have cuts. Therefore, $\text{send } x(y.P_1); P_2$ does not have cuts as well. \square

E.2 The relation \approx

Definition E.3. Let \approx be the least relation on proof terms which contains \equiv and \rightarrow , is closed under the rules of figures 12, 13 and 14 and satisfies the discard conversion **[dis0]**,

$$\frac{P \vdash y : \bar{A}; \Gamma \quad \overline{0 \vdash \emptyset; \Gamma, x : A} \text{ [T0]}}{y.P \text{ !}x \mid 0 \vdash \emptyset; \Gamma \text{ [Tcut!]}} \approx \overline{0 \vdash \emptyset; \Gamma} \text{ [T0]}$$

[dis1]

$$\frac{P \vdash y : \bar{A}; \Gamma \quad \overline{\text{close } z \vdash z : 1; \Gamma, x : A} \text{ [T1]}}{y.P \text{ !}x \mid \text{close } z \vdash z : 1; \Gamma \text{ [Tcut!]}} \approx \overline{\text{close } z \vdash z : 1; \Gamma} \text{ [T1]}$$

and **[disFwd]**

$$\frac{P \vdash y : \bar{A}; \Gamma \quad \overline{\text{fwd } z \ w \vdash z : B, w : \bar{B}; \Gamma, x : A} \text{ [Tfwd]}}{y.P \text{ !}x \mid \text{fwd } z \ w \vdash z : B, w : \bar{B}; \Gamma \text{ [Tcut!]}} \approx \overline{\text{fwd } z \ w \vdash z : B, w : \bar{B}; \Gamma} \text{ [Tfwd]}$$

$$\begin{aligned}
& P \mid x \mid \text{wait } y; Q \approx \text{wait } y; (P \mid x \mid Q) \text{ [cut-}\perp\text{]} \\
& P \mid x \mid \text{send } y(z.Q_1); Q_2 \approx \text{send } y(z.(P \mid x \mid Q_1)); Q_2, x \notin \text{fn}(Q_2) \text{ [cut-}\otimes_1\text{]} \\
& P \mid x \mid \text{send } y(z.Q_1); Q_2 \approx \text{send } y(z.Q_1); (P \mid x \mid Q_2), x \notin \text{fn}(Q_1) \text{ [cut-}\otimes_2\text{]} \\
& P \mid x \mid \text{recv } y(z); Q \approx \text{recv } y(z); (P \mid x \mid Q) \text{ [cut-}\wp\text{]} \\
& P \mid x \mid y.\text{inl}; Q \approx y.\text{inl}; (P \mid x \mid Q) \text{ [cut-}\oplus_l\text{]} \\
& P \mid x \mid y.\text{inr}; Q \approx y.\text{inr}; (P \mid x \mid Q) \text{ [cut-}\oplus_r\text{]} \\
& P \mid x \mid \text{case } y \{ \mid \text{inl} : Q_1 \mid \text{inr} : Q_2 \} \approx \text{case } y \{ \mid \text{inl} : (P \mid x \mid Q_1) \mid \text{inr} : (P \mid x \mid Q_2) \} \text{ [cut-}\&\text{]} \\
& P \mid x \mid ?y; Q \approx ?y; (P \mid x \mid Q) \text{ [cut-?]} \\
& P \mid x \mid \text{call } y(z); Q \approx \text{call } y(z); (P \mid x \mid Q) \text{ [cut-copy]} \\
& P \mid x \mid \text{free } y; Q \approx \text{free } y; (P \mid x \mid Q) \text{ [cut-free]} \\
& P \mid x \mid \text{read } y(z); Q \approx \text{read } y(z); (P \mid x \mid Q) \text{ [cut-read]} \\
& P \mid x \mid \text{wrt } y(z.Q_1); Q_2 \approx \text{wrt } y(z.Q_1); (P \mid x \mid Q_2) \text{ [cut-write]}
\end{aligned}$$

Fig. 13. Action-Cut Commuting Rules \approx

In all the rules of figures 12, 13 and 14 we consider the subject of the prefixed action y to be distinct of x .

REMARK 1. In this section all the conversions of \approx are meant to be on typed processes or proofs. To be concise, we list the conversions of figures 12, 13 and 14 with the process syntax. However, each rule corresponds always to a typed conversion. For example, rule [cut- \perp] is the conversion on proofs

$$\frac{P_1 \vdash \Delta_1, x : \bar{A}; \Gamma \quad \frac{P_2 \vdash \Delta_2, x : A; \Gamma}{\text{wait } y; P_1 \vdash \Delta_2, x : A, y : \perp; \Gamma} \approx \frac{P_1 \vdash \Delta_1, x : \bar{A}; \Gamma \quad P_2 \vdash \Delta_2, x : A; \Gamma}{P_1 \mid x \mid P_2 \vdash \Delta_1, \Delta_2; \Gamma}}{P_1 \mid x \mid \text{wait } y; P_2 \vdash \Delta_1, \Delta_2, y : \perp; \Gamma} \quad \frac{P_1 \vdash \Delta_1, x : \bar{A}; \Gamma \quad P_2 \vdash \Delta_2, x : A; \Gamma}{\text{wait } y; (P_1 \mid x \mid P_2) \vdash \Delta_1, \Delta_2, y : \perp; \Gamma}$$

REMARK 2. Observe that there is no commutation rules for share and the linear cut with the prefixed actions $!y(z); Q$ and $\text{cell } y(z.Q)$. In these proof-terms, the domain of linear typing context is the singleton $\{y\}$. Thus, it is not possible to form either a share $\text{share } x \{P \parallel \alpha; Q\}$ or a linear cut $P \mid x \mid \alpha; Q$, with $y \neq x$.

Obviously, there is no commuting rule for $\text{close } y$ because this process has no continuation.

Notice as well that there are two commutation rules for the share construct and the linear cut with the output prefixed action $[\otimes_1]$ and $[\otimes_2]$, with a proviso guiding the distribution.

$$\begin{aligned}
& w.P \mid!x \mid \text{wait } y; Q \approx \text{wait } y; (w.P \mid!x \mid Q) \text{ [cut!-\perp]} \\
& w.P \mid!x \mid \text{send } y(z.Q_1); Q_2 \approx \text{send } y(z.(w.P \mid!x \mid Q_1)); (w.P \mid!x \mid Q_2), x \notin \text{fn}(Q_2) \text{ [cut!-\otimes]} \\
& w.P \mid!x \mid \text{recv } y(z); Q \approx \text{recv } y(z); (w.P \mid!x \mid Q) \text{ [cut!-\wp]} \\
& w.P \mid!x \mid y.\text{inl}; Q \approx y.\text{inl}; (w.P \mid!x \mid Q) \text{ [cut!-\oplus_l]} \\
& w.P \mid!x \mid y.\text{inr}; Q \approx y.\text{inr}; (w.P \mid!x \mid Q) \text{ [cut!-\oplus_r]} \\
& w.P \mid!x \mid \text{case } y \{ \mid\text{inl} : Q_1 \mid \text{inr} : Q_2 \} \approx \text{case } y \{ \mid\text{inl} : (w.P \mid!x \mid Q_1) \mid \text{inr} : (w.P \mid!x \mid Q_2) \} \text{ [cut!-\&]} \\
& w.P \mid!x \mid ?y; Q \approx ?y; (w.P \mid!x \mid Q) \text{ [cut!-\?]} \\
& w.P \mid!x \mid !y(z); Q \approx !y(z); (w.P \mid!x \mid Q) \text{ [cut!-\!]} \\
& w.P \mid!x \mid \text{call } y(z); Q \approx \text{call } y(z); (w.P \mid!x \mid Q) \text{ [cut!-\text{copy}]} \\
& w.P \mid!x \mid \text{cell } y(z.Q) \approx \text{cell } y(z.(w.P \mid!x \mid Q)) \text{ [cut!-\text{cell}]} \\
& w.P \mid!x \mid \text{free } y; Q \approx \text{free } y; (w.P \mid!x \mid Q) \text{ [cut!-\text{free}]} \\
& w.P \mid!x \mid \text{read } y(z); Q \approx \text{read } y(z); (w.P \mid!x \mid Q) \text{ [cut!-\text{read}]} \\
& w.P \mid!x \mid \text{wrt } y(z.Q_1); Q_2 \approx \text{wrt } y(z.(w.P \mid!x \mid Q_1)); (w.P \mid!x \mid Q_2) \text{ [cut!-\text{write}]}
\end{aligned}$$

Fig. 14. Action-Cut! Commuting Rules \approx

The discard conversions [dis0], [dis1] and [disFwd], together with the distributions laws for the unrestricted cut allow us to derive the general rule stated in the following lemma.

LEMMA E.4. *For all proof terms $P \vdash y : \bar{A}; \Gamma$ and $Q \vdash \Delta; \Gamma, x : A$ s.t. $x \notin \text{fn}(Q)$ we have*

$$y.P \mid!x \mid Q \approx Q$$

PROOF. The proof is by induction on the height of the derivation tree $Q \vdash \Delta; \Gamma$. We perform case analysis on the root rule. We illustrate the proof with the following cases

Case [T0]

By inversion

$$\overline{\mathbf{0} \vdash \emptyset; \Gamma, x : A}$$

where $\Delta = \emptyset$ and $Q = \mathbf{0}$.

From [dis0] we obtain $y.P \mid!x \mid \mathbf{0} \approx \mathbf{0}$.

Case [T1]

Handled similarly to [T0]. Apply [dis1].

Case [Tfwd]

Handled similarly to [T0]. Apply [disFwd].

Case [T⊥]

By inversion

$$\frac{Q' \vdash \Delta'; \Gamma, x : A}{\text{wait } z; Q' \vdash \Delta', z : \perp; \Gamma, x : A}$$

where $Q = \text{wait } z; Q'$ and $\Delta = \Delta', z : \perp$.

Then

$$\begin{aligned} y.P \mid!x \text{ wait } z; Q' &\approx \text{wait } z; (y.P \mid!x \mid Q') && \text{([cut!-\perp])} \\ &\approx \text{wait } z; Q' && \text{(induction on } Q' \vdash \Delta'; \Gamma, x : A) \end{aligned}$$

Case [Tpar]

By inversion

$$\frac{Q_1 \vdash \Delta_1; \Gamma, x : A \quad Q_2 \vdash \Delta_2; \Gamma, x : A}{Q_1 \parallel Q_2 \vdash \Delta_1, \Delta_2; \Gamma, x : A}$$

where $Q = Q_1 \parallel Q_2$ and $\Delta = \Delta_1, \Delta_2$.

Then

$$\begin{aligned} y.P \mid!x \mid (Q_1 \parallel Q_2) &\approx (y.P \mid!x \mid Q_1) \parallel (y.P \mid!x \mid Q_2) && \text{([C!M])} \\ &\approx Q_1 \parallel Q_2 && \text{(induction on } Q_1 \vdash \Delta_1; \Gamma, x : A \text{ and } Q_2 \vdash \Delta_2; \Gamma, x : A) \end{aligned}$$

Case [Tcopy]Since $x \notin \text{fn}(Q)$, we conclude that the subject of the introduced action is other than x .

By inversion

$$\frac{Q' \vdash \Delta, w : B; \Gamma', z : B, x : A}{\text{call } z(w); Q' \vdash \Delta; \Gamma', z : B, x : A}$$

where $Q = \text{call } z(w); Q'$ and $\Gamma = \Gamma', z : B$.

Then

$$\begin{aligned} y.P \mid!x \mid \text{call } z(w); Q' &\approx \text{call } z(w); (y.P \mid!x \mid Q') && \text{([cut!-copy])} \\ &\approx \text{call } z(w); Q' && \text{(induction)} \end{aligned}$$

□

E.3 Proof Normalisation*Definition E.5 (The measure #).* We define $\# : \text{Proc} \rightarrow \mathbb{N}$ inductively by

$\#(0) = 1$	$\#(\text{fwd } x \ y) = 2$	$\#(P \parallel Q) = \#P \times \#Q$
$\#(P \mid!x \mid Q) = \#P \times \#Q$	$\#(y.P \mid!x \mid Q) = \#P \times \#Q$	$\#(\text{share } x \ \{P \parallel Q\}) = \#P \times \#Q$
$\#(P + Q) = \#P + \#Q$	$\#(\text{close } x) = 2$	$\#(\text{wait } x; P) = 1 + \#P$
$\#(\text{send } x(y.P); Q) = 1 + \#P \times \#Q$	$\#(\text{recv } x(y); P) = 1 + \#P$	$\#(x.\text{inl}; P) = 1 + \#P$
$\#(x.\text{inr}; P) = 1 + \#P$	$\#(\text{case } x \ \{\mid\text{inl} : P \mid \text{inr} : Q\}) = 1 + \#P + \#Q$	$\#(!x(y); P) = 1 + \#P$
$\#(?x; P) = 1 + \#P$	$\#(\text{call } x(y); P) = 1 + \#P$	
$\#(\text{read } x(y); P) = 1 + \#P$	$\#(\text{wrt } x(y.P); Q) = 1 + \#P \times \#Q$	$\#(\text{free } x; P) = 1 + \#P$

LEMMA E.6. For all processes P , $\#P > 0$.

LEMMA E.7. *Let $P \vdash \Delta; \Gamma$ be s.t. $P \neq \mathbf{0}$. Then, $\#P > 1$.*

PROOF. The proof is by induction on the typing derivation $P \vdash \Delta; \Gamma$. We perform case analysis on the root rule.

Case [Tzero]

Holds vacuously, because $P = \mathbf{0}$.

Case [Tfwd]

By inversion, $P = \text{fwd } x \ y$. By definition, $\#(\text{fwd } x \ y) = 2 > 1$.

Case [T1]

By inversion, $P = \text{close } x$. By definition, $\#(\text{close } x) = 2 > 1$.

Case [T⊥]

By inversion, $P = \text{wait } x; P'$. Then

$$\begin{aligned} \#(\text{wait } x; P') &= 1 + \#(P') && \text{(by definition)} \\ &> 1 + 0 && \text{(lemma E.6)} \\ &= 1 \end{aligned}$$

Cases [T⊗], [T⊗], [T&], [T⊕], [T⊕_r], [T!], [T?], [Tcopy], [Tfree], [Tread] and [Twrite] are handled similarly to case [T⊥].

Case [Tpar]

By inversion

$$\frac{P_1 \vdash \Delta_1; \Gamma \quad P_2 \vdash \Delta_2; \Gamma}{P_1 \parallel P_2 \vdash \Delta_1, \Delta_2; \Gamma}$$

where $\Delta = \Delta_1, \Delta_2$ and $P = P_1 \parallel P_2$.

Since $P \neq \mathbf{0}$, then either $P_1 \neq \mathbf{0}$ or $P_2 \neq \mathbf{0}$. Assume w.l.o.g. that $P_1 \neq \mathbf{0}$.

Then

$$\begin{aligned} \#(P_1 \parallel P_2) &= \#(P_1) \times \#(P_2) && \text{(by definition)} \\ &\geq \#(P_1) \times 1 && \text{(lemma E.6)} \\ &= \#(P_1) \\ &> 1 && \text{(by induction on } P_1 \vdash \Delta_1; \Gamma) \end{aligned}$$

Case [Tcut]

By inversion

$$\frac{P_1 \vdash \Delta_1, x : \bar{A}; \Gamma \quad P_2 \vdash \Delta_2, x : A; \Gamma}{P_1 \mid x \ P_2 \vdash \Delta_1, \Delta_2; \Gamma}$$

where $P = P_1 \mid x \ P_2$ and $\Delta = \Delta_1, \Delta_2$.

Observe that P_1 and P_2 both have a nonempty linear typing context. Hence, both $P_1 \neq \mathbf{0}$ and $P_2 \neq \mathbf{0}$.

However, we just need to assume $P_1 \neq \mathbf{0}$ and then proceed as in case [Tpar].

Case [Tcut!]

By inversion

$$\frac{P_1 \vdash y : \bar{A}; \Gamma \quad P_2 \vdash \Delta; \Gamma, x : A}{y.P_1 \mid x \ P_2 \vdash \Delta_1, \Delta_2; \Gamma}$$

Since the linear typing context of P_1 is nonempty, then $P_1 \neq \mathbf{0}$.

Hence

$$\begin{aligned}
 \#(y.P_1 \mid !x \mid P_2) &= \#(P_1) \times \#(P_2) \\
 &\geq \#(P_1) \times 1 && \text{(lemma E.6)} \\
 &= \#P_1 \\
 &> 1 && \text{(by induction on } P_1 \vdash y : \bar{A}; \Gamma)
 \end{aligned}$$

Case [Tshare]

Handled similarly to [Tcut].

Case [Tsum]

Handled similarly to case [Tpar].

□

Observe that the measure remains invariant under some structural congruence rules of \equiv , namely the linearly distributive rules of cut and share and the distributive rules over sum. Importantly, though, the \equiv share commuting conversions produce a #-smaller processes when read from left to right. The same applies to the commuting conversions \approx (cf. definition E.3). These #-decreasing conversions play a crucial role in the following lemma.

LEMMA E.8. *Let $P \vdash \Delta, x : \Box A; \Gamma$ and $Q \vdash \Delta', x : \Box A; \Gamma$. One of the following hypothesis hold*

- (i) *There is a process R s.t. $\text{share } x \{P \parallel Q\} \approx R$ and $\#(\text{share } x \{P \parallel Q\}) > \#R$.*
- (ii) *There are processes R, S s.t. $\text{share } x \{P \parallel Q\} \approx R + S$ and $\#(\text{share } x \{P \parallel Q\}) > \#R, \#S$.*
- (iii) *There is a process R s.t. $\text{share } x \{P \parallel Q\} \approx \text{share } x \{\text{fwd } x \ y \parallel R\}$.*

PROOF. The proof is by induction on the sum of depths of the derivation trees $P \vdash \Delta, x : \Box A; \Gamma$ and $Q \vdash \Delta', x : \Box A; \Gamma$. We perform case analysis on the root rule of each tree.

Case Exclusions. Since both P and Q have a nonempty linear typing context, rule [T0] is excluded. Observe that rules [T1], [T!] and [Tcell] type a process with a singleton linear typing context $y : B$, where $B = \mathbf{1}$, $B = !C$ or $B = \Box C$. Because of this, they are excluded as well.

Organisation. The remaining cases are organised in the following groups

Group A: Both derivations have as root rule [Tfree], [Tread] or [Twrite]. Furthermore, the subject of the introduced action in both derivations is x .

Group B: One of the root rules is [Tfree], [Tread] or [Twrite], but the subject of the introduced action is $y \neq x$; or one of the root rules is either [T \perp], [T \otimes], [T \wp], [T \oplus_l], [T \oplus_r], [T $\&$], [T $?$], [Tcopy].

Group C: One of the root rules is either [Tpar], [Tcut], [Tcut!] or [Tshare] on a name $y \neq x$.

Group D: One of the root rules is [Tshare] on name x .

Group E: One of the root rules is [Tsum].

Group F: One of the root rules is [Tfwd].

General Strategy. In some groups (A, B and E) we just apply a conversion \approx to obtain either a process or a sum of processes which have a lower #. The conversions of group A are the share commuting rules of \equiv [free-free], [free-act] or [interleaving]. The conversions of group B are the action-share commuting rules of figure 12. As for group E, we simply distribute the sharing over the sum.

The arithmetic works in groups A and B because all the prefixed actions value one plus something. This unit, when inside the sharing, is multiplying by something greater than one (both arguments of the sharing are necessarily distinct of $\mathbf{0}$). When pushed outside, this weight vanishes.

Cases of group C are handled by applying one of the share distribution laws and induction. We handle some representative cases of each group.

Group A Case [Tfree] for both P and Q

Then

$$\frac{P' \vdash \Delta; \Gamma}{\text{free } x; P' \vdash \Delta, x : \Box A; \Gamma} \text{ [Tfree]} \quad \frac{Q' \vdash \Delta'; \Gamma}{\text{free } x; Q' \vdash \Delta', x : \Box A; \Gamma} \text{ [Tfree]}$$

where $P = \text{free } x; P'$ and $Q = \text{free } x; Q'$.

We have

$$\begin{aligned} & \text{share } x \{ \text{free } x; P' \parallel \text{free } x; Q' \} \\ & \equiv \text{free } x; (P' \parallel Q') \end{aligned} \quad (\equiv [\text{Sh1}])$$

Observe that

$$\begin{aligned} \#(\text{share } x \{ \text{free } x; P' \parallel \text{free } x; Q' \}) &= \#(\text{free } x; P') \times \#(\text{free } x; Q') \\ &= (1 + \#P') \times (1 + \#Q') \\ &= 1 + \#Q' + \#P' + \#P' \times \#Q' \\ &> 1 + \#P' \times \#Q' \quad (\#P', \#Q' > 0) \\ &= \#(\text{free } x; (P' \parallel Q')) \end{aligned}$$

Case [Tfree] for P and either [Tread] or [Twrite] for Q

Suppose w.l.o.g. [Tread] for Q .

Then

$$\frac{P' \vdash \Delta; \Gamma}{\text{free } x; P' \vdash \Delta, x : \Box A; \Gamma} \text{ [Tfree]} \quad \frac{Q' \vdash \Delta', y : ?A, x : \Box A; \Gamma}{\text{read } x(y); Q' \vdash \Delta', x : \Box A; \Gamma} \text{ [Tread]}$$

where $P = \text{free } x; P'$ and $Q = \text{read } x(y); Q'$.

We have

$$\text{share } x \{ \text{free } x; P' \parallel \text{read } x(y); Q' \} \equiv \text{read } x(y); \text{share } x \{ \text{free } x; P' \parallel Q' \}$$

Observe that

$$\begin{aligned} \#(\text{share } x \{ \text{free } x; P' \parallel \text{read } x(y); Q' \}) &= \#P \times \#(\text{read } x(y); Q) \\ &= \#P \times (1 + \#Q') \\ &= \#P + \#P \times \#Q' \\ &> 1 + \#P \times \#Q' \quad (\#P > 1) \\ &= \#(\text{read } x(y); \text{share } x \{ \text{free } x; P' \parallel Q' \}) \end{aligned}$$

Case [Tread] or [Twrite] for both P and Q

Suppose w.l.o.g. that we have [Tread] for both P and Q .

We have

$$\frac{P' \vdash \Delta, y : ?A, x : \Box A; \Gamma}{\text{read } x(y); P' \vdash \Delta, x : \Box A; \Gamma} \text{ [Tread]} \quad \frac{Q' \vdash \Delta', z : ?A, x : \Box A; \Gamma}{\text{read } x(z); Q' \vdash \Delta', x : \Box A; \Gamma} \text{ [Tread]}$$

where $P = \text{read } x(y); P'$ and $Q = \text{read } x(z); Q'$.

Therefore

$$\begin{aligned} & \text{share } x \{ \text{read } x(y); P' \parallel \text{read } x(z); Q' \} \\ & \equiv \text{read } x(y); \text{share } x \{ P' \parallel Q \} + \text{read } x(z); \text{share } x \{ P \parallel Q' \} \end{aligned} \quad (\equiv [\text{Sh3}])$$

Observe that

$$\begin{aligned} \#(\text{share } x \{ \text{read } x(y); P' \parallel \text{read } x(z); Q' \}) &= \#(\text{read } x(y); P') \times \#(\text{read } x(z); Q') \\ &= (1 + \#P') \times \#Q \\ &= \#Q + \#P' \times \#Q \\ &> 1 + \#P' \times \#Q \quad (\#Q > 1) \\ &= \#(\text{read } x(y); \text{share } x \{ P' \parallel Q \}) \end{aligned}$$

Similarly, one can derive

$$\#(\text{share } x \{ \text{read } x(y); P' \parallel \text{read } x(z); Q' \}) > \#(\text{read } x(z); \text{share } x \{ P \parallel Q' \})$$

Group B

Case [T⊥]

We have

$$\frac{P' \vdash \Delta'', x : \Box A; \Gamma}{\text{wait } y; P' \vdash \Delta'', x : \Box A, y : \perp; \Gamma}$$

where $P = \text{wait } y; P'$ and $\Delta = \Delta'', y : \perp$.

Therefore

$$\text{share } x \{ \text{wait } y; P' \parallel Q \} \approx \text{wait } y; \text{share } x \{ P' \parallel Q \} \quad (\approx [\text{share-}\perp])$$

and

$$\begin{aligned} \#(\text{share } x \{ \text{wait } y; P' \parallel Q \}) &= (1 + \#P') \times \#Q \\ &= \#Q + \#P' \times \#Q \\ &> 1 + \#P' \times \#Q \quad (\#Q > 1) \\ &= \#(\text{wait } y; (\text{share } x \{ P' \parallel Q \})) \end{aligned}$$

Case [T⊗]

We have

$$\frac{P_1 \vdash \Delta_1, x : \Box A, y : B; \Gamma \quad P_2 \vdash \Delta_2, z : C; \Gamma}{\text{send } z(y.P_1); P_2 \vdash \Delta_1, \Delta_2, x : \Box A, z : B \otimes C; \Gamma}$$

where $P = \text{send } z(y.P_1); P_2$ and $\Delta = \Delta_1, \Delta_2, z : B \otimes C$. We assume w.l.o.g. that x lies on the linear typing context of P_1 .

Therefore

$$\text{share } x \{ \text{send } z(y.P_1); P_2 \parallel Q \} \approx \text{send } z(y.(\text{share } x \{ P_1 \parallel Q \})); P_2 \quad (\approx [\text{share-}\otimes_1])$$

and

$$\begin{aligned}
\#(\text{share } x \{ \text{send } z(y.P_1); P_2 \parallel Q \}) &= (1 + \#P_1 \times \#P_2) \times \#Q \\
&= \#Q + \#P_1 \times \#P_2 \times \#Q \\
&> 1 + \#P_1 \times \#P_2 \times \#Q && (\#Q > 1) \\
&= \#(\text{send } z(y.(\text{share } x \{ P_1 \parallel Q \})); P_2)
\end{aligned}$$

Case [T&]

We have

$$\frac{P_1 \vdash \Delta'', x : \Box A, y : B; \Gamma \quad P_2 \vdash \Delta'', x : \Box A, y : C; \Gamma}{\text{case } y \{ | \text{inl} : P_1 \mid \text{inr} : P_2 \} \vdash \Delta'', x : \Box A, y : B \& C; \Gamma}$$

where $P = \text{case } y \{ | \text{inl} : P_1 \mid \text{inr} : P_2 \}$ and $\Delta = \Delta'', y : B \& C$.

Therefore

$$\text{share } x \{ \text{case } y \{ | \text{inl} : P_1 \mid \text{inr} : P_2 \} \parallel Q \} \approx \text{case } y \{ | \text{inl} : \text{share } x \{ P_1 \parallel Q \} \mid \text{inr} : \text{share } x \{ P_2 \parallel Q \} \} \quad (\approx [\text{share-}\&])$$

and

$$\begin{aligned}
\#(\text{share } x \{ \text{case } y \{ | \text{inl} : P_1 \mid \text{inr} : P_2 \} \parallel Q \}) &= (1 + \#P_1 + \#P_2) \times \#Q \\
&= \#Q + \#P_1 \times \#Q + \#P_2 \times \#Q \\
&> 1 + \#P_1 \times \#Q + \#P_2 \times \#Q && (\#Q > 1) \\
&= \#(\text{case } y \{ | \text{inl} : \text{share } x \{ P_1 \parallel Q \} \mid \text{inr} : \text{share } x \{ P_2 \parallel Q \} \})
\end{aligned}$$

Group C Case [Tpar]

We have

$$\frac{P_1 \vdash \Delta_1, x : \Box A; \Gamma \quad P_2 \vdash \Delta_2; \Gamma}{P_1 \parallel P_2 \vdash \Delta_1, \Delta_2, x : \Box A; \Gamma}$$

where $P = P_1 \parallel P_2$ and $\Delta = \Delta_1, \Delta_2$.

Therefore

$$\text{share } x \{ P_1 \parallel P_2 \parallel Q \} \equiv \text{share } x \{ P_1 \parallel Q \} \parallel P_2 \quad (\equiv [\text{share-par}], x \notin \text{fn}(P_2))$$

By induction on P_1, Q we conclude that one of the following cases hold

Case exists R s.t. $\text{share } x \{ P_1 \parallel Q \} \approx R$ and $\#(\text{share } x \{ P_1 \parallel Q \}) > \#R$

Then

$$\text{share } x \{ P_1 \parallel P_2 \parallel Q \} \approx R \parallel P_2$$

and

$$\begin{aligned}
\#(\text{share } x \{ P_1 \parallel P_2 \parallel Q \}) &= \#(P_1 \parallel P_2) \times \#Q \\
&= \#P_1 \times \#P_2 \times \#Q \\
&= \#P_1 \times \#Q \times \#P_2 \\
&= \#(\text{share } x \{ P_1 \parallel Q \}) \times \#P_2 \\
&> \#R \times \#P_2 && (\text{i.h.}) \\
&= \#(R \parallel P_2)
\end{aligned}$$

Case exists R, S s.t. $\text{share } x \{P_1 \parallel Q\} \approx R + S$ and $\#(\text{share } x \{P_1 \parallel Q\}) > \#R, \#S$
Then

$$\begin{aligned} \text{share } x \{P_1 \parallel P_2 \parallel Q\} &\approx (R + S) \parallel P_2 \\ &\approx (R \parallel P_2) + (S \parallel P_2) \end{aligned}$$

See (*) from the previous case to justify the inequations

$$\#(\text{share } x \{P_1 \parallel P_2 \parallel Q\}) > \#(R \parallel P_2), \#(S \parallel P_2)$$

Case $\text{share } x \{P_1 \parallel Q\} \approx \text{share } x \{\text{fwd } x y \parallel R\}$, for some process R
Then

$$\begin{aligned} \text{share } x \{P_1 \parallel P_2 \parallel Q\} &\equiv \text{share } x \{P_1 \parallel Q\} \parallel P_2 && (\equiv [\text{share-par}], x \notin \text{fn}(P_2)) \\ &\approx \text{share } x \{\text{fwd } x y \parallel R\} \parallel P_2 \\ &\equiv \text{share } x \{\text{fwd } x y \parallel R \parallel P_2\} && (\equiv [\text{share-par}], x \notin \text{fn}(P_2)) \end{aligned}$$

Group D [Tshare] on x
We have

$$\frac{P_1 \vdash \Delta_1, x : \Box A; \Gamma \quad P_2 \vdash \Delta_2, x : \Box A; \Gamma}{\text{share } x \{P_1 \parallel P_2\} \vdash \Delta_1, \Delta_2, x : \Box A; \Gamma}$$

where $P = \text{share } x \{P_1 \parallel P_2\}$ and $\Delta = \Delta_1, \Delta_2$

By induction on P_1, P_2 we conclude that one of the following cases hold

Case Exists R s.t. $\text{share } x \{P_1 \parallel P_2\} \approx R$ and $\#(\text{share } x \{P_1 \parallel P_2\}) > \#R$.
Then

$$\text{share } x \{\text{share } x \{P_1 \parallel P_2\} \parallel Q\} \approx \text{share } x \{R \parallel Q\}$$

and (*)

$$\begin{aligned} \#(\text{share } x \{\text{share } x \{P_1 \parallel P_2\} \parallel Q\}) &= \#(\text{share } x \{P_1 \parallel P_2\}) \times \#Q \\ &= \#P_1 \times \#P_2 \times \#Q \\ &= \#(\text{share } x \{P_1 \parallel P_2\}) \times \#Q \\ &> \#R \times \#P_Q && (\text{i.h.}) \\ &= \#(\text{share } x \{R \parallel Q\}) \end{aligned}$$

Case Exists R, S s.t. $\text{share } x \{P_1 \parallel P_2\} \approx R + S$ and $\#(\text{share } x \{P_1 \parallel P_2\}) > \#R, \#S$.
Then

$$\begin{aligned} \text{share } x \{\text{share } x \{P_1 \parallel P_2\} \parallel Q\} &\approx \text{share } x \{(R + S) \parallel Q\} \\ &\approx (\text{share } x \{R \parallel Q\}) + (\text{share } x \{S \parallel Q\}) \end{aligned}$$

See (*) from the previous case to justify the inequations

$$\#(\text{share } x \{\text{share } x \{P_1 \parallel P_2\} \parallel Q\}) > \#(\text{share } x \{R \parallel Q\}), \#(\text{share } x \{S \parallel Q\})$$

Case $\text{share } x \{P_1 \parallel P_2\} \approx \text{share } x \{\text{fwd } x y \parallel R\}$ for some process R .
Then

$$\begin{aligned} \text{share } x \{P \parallel Q\} &\approx \text{share } x \{\text{share } x \{\text{fwd } x y \parallel R\} \parallel Q\} \\ &\approx \text{share } x \{\text{fwd } x y \parallel \text{share } x \{R \parallel Q\}\} && (\equiv \text{associativity } [\text{share}]) \end{aligned}$$

Group E [Tsum]

We have

$$\frac{P_1 \vdash \Delta, x : \Box A; \Gamma \quad P_2 \vdash \Delta, x : \Box A; \Gamma}{P_1 + P_2 \vdash \Delta, x : \Box A; \Gamma}$$

where $P = P_1 + P_2$.

Therefore

$$\text{share } x \{P_1 + P_2 \parallel Q\} \equiv \text{share } x \{P_1 \parallel Q\} + \text{share } x \{P_2 \parallel Q\} \quad (\equiv [\text{ShSm}])$$

Observe that

$$\begin{aligned} \#(\text{share } x \{P_1 + P_2 \parallel Q\}) &= \#(P_1 + P_2) \times \#Q \\ &= (\#P_1 + \#P_2) \times \#Q \\ &= \#P_1 \times \#Q + \#P_2 \times \#Q \\ &> \#P_1 \times \#Q && (\#P_2, \#Q > 0) \\ &= \#(\text{share } x \{P_1 \parallel Q\}) \end{aligned}$$

Similarly, one can derive

$$\#(\text{share } x \{P_1 + P_2 \parallel Q\}) > \#(\text{share } x \{P_2 \parallel Q\})$$

Group F [Tfwd]

We have

$$\frac{}{\text{fwd } x y \vdash x : \Box A, y : \Box \bar{A}}$$

where $P = \text{fwd } x y$.

Then

$$\text{share } x \{P \parallel Q\} \approx \text{share } x \{\text{fwd } x y \parallel Q\}$$

□

Definition E.9. We define $<$ to be least binary relation on types s.t. the following holds

- If $d(A) < d(B)$, then $A < B$.
- $\Box A < \Box \bar{A}$.

where $d(A)$ is the depth (the maximum length of a branch in the construction tree) of the type A .

LEMMA E.10 (CUT ADMISSIBILITY). *The following two hypothesis hold*

$H_1(A, P, Q)$ Let $P \vdash \Delta', x : \bar{A}; \Gamma$, $Q \vdash \Delta, x : A; \Gamma$ be normal processes. There exists a normal process R s.t. $P \mid x : A \mid Q \approx R$.

$H_2(A, P, Q)$ Let $P \vdash y : \bar{A}; \Gamma$ and $Q \vdash \Delta; \Gamma, x : A$ be normal processes. There exists a normal process R s.t. $y.P \mid !x : A \mid Q \approx R$.

PROOF. The proof is by mutual induction. More precisely, by lexicographical induction: first on A (ordered by $<$), then on the hypothesis being proved (we consider $H_1 < H_2$), and then on $\#(P \mid x \mid Q)$.

To justify the inductive call we use the following notation

$$(A, H_i, P, Q) \rightarrow (B, H_j, R, S)$$

which means that we are proving hypothesis $H_i(A, P, Q)$ and that somewhere during the proof we appeal to hypothesis $H_j(B, R, S)$. The inductive call has to respect the lexicographical order.

Proof of H_1

We perform case analysis on the root rules of the derivation trees $P \vdash \Delta', x : \bar{A}; \Gamma$ and $Q \vdash \Delta, x : A; \Gamma$. The cases are organised in the following groups.

Group A: Both derivations have as root rule either [T1], [T \perp], [T \otimes], [T \wp], [T \oplus_l], [T \oplus_r], [T&], [T!], [T?], [Tcell], [Tfree], [Tread] or [Twrite]. Furthermore, the subject of the introduced actions in both derivations is x .

Group B: One of the root rules is either [T \perp], [T \otimes], [T \wp], [T \oplus_l], [T \oplus_r], [T&], [T?], [Tcopy], [Tcell], [Tfree], [Tread] or [Twrite]. Furthermore, the subject of the introduced action is $y \neq x$.

Group C: One of the root rules is either [Tpar] or [Tsum]; or [Tshare] on a channel $y \neq x$.

Group D: The root rules are [Tcell] and [Tshare] on the same channel x .

Group E: One of the root rules is [Tcut].

Observe that the following cases are excluded

- One of the root rules is [T0].
- One of the root rules is [Tcopy] and the subject of the introduced action is x .
- One of the root rules is either [T!] or [Tcell] and the subject of the introduced action is $y \neq x$.

They are all excluded because of the same reason: they introduce a linear typing context which does not contain the name x .

Group A Since the name x is typed by \bar{A} in P and by A in Q we conclude that the introduced actions must be dual. Therefore, we are able to apply one of the principal cut reductions. We perform case analysis on A . We illustrate with some representative cases.

Case $A = \perp$.

We have

$$\frac{}{\text{wait } x; \vdash x : \mathbf{1}; \Gamma} \quad \frac{Q_0 \vdash \Delta; \Gamma}{\text{wait } x; Q_0 \vdash \Delta, x : \perp; \Gamma}$$

where $P = \text{close } x$, $\Delta = \emptyset$ and $Q = \text{wait } x; Q_0$.

Then

$$\text{close } x \mid x : \perp \mid \text{wait } x; Q_0 \rightarrow Q_0 \quad (\rightarrow [\mathbf{1}\perp])$$

By hypothesis, Q , and hence Q_0 , is normal.

Case $A = A_1 \wp A_2$.

We have

$$\frac{P_1 \vdash \Delta'_1, y : \bar{A}_1; \Gamma \quad P_2 \vdash \Delta'_2, x : \bar{A}_2; \Gamma}{\text{send } x(y.P_1); P_2 \vdash \Delta'_1, \Delta'_2, x : \bar{A}_1 \otimes \bar{A}_2; \Gamma} \quad \frac{Q' \vdash \Delta, x : A_2, y : A_1; \Gamma}{\text{recv } x(y); Q' \vdash \Delta, x : A_1 \wp A_2}$$

where $P = \text{send } x(y.P_1); P_2$, $\Delta' = \Delta'_1, \Delta'_2$ and $Q = \text{recv } x(z); Q'$.

Then

$$\begin{aligned} & \text{send } x(y.P_1); P_2 \mid x : A_1 \wp A_2 \mid \text{recv } x(z); Q' \\ & \rightarrow P_2 \mid x : A_2 \mid (P_1 \mid y : A_1 \mid \{y/z\}Q') && (\rightarrow [\otimes\wp]) \\ & \approx P_2 \mid x : A_2 \mid R_1 && (\text{induction } (A_1 \wp A_2, H_1, -, -) \rightarrow (A_1, H_1, -, -)) \\ & \approx R && (\text{induction } (A_1 \wp A_2, H_1, -, -) \rightarrow (A_2, H_1, -, -)) \end{aligned}$$

where both R_1 and R are normal.

Case $A = ?B$

We have

$$\frac{P' \vdash y : \bar{B}; \Gamma}{!x(y); P' \vdash x : !\bar{B}; \Gamma} \quad \frac{Q' \vdash \Delta; \Gamma, x : A}{?x; Q' \vdash \Delta, x : ?B; \Gamma}$$

where $P = !x(y); P', \Delta' = \emptyset$ and $Q = ?x; Q'$.

Then

$$\begin{aligned} & !x(y); P' \quad |x : ?B| \quad ?x; Q' \\ & \rightarrow y.P' \quad |!x : B| \quad Q' && (\rightarrow [!?]) \\ & \approx R && (\text{induction } (?B, H_1, -, -) \rightarrow (B, H_2, -, -)) \end{aligned}$$

where R is normal.

Case $A = \Box B$.

We have

$$\frac{P' \vdash y : !\bar{B}; \Gamma}{\text{cell } x(y.P') \vdash x : \Box \bar{B}; \Gamma}$$

where $P = \text{cell } x(y.P')$ and $\Delta' = \emptyset$.

The \Box modality can be introduced by three possible rules: [Tfree], [Tread] or [Twrite].

We handle cases [Tread] and [Twrite]. Case [Tfree] is very similar to case $A = \perp$.

Case [Tread].

We have

$$\frac{Q' \vdash \Delta, z : ?B, x : \Box B; \Gamma}{\text{read } x(z); Q' \vdash \Delta, x : \Box B; \Gamma}$$

where $Q = \text{read } x(z); Q'$.

Then

$$\begin{aligned} & \text{cell } x(y.P') \quad |x : \Box B| \quad \text{read } x(z); Q' \\ & \rightarrow \{z/y\}P' \quad |z : !B| \quad (\text{cell } x(y.P') \quad |x : \Box B| \quad Q') && (\rightarrow [\Box\Box\text{-read}]) \\ & \approx \{z/y\}P' \quad |z : !B| \quad R' && (\text{induction } (\Box B, H_1, P, Q) \rightarrow (\Box B, H_1, P, Q')) \\ & \approx R && (\text{induction } (\Box B, -, -, -) \rightarrow (!B, -, -, -)) \end{aligned}$$

where both R' and R are normal.

Case [Twrite].

We have

$$\frac{Q_1 \vdash z : !\bar{A}; \Gamma \quad Q_2 \vdash \Delta, x : \Box A; \Gamma}{\text{wrt } x(y.Q_1); Q_2 \vdash \Delta, x : \Box A; \Gamma}$$

where $Q = \text{wrt } x(z.Q_1); Q_2$.

Then

$$\begin{aligned} & \text{cell } x(y.P') \quad |x : \Box B| \quad \text{wrt } x(z.Q_1); Q_2 \\ & \rightarrow \text{cell } x(z.Q_1) \quad |x : \Box B| \quad Q_2 && (\rightarrow [\Box\Box\text{-write}]) \\ & \approx R && (\text{induction } (\Box B, H_1, \text{cell } x(y.P'), \text{wrt } x(z.Q_1); Q_2) \rightarrow (\Box B, H_1, \text{cell } x(z.Q_1), Q_2)) \end{aligned}$$

where R is normal.

Group B The cases of this group are handled by applying one of the action-cut commuting conversions of figure 13, followed by an inductive call. We illustrate for case [T⊥].

Case [T⊥].

We have

$$\frac{Q' \vdash \Delta_0, x : A; \Gamma}{\text{wait } y; Q' \vdash \Delta_0, x : A, y : \perp; \Gamma}$$

where $Q = \text{wait } y; Q'$ and $\Delta = \Delta_0, y : \perp$.

Then

$$\begin{aligned} P \mid x \mid \text{wait } y; Q' &\approx \text{wait } y; (P \mid x \mid Q') && \text{(figure 13, } [\perp]) \\ &\approx \text{wait } y; (R) && \text{(induction } (A, H_1, P, Q) \rightarrow (A, H_1, P', Q)) \end{aligned}$$

where R , and hence $\text{wait } y; R$ is normal.

Group C Cases of this group are handled by applying one of the distributive rules of \equiv .

Case [Tpar].

We have

$$\frac{P_1 \vdash \Delta'_1, x : \bar{A}; \Gamma \quad P_2 \vdash \Delta'_2; \Gamma}{P_1 \parallel P_2 \vdash \Delta'_1, \Delta'_2, x : \bar{A}; \Gamma}$$

where $P = P_1 \parallel P_2$ and $\Delta' = \Delta'_1, \Delta'_2$.

Then

$$\begin{aligned} (P_1 \parallel P_2) \mid x : A \mid Q &\equiv (P_1 \mid x : A \mid Q) \parallel P_2 && (\equiv [\text{CM}]) \\ &\approx R \parallel P_2 && \text{(induction } (A, H_1, P, Q) \rightarrow (A, H_1, P_1, Q)) \end{aligned}$$

where R and P_2 , and hence $R \parallel P_2$, are both normal.

Case [Tsum]. We have

$$\frac{P_1 \vdash \Delta', x : \bar{A}; \Gamma \quad P_2 \vdash \Delta', x : \bar{A}; \Gamma}{P_1 + P_2 \vdash \Delta', x : \bar{A}; \Gamma}$$

where $P = P_1 + P_2$.

Then

$$\begin{aligned} (P_1 + P_2) \mid x : A \mid Q &\equiv (P_1 \mid x : A \mid Q) + (P_2 \mid x : A \mid Q) && (\equiv [\text{CSm}]) \\ &\approx R_1 + (P_2 \mid x : A \mid Q) && \text{(induction } (A, H_1, P, Q) \rightarrow (A, H_1, P_1, Q)) \\ &\approx R_1 + R_2 && \text{(induction } (A, H_1, P, Q) \rightarrow (A, H_1, P_2, Q)) \end{aligned}$$

where both R_1, R_2 , and hence $R_1 + R_2$, are normal.

Case [Tshare] on a channel $y \neq x$. Distribute the cut and apply the i.h. (similar to case [Tpar]).

Group D [Tcell] and [Tshare] on a channel x .

We have

$$\frac{P' \vdash y : !\bar{B}; \Gamma \quad Q_1 \vdash \Delta'_1, x : \boxplus B; \Gamma \quad Q_2 \vdash \Delta'_2, x : \boxplus B; \Gamma}{\text{cell } x(y.P') \vdash x : \boxplus \bar{B}; \Gamma \quad \text{share } x \{Q_1 \parallel Q_2\} \vdash \Delta'_1, \Delta'_2, x : \boxplus B; \Gamma}$$

where $P = \text{cell } x(y.P')$, $\Delta = \emptyset$, $Q = \text{share } x \{Q_1 \parallel Q_2\}$, $\Delta' = \Delta'_1, \Delta'_2$ and $A = \boxplus B$.

By applying lemma E.8 to hypothesis $Q_1 \vdash \Delta'_1, x : \boxplus B; \Gamma$ and $Q_2 \vdash \Delta'_2, x : \boxplus B; \Gamma$ we conclude that one of the following cases hold

Case Exists Q' s.t. $Q \approx Q'$ and $\#Q > \#Q'$.

Then

$$\begin{aligned} P \mid x : A \mid Q &\approx P \mid x : A \mid Q' \\ &\approx R \quad (\text{induction } (A, H_1, P, Q) \rightarrow (A, H_1, P, Q')) \end{aligned}$$

where R is normal.

Case Exists R_1, R_2 s.t. $Q \approx R_1 + R_2$ and $\#Q > \#R_1, \#R_2$.

Then

$$\begin{aligned} P \mid x : A \mid Q &\approx P \mid x : A \mid (R_1 + R_2) \\ &\approx (P \mid x : A \mid R_1) + (P \mid x : A \mid R_2) \\ &\approx S_1 + (P \mid x : A \mid R_2) \quad (\text{induction } (A, H_1, P, Q) \rightarrow (A, H_1, P, R_1)) \\ &\approx S_1 + S_2 \quad (\text{induction } (A, H_1, P, Q) \rightarrow (A, H_1, P, R_2)) \end{aligned}$$

where both S_1 and S_2 , and hence $S_1 + S_2$, are normal.

Case Exists Q' s.t. $Q \approx \text{share } x \{ \text{fwd } x z \mid Q' \}$

Then

$$P \mid x : A \mid Q \approx \text{cell } x(y.P') \mid x : A \mid \text{share } x \{ \text{fwd } x z \mid Q' \}$$

Observe that $\text{cell } x(y.P') \mid x : A \mid \text{share } x \{ \text{fwd } x z \mid Q' \}$ is open.

Observe that the transformations of lemma E.8 do not introduce newer cuts and do not interfere with the existing ones. As a consequence, the processes obtained from the lemma are still normal.

Group E [Tcut]

We have

$$P = \text{cell } y(z.P_1) \mid y : B \mid \text{share } y \{ \text{fwd } y w \mid P_2 \}$$

There are two hypothesis to consider, depending on whether (i) $w \neq x$ or (ii) $w = x$.

Case (i) $w \neq x$

Then

$$\begin{aligned} P \mid x : A \mid Q &= (\text{cell } y(z.P_1) \mid y : B \mid \text{share } y \{ \text{fwd } y w \mid P_2 \}) \mid x : A \mid Q \\ &\approx \text{cell } y(z.P_1) \mid y : B \mid \text{share } y \{ \text{fwd } y w \mid P_2 \mid x : A \mid Q \} \\ &\approx \text{cell } y(z.P_1) \mid y : B \mid \text{share } y \{ \text{fwd } y w \mid R \} \quad (\text{induction } (A, H_1, P, Q) \rightarrow (A, H_1, P_2, Q)) \end{aligned}$$

where R is normal.

Case (ii) $w = x$

First observe that because y and x occur in a forwarder, the cut formulas A and B have the same complexity.

Then

$$\begin{aligned} P \mid x : A \mid Q &= (\text{cell } y(z.P_1) \mid y : A \mid \text{share } y \{ \text{fwd } y x \mid P_2 \}) \mid x : A \mid Q \\ &\approx \text{cell } y(z.P_1) \mid y : A \mid \text{share } y \{ \{y/x\}Q \mid P_2 \} \\ &\approx R \quad (\text{induction } (A, H_1, P, Q) \rightarrow (A, H_1, \text{cell } y(z.P_1), \text{share } y \{ \{y/x\}Q \mid P_2 \})) \end{aligned}$$

where R is normal.

The following arithmetic justifies the inductive call

$$\begin{aligned}
\#(P \mid x \mid Q) &= \#P \times \#Q \\
&= \#(\text{cell } y(z.P_1) \mid y : B \mid \text{share } y \{ \text{fwd } y \ x \ \parallel P_2 \}) \times \#Q \\
&= \#\text{cell } y(z.P_1) \times \#\text{fwd } y \ x \times \#P_2 \times \#Q \\
&> \#\text{cell } y(z.P_1) \times \#P_2 \times \#Q && \text{(since } \text{fwd } y \ x > 2) \\
&= \#\text{cell } y(z.P_1) \times \#P_2 \times \#(\{y/x\}Q) \\
&= \#(\text{cell } y(z.P_1) \mid y \mid \text{share } y \{ \{y/x\}Q \ \parallel P_2 \})
\end{aligned}$$

Proof of H_2

The proof is by structural induction on a derivation tree for $Q \vdash \Delta; \Gamma, x : A$. We perform case analysis on the root rule of the tree. The cases to consider are organised in the following groups.

Group A: The root rule is either [T0], [T1] or [Tfwd].

Group B: The root rule is [Tcopy] and the subject of the introduced action is x .

Group C: The root rule is [Tcopy] and the subject of the introduced action is $y \neq x$; or the root rule is either [T \perp], [T \otimes], [T \otimes], [T \otimes], [T \oplus_l], [T \oplus_r], [T $\&$], [T!], [T?], [Tcell], [Tfree], [Tread] or [Twrite].

Group D: The root rule is either [Tpar], [Tshare], [Tsum].

Group E: The root rule is [Tcut].

In all the groups we apply one transformation to the cut (possibly followed by induction). In group A, we apply the one of cut! conversions [dis0], [dis1] or [disFwd] that discharges the server. In B, we apply a principal cut reduction. In C, we apply one of the cut!-action commuting conversions of figure 14. In D and E we apply one of the cut! conversions of \equiv that distributes the server.

Group A

Case We illustrate for case [T0].

We have

$$\overline{0 \vdash \emptyset; \Gamma}$$

Then

$$y.P \mid !x : A \mid 0 \approx 0$$

and 0 is normal.

Group B We have

$$\frac{Q' \vdash \Delta, z : A; \Gamma, x : A}{\text{call } x(z); Q' \vdash \Delta; \Gamma, x : A}$$

where $Q = \text{call } x(z); Q'$.

Then

$$\begin{aligned}
y.P \mid !x : A \mid \text{call } x(z); Q' &\rightarrow \{z/y\}P \mid z : A \mid (y.P \mid !x : A \mid Q') && (\rightarrow [C!]) \\
&\approx \{z/y\}P \mid z : A \mid R' && \text{(induction } (A, H_2, P, Q) \rightarrow (A, H_2, P, Q')) \\
&\approx R && \text{(induction } (A, H_2, -, -) \rightarrow (A, H_1, -, -))
\end{aligned}$$

where both R' and R are normal.

Group C The cases of this group are handled by applying one the aciton-cut! commuting conversions of figure 14. We illustrate for case [T \perp].

Case [T⊥].

We have

$$\frac{Q' \vdash \Delta'; \Gamma, x : A}{\text{wait } y; Q' \vdash \Delta', y : \perp; \Gamma, x : A}$$

where $Q = \text{wait } y; Q'$ and $\Delta = \Delta', y : \perp$.

Then

$$\begin{aligned} y.P \mid x : A \mid \text{wait } y; Q' &\approx \text{wait } y; (y.P \mid x : A \mid Q') && \text{(figure 14 [⊥])} \\ &\approx \text{wait } y; R && \text{(induction } (A, H_2, P, Q) \rightarrow (A, H_2, P, Q')) \end{aligned}$$

where R , and hence $\text{wait } y; R$, is normal.

Group D These cases are handled by applying one of the \equiv distributive rules. We handle case [Tpar]. The other cases are handled similarly.

Case [Tpar].

We have

$$\frac{Q_1 \vdash \Delta_1; \Gamma, x : A \quad Q_2 \vdash \Delta_2; \Gamma, x : A}{Q_1 \parallel Q_2 \vdash \Delta_1, \Delta_2; \Gamma, x : A}$$

where $Q = Q_1 \parallel Q_2$ and $\Delta = \Delta_1, \Delta_2$.

Then

$$\begin{aligned} y.P \mid x : A \mid (Q_1 \parallel Q_2) &\equiv (y.P \mid x : A \mid Q_1) \parallel (y.P \mid x : A \mid Q_2) && (\equiv [\text{C!M}]) \\ &\approx R_1 \parallel (y.P \mid x : A \mid Q_2) && \text{(induction } (A, H_2, P, Q) \rightarrow (A, H_2, P, Q_1)) \\ &\approx R_1 \parallel R_2 && \text{(induction } (A, H_2, P, Q) \rightarrow (A, H_2, P, Q_1)) \end{aligned}$$

where both R_1 and R_2 , and hence $R_1 \parallel R_2$, are normal.

Group E [Tcut]

We have

$$Q = \text{cell } z(w.Q_1) \mid z \mid \text{share } z \{ \text{fwd } z u \parallel Q_2 \}$$

Then

$$\begin{aligned} y.P \mid x : A \mid Q &= y.P \mid x : A \mid (\text{cell } z(w.Q_1) \mid z \mid \text{share } z \{ \text{fwd } z u \parallel Q_2 \}) \\ &\approx \text{cell } z(w.(y.P \mid x : A \mid Q_1)) \mid z \mid \text{share } z \{ \text{fwd } z u \parallel (y.P \mid x : A \mid Q_2) \} \\ &\approx R_1 \mid z \mid \text{share } z \{ \text{fwd } z u \parallel (y.P \mid x : A \mid Q_2) \} && \text{(induction } (A, H_2, P, Q) \rightarrow (A, H_2, P, Q_1)) \\ &\approx R_1 \mid z \mid \text{share } z \{ \text{fwd } z u \parallel R_2 \} && \text{(induction } (A, H_2, P, Q) \rightarrow (A, H_2, P, Q_2)) \end{aligned}$$

where R_1 and R_2 are normal. □

THEOREM 8.4 (NORMALISATION). *Given $P \vdash \Delta; \Gamma$ there is a normal form Q s.t. $P \approx Q$.*

PROOF. By induction on the typing derivation. For cases [Tcut] and [Tcut!] apply lemma E.10. □

COROLLARY 8.5 (CONSERVATION). *Let process $P \vdash \Delta; \Gamma$ and $\Delta; \Gamma$ a sequent in propositional linear logic with par. Then there is a cut-free process Q s.t. $P \approx Q$.*

PROOF. By theorem 8.4, we conclude that exists a normal process Q s.t. $P \approx Q$.

Since Q is normal and Δ is \boxtimes -free, then Q does not have cuts (lemma E.2). □

F TYPED CONVERSIONS FIGURES

$$\begin{array}{c}
\frac{}{\text{fwd } x \ y \vdash x : \bar{A}, y : A; \Gamma} \equiv \frac{}{\text{fwd } y \ x \vdash y : A, x : \bar{A}; \Gamma} \text{ [C-fwd]} \\
\\
\frac{P \vdash \Delta; \Gamma \quad Q \vdash \Delta'; \Gamma}{P \parallel Q \vdash \Delta, \Delta'; \Gamma} \equiv \frac{Q \vdash \Delta'; \Gamma \quad P \vdash \Delta; \Gamma}{Q \parallel P \vdash \Delta', \Delta; \Gamma} \text{ [C-M]} \\
\\
\frac{P \vdash \Delta, x : \bar{A}; \Gamma \quad Q \vdash \Delta', x : A; \Gamma}{P \ |x| \ Q \vdash \Delta, \Delta'; \Gamma} \equiv \frac{Q \vdash \Delta', x : A; \Gamma \quad P \vdash \Delta, x : \bar{A}; \Gamma}{Q \ |x| \ P \vdash \Delta', \Delta; \Gamma} \text{ [C-C]} \\
\\
\frac{P \vdash \Delta, x : \Box A; \Gamma \quad Q \vdash \Delta', x : \Box A; \Gamma}{\text{share } x \ \{P \parallel Q\} \vdash \Delta, \Delta', x : \Box A; \Gamma} \equiv \frac{Q \vdash \Delta', x : \Box A; \Gamma \quad P \vdash \Delta, x : \Box A; \Gamma}{\text{share } x \ \{Q \parallel P\} \vdash \Delta', \Delta, x : \Box A; \Gamma} \text{ [C-Sh]} \\
\\
\frac{P \vdash \Delta; \Gamma \quad Q \vdash \Delta; \Gamma}{P + Q \vdash \Delta; \Gamma} \equiv \frac{Q \vdash \Delta; \Gamma \quad P \vdash \Delta; \Gamma}{Q + P \vdash \Delta; \Gamma} \text{ [C-Sm]} \\
\\
\frac{P \vdash \Delta, x : \bar{A}; \Gamma \quad \frac{Q \vdash \Delta', x : A; \Gamma \quad R \vdash \Delta''; \Gamma}{Q \parallel R \vdash \Delta', \Delta; \Gamma}}{P \ |x| \ (Q \parallel R) \vdash \Delta, \Delta', \Delta''; \Gamma} \\
\equiv \\
\frac{P \vdash \Delta, x : \bar{A}; \Gamma \quad Q \vdash \Delta', x : A; \Gamma}{P \ |x| \ Q \vdash \Delta, \Delta'; \Gamma} \quad R \vdash \Delta''; \Gamma \text{ [C-CM]} \\
\frac{}{(P \ |x| \ Q) \parallel R \vdash \Delta, \Delta', \Delta''; \Gamma} \\
\\
\frac{P \vdash \Delta, x : \bar{A}; \Gamma \quad \frac{Q \vdash \Delta', x : A, y : \bar{B}; \Gamma \quad R \vdash \Delta'', y : B; \Gamma}{Q \ |y| \ R \vdash \Delta', x : A, \Delta; \Gamma}}{P \ |x| \ (Q \ |y| \ R) \vdash \Delta, \Delta', \Delta''; \Gamma} \\
\equiv \\
\frac{P \vdash \Delta, x : \bar{A}; \Gamma \quad Q \vdash \Delta', x : A, y : \bar{B}; \Gamma}{P \ |x| \ Q \vdash \Delta, \Delta', y : \bar{B}; \Gamma} \quad R \vdash \Delta'', y : B; \Gamma \text{ [C-CC]} \\
\frac{}{(P \ |x| \ Q) \ |y| \ R \vdash \Delta, \Delta', \Delta''; \Gamma} \\
\\
\frac{P \vdash \Delta, x : \bar{A}; \Gamma \quad \frac{Q \vdash y : \bar{B}; \Gamma \quad R \vdash \Delta', x : A; \Gamma, z : B}{y.Q \ |!z| \ R \vdash \Delta', x : A; \Gamma}}{P \ |x| \ (y.Q \ |!z| \ R) \vdash \Delta, \Delta'; \Gamma} \\
\equiv \\
\frac{P \vdash \Delta, x : \bar{A}; \Gamma}{P \vdash \Delta, x : \bar{A}; \Gamma, z : B} \text{ [weak]} \quad R \vdash \Delta', x : A; \Gamma, z : B \text{ [C-CC!]} \\
\frac{Q \vdash y : \bar{B}; \Gamma}{y.Q \ |!z| \ (P \ |x| \ R) \vdash \Delta, \Delta'; \Gamma}
\end{array}$$

Fig. 15

$$\begin{array}{c}
\frac{Q \vdash \Delta', x : A, y : \Box B; \Gamma \quad R \vdash \Delta'', y : \Box B; \Gamma}{P \vdash \Delta, x : \bar{A}; \Gamma \quad \text{share } y \{Q \parallel R\} \vdash \Delta', x : A, \Delta'', y : \Box B; \Gamma} \\
\equiv \\
\frac{P \mid x \mid \text{share } y \{Q \parallel R\} \vdash \Delta, \Delta', \Delta'', y : \Box B; \Gamma}{P \vdash \Delta, x : \bar{A}; \Gamma \quad Q \vdash \Delta', x : A, y : \Box B; \Gamma} \\
\equiv \\
\frac{P \mid x \mid Q \vdash \Delta, \Delta', y : \Box B; \Gamma \quad R \vdash \Delta'', y : \Box B; \Gamma}{\text{share } y \{P \mid x \mid Q \parallel R\} \vdash \Delta, \Delta', \Delta'', y : \Box B; \Gamma} \text{ [C-CSH]} \\
\\
\frac{Q \vdash \Delta_2, x : A, y : \Box B; \Gamma \quad R \vdash \Delta_3, y : \Box B; \Gamma}{P \vdash \Delta_1, x : \bar{A}; \Gamma \quad \text{shareL } y \{Q \parallel R\} \vdash \Delta_2, \Delta_3, x : A, y : \Box B; \Gamma} \\
\equiv \\
\frac{P \mid x \mid \text{shareL } y \{Q \parallel R\} \vdash \Delta_1, \Delta_2, \Delta_3, y : \Box B; \Gamma}{P \vdash \Delta_1, x : \bar{A}; \Gamma \quad Q \vdash \Delta_2, x : A, y : \Box B; \Gamma} \\
\equiv \\
\frac{P \mid y \mid Q \vdash \Delta_1, \Delta_2, y : \Box B; \Gamma \quad R \vdash \Delta_3, y : \Box B; \Gamma}{\text{shareL } x \{P \mid y \mid Q \parallel R\} \vdash \Delta_1, \Delta_2, \Delta_3, y : \Box B; \Gamma} \text{ [C-CSHL1]} \\
\\
\frac{R \vdash \Delta_2, y : \Box B; \Gamma \quad Q \vdash \Delta_3, y : \Box B, x : A; \Gamma}{P \vdash \Delta_1, x : \bar{A}; \Gamma \quad \text{shareL } y \{R \parallel Q\} \vdash \Delta_2, \Delta_3, y : \Box B, x : A; \Gamma} \\
\equiv \\
\frac{P \mid x \mid \text{shareL } y \{R \parallel Q\} \vdash \Delta_1, \Delta_2, \Delta_3, y : \Box B; \Gamma}{R \vdash \Delta_2, y : \Box B; \Gamma \quad P \vdash \Delta_1, x : \bar{A}; \Gamma \quad Q \vdash \Delta_3, y : \Box B, x : A; \Gamma} \text{ [C-CSHL2]} \\
\\
\frac{Q \vdash \Delta', x : \Box A; \Gamma \quad R \vdash \Delta''; \Gamma}{P \vdash \Delta, x : \Box A; \Gamma \quad Q \parallel R \vdash \Delta', x : \Box A, \Delta''; \Gamma} \\
\equiv \\
\frac{\text{share } x \{P \parallel (Q \parallel R)\} \vdash \Delta, \Delta', \Delta'', x : \Box A; \Gamma}{P \vdash \Delta, x : \Box A; \Gamma \quad Q \vdash \Delta', x : \Box A; \Gamma} \\
\equiv \\
\frac{\text{share } x \{P \parallel Q\} \vdash \Delta, \Delta', x : \Box A; \Gamma \quad R \vdash \Delta''; \Gamma}{(\text{share } x \{P \parallel Q\}) \parallel R \vdash \Delta, \Delta', x : \Box A, \Delta''; \Gamma} \text{ [C-ShM]} \\
\\
\frac{Q \vdash y : \bar{B}; \Gamma \quad R \vdash \Delta', x : \Box A; \Gamma, z : B}{P \vdash \Delta, x : \Box A; \Gamma \quad y.Q \mid !z \mid R \vdash \Delta', x : \Box A; \Gamma} \\
\equiv \\
\frac{\text{share } x \{P \parallel (y.Q \mid !z \mid R)\} \vdash \Delta, \Delta', x : \Box A; \Gamma}{P \vdash \Delta, x : \Box A; \Gamma} \\
\equiv \\
\frac{P \vdash \Delta, x : \Box A; \Gamma}{P \vdash \Delta, x : \Box A; \Gamma, z : B} \text{ [weak]} \\
\frac{R \vdash \Delta', x : \Box A; \Gamma, z : B}{\text{share } x \{P \parallel R\} \vdash \Delta, \Delta', x : \Box A; \Gamma, z : B} \text{ [C-ShC!]} \\
\frac{y.Q \mid !z \mid (\text{share } x \{P \parallel R\}) \vdash \Delta, \Delta', x : \Box A; \Gamma}{Q \vdash y : \bar{B}; \Gamma}
\end{array}$$

$$\begin{array}{c}
\frac{Q \vdash \Delta', x : \Box A, y : \Box B; \Gamma \quad R \vdash \Delta'', y : \Box B; \Gamma}{P \vdash \Delta, x : \Box A; \Gamma \quad \text{share } y \{Q \parallel R\} \vdash \Delta', x : \Box A, \Delta'', y : \Box B; \Gamma} \\
\frac{\text{share } x \{P \parallel \text{share } y \{Q \parallel R\}\} \vdash \Delta, \Delta', \Delta'', x : \Box A, y : \Box B; \Gamma}{\equiv} \\
\frac{P \vdash \Delta, x : \Box A; \Gamma \quad Q \vdash \Delta', x : \Box A, y : \Box B; \Gamma}{\text{share } x \{P \parallel Q\} \vdash \Delta, \Delta', x : \Box A, y : \Box B; \Gamma} \quad R \vdash \Delta'', y : \Box B; \Gamma \quad [\text{C-ShSh}] \\
\frac{\text{share } y \{\text{share } x \{P \parallel Q\} \parallel R\} \vdash \Delta, \Delta', x : \Box A, \Delta'', y : \Box B; \Gamma}{\equiv} \\
\frac{Q \vdash \Delta', x : \Box A, y : \Box B; \Gamma \quad R \vdash \Delta'', y : \Box B; \Gamma}{P \vdash \Delta, x : \Box A; \Gamma \quad \text{shareL } y \{Q \parallel R\} \vdash \Delta', x : \Box A, \Delta'', y : \Box B; \Gamma} \\
\frac{\text{share } x \{P \parallel \text{shareL } y \{Q \parallel R\}\} \vdash \Delta, \Delta', \Delta'', x : \Box A, y : \Box B; \Gamma}{\equiv} \\
\frac{P \vdash \Delta, x : \Box A; \Gamma \quad Q \vdash \Delta', x : \Box A, y : \Box B; \Gamma}{\text{share } x \{P \parallel Q\} \vdash \Delta, \Delta', x : \Box A, y : \Box B; \Gamma} \quad R \vdash \Delta'', y : \Box B; \Gamma \quad [\text{C-ShShL1}] \\
\frac{\text{shareL } y \{\text{share } x \{P \parallel Q\} \parallel R\} \vdash \Delta, \Delta', x : \Box A, \Delta'', y : \Box B; \Gamma}{\equiv} \\
\frac{Q \vdash \Delta', y : \Box B; \Gamma \quad R \vdash \Delta'', x : \Box A, y : \Box B; \Gamma}{P \vdash \Delta, x : \Box A; \Gamma \quad \text{shareL } y \{Q \parallel R\} \vdash \Delta', x : \Box A, \Delta'', y : \Box B; \Gamma} \\
\frac{\text{share } x \{P \parallel \text{shareL } y \{Q \parallel R\}\} \vdash \Delta, \Delta', \Delta'', x : \Box A, y : \Box B; \Gamma}{\equiv} \\
\frac{P \vdash \Delta, x : \Box A; \Gamma \quad R \vdash \Delta'', x : \Box A, y : \Box B; \Gamma}{\text{share } x \{P \parallel R\} \vdash \Delta, \Delta'', x : \Box A, y : \Box B; \Gamma} \quad Q \vdash \Delta', y : \Box B; \Gamma \quad [\text{C-ShShL2}] \\
\frac{\text{shareL } y \{Q \parallel \text{share } x \{P \parallel R\}\} \vdash \Delta, \Delta', \Delta'', x : \Box A, y : \Box B; \Gamma}{\equiv} \\
\frac{R \vdash \Delta'; \Gamma}{R \vdash \Delta'; \Gamma, x : \bar{A}} \quad [\text{weak}] \\
\frac{Q \vdash \Delta; \Gamma, x : \bar{A} \quad R \vdash \Delta'; \Gamma, x : \bar{A}}{P \vdash y : A; \Gamma \quad Q \parallel R \vdash \Delta, \Delta'; \Gamma, x : \bar{A}} \\
\frac{y.P \mid !x : A \mid (Q \parallel R) \vdash \Delta, \Delta'; \Gamma}{\equiv} \\
\frac{P \vdash y : A; \Gamma \quad Q \vdash \Delta; \Gamma, x : \bar{A}}{y.P \mid !x : A \mid Q \vdash \Delta; \Gamma} \quad R \vdash \Delta'; \Gamma \quad [\text{C-C!M}] \\
\frac{y.P \mid !x : A \mid Q \parallel R \vdash \Delta, \Delta'; \Gamma}{\equiv}
\end{array}$$

Fig. 17

$$\begin{array}{c}
\frac{Q \vdash w : B; \Gamma}{Q \vdash w : B; \Gamma, x : \bar{A}} \text{ [weak]} \quad R \vdash \Delta; \Gamma, x : \bar{A}, z : \bar{B}}{P \vdash y : A; \Gamma \quad \frac{w.Q \mid !z : B \mid R \vdash \Delta; \Gamma, x : \bar{A}}{y.P \mid !x : A \mid (w.Q \mid !z : B \mid R) \vdash \Delta; \Gamma}} \\
\equiv \\
\frac{P \vdash y : A; \Gamma}{P \vdash y : \bar{A}; \Gamma, z : \bar{B}} \text{ [weak]} \quad R \vdash \Delta; \Gamma, x : \bar{A}, z : \bar{B}}{Q \vdash w : B; \Gamma \quad \frac{y.P \mid !x : A \mid R \vdash \Delta; \Gamma, z : \bar{B}}{w.Q \mid !z : B \mid (y.P \mid !x : A \mid R) \vdash \Delta; \Gamma}} \text{ [C-C!C!]} \\
\equiv \\
\frac{R \vdash \Delta', z : \Box B; \Gamma}{R \vdash \Delta', z : \Box B; \Gamma, x : \bar{A}} \text{ [weak]} \quad Q \vdash \Delta, z : \Box B; \Gamma, x : \bar{A}}{P \vdash y : \bar{A}; \Gamma \quad \frac{\text{shareL } z \{Q \parallel R\} \vdash \Delta, \Delta', z : \Box B; \Gamma, x : \bar{A}}{y.P \mid !x : A \mid (\text{shareL } z \{Q \parallel R\}) \vdash \Delta, \Delta', z : \Box B; \Gamma}} \\
\equiv \\
\frac{P \vdash y : \bar{A}; \Gamma \quad Q \vdash \Delta, z : \Box B; \Gamma, x : \bar{A}}{y.P \mid !x : A \mid Q \vdash \Delta, z : \Box B; \Gamma} \quad R \vdash \Delta', z : \Box B; \Gamma \text{ [C-C!ShL1]}}{\text{shareL } z \{(y.P \mid !x : A \mid Q) \parallel R\} \vdash \Delta, \Delta', \Box B; \Gamma} \\
\equiv \\
\frac{Q \vdash \Delta, z : \Box B; \Gamma}{Q \vdash \Delta, z : \Box B; \Gamma, x : \bar{A}} \text{ [weak]} \quad R \vdash \Delta', z : \Box B; \Gamma, x : \bar{A}}{P \vdash y : \bar{A}; \Gamma \quad \frac{\text{shareL } z \{Q \parallel R\} \vdash \Delta, \Delta', z : \Box B; \Gamma, x : \bar{A}}{y.P \mid !x : A \mid (\text{shareL } z \{Q \parallel R\}) \vdash \Delta, \Delta', z : \Box B; \Gamma}} \\
\equiv \\
\frac{P \vdash y : \bar{A}; \Gamma \quad R \vdash \Delta', z : \Box B; \Gamma, x : \bar{A}}{y.P \mid !x : A \mid R \vdash \Delta', z : \Box B; \Gamma} \text{ [C-C!ShL2]}}{\text{shareL } z \{Q \parallel (y.P \mid !x : A \mid R)\} \vdash \Delta, \Delta', \Box B; \Gamma} \\
\equiv \\
\frac{P \vdash \Delta; \Gamma \quad Q \vdash \Delta', x : \Box A; \Gamma}{P \parallel Q \vdash \Delta, \Delta', x : \Box A; \Gamma} \quad R \vdash \Delta'', x : \Box A; \Gamma}{\text{shareL } x \{(P \parallel Q) \parallel R\} \vdash \Delta, \Delta', \Delta'', x : \Box A; \Gamma} \\
\equiv \\
\frac{Q \vdash \Delta', x : \Box A; \Gamma \quad R \vdash \Delta'', x : \Box A; \Gamma}{P \vdash \Delta; \Gamma \quad \text{shareL } x \{Q \parallel R\} \vdash \Delta', \Delta'', x : \Box A; \Gamma} \text{ [C-CShLM]}}{P \parallel (\text{shareL } x \{Q \parallel R\}) \vdash \Delta, \Delta', \Delta'', x : \Box A; \Gamma}
\end{array}$$

Fig. 18

$$\begin{array}{c}
\frac{P \vdash \Delta_1, y : \boxed{B}, x : \boxed{A}; \Gamma \quad R \vdash \Delta_2, y : \boxed{B}; \Gamma}{\text{shareL } y \{P \parallel R\} \vdash \Delta_1, \Delta_2, y : \boxed{B}, x : \boxed{A}; \Gamma} \quad Q \vdash \Delta_3, x : \boxed{A}; \Gamma \\
\frac{\text{shareL } x \{\text{shareL } y \{P \parallel R\} \parallel Q\} \vdash \Delta_1, \Delta_2, \Delta_3, y : \boxed{B}, x : \boxed{A}; \Gamma}{\equiv} \\
\frac{P \vdash \Delta_1, y : \boxed{B}, x : \boxed{A}; \Gamma \quad Q \vdash \Delta_3, x : \boxed{A}; \Gamma}{\text{shareL } x \{P \parallel Q\} \vdash \Delta_1, \Delta_3, y : \boxed{B}, x : \boxed{A}; \Gamma} \quad R \vdash \Delta_2, y : \boxed{B}; \Gamma \text{ [C-ShLShL1]} \\
\frac{\text{shareL } y \{\text{shareL } x \{P \parallel Q\} \parallel R\} \vdash \Delta_1, \Delta_2, \Delta_3, y : \boxed{B}, x : \boxed{A}; \Gamma}{\equiv} \\
\frac{R \vdash \Delta_1, y : \boxed{B}; \Gamma \quad P \vdash \Delta_2, y : \boxed{B}, x : \boxed{A}; \Gamma}{\text{shareL } y \{R \parallel P\} \vdash \Delta_1, \Delta_2, y : \boxed{B}, x : \boxed{A}; \Gamma} \quad Q \vdash \Delta_3, x : \boxed{A}; \Gamma \\
\frac{\text{shareL } x \{\text{shareL } y \{R \parallel P\} \parallel Q\} \vdash \Delta_1, \Delta_2, \Delta_3, y : \boxed{A}, x : \boxed{A}; \Gamma}{\equiv} \\
\frac{P \vdash \Delta_2, y : \boxed{B}, x : \boxed{A}; \Gamma \quad Q \vdash \Delta_3, x : \boxed{A}; \Gamma}{R \vdash \Delta_1, y : \boxed{B}; \Gamma \quad \text{shareL } x \{P \parallel Q\} \vdash \Delta, \Delta_3, x : \boxed{A}, y : \boxed{B}} \text{ [C-ShLShL2]} \\
\frac{\text{shareL } y \{R \parallel \text{shareL } x \{P \parallel Q\}\} \vdash \Delta_1, \Delta_2, \Delta_3, y : \boxed{B}, x : \boxed{A}; \Gamma}{\equiv} \\
\frac{P \vdash \Delta; \Gamma \quad Q \vdash \Delta'; \Gamma}{P \parallel Q \vdash \Delta, \Delta'; \Gamma} \quad \frac{Q \vdash \Delta'; \Gamma \quad R \vdash \Delta''; \Gamma}{Q \parallel R \vdash \Delta', \Delta''; \Gamma} \text{ [C-MM]} \\
\frac{P \parallel Q \parallel R \vdash \Delta, \Delta', \Delta''; \Gamma}{P \parallel (Q \parallel R) \vdash \Delta, \Delta', \Delta''; \Gamma} \\
\frac{P \vdash \Delta; \Gamma \quad Q \vdash \Delta; \Gamma}{P + Q \vdash \Delta; \Gamma} \quad \frac{R \vdash \Delta; \Gamma}{R \vdash \Delta; \Gamma} \equiv \frac{P \vdash \Delta; \Gamma}{P \vdash \Delta; \Gamma} \quad \frac{Q \vdash \Delta; \Gamma \quad R \vdash \Delta; \Gamma}{Q + R \vdash \Delta; \Gamma} \text{ [C-SmSm]} \\
\frac{P + (Q + R) \vdash \Delta; \Gamma}{(P + Q) + R \vdash \Delta; \Gamma} \\
\frac{Q \vdash \Delta; \Gamma, x : A \quad R \vdash \Delta'; \Gamma, x : A}{Q \parallel R \vdash \Delta, \Delta'; \Gamma, x : A} \\
\frac{y.P \mid!x : \bar{A} \mid (Q \parallel R) \vdash \Delta, \Delta'; \Gamma}{\equiv} \\
\frac{P \vdash y : \bar{A}; \Gamma \quad Q \vdash \Delta; \Gamma, x : A}{y.P \mid!x : \bar{A} \mid Q \vdash \Delta; \Gamma} \quad \frac{P \vdash y : \bar{A}; \Gamma \quad R \vdash \Delta'; \Gamma, x : A}{y.P \mid!x : \bar{A} \mid R \vdash \Delta'; \Gamma} \text{ [D-C!M]} \\
\frac{y.P \mid!x \mid Q \parallel (y.P \mid!x \mid R) \vdash \Delta, \Delta'; \Gamma}{(y.P \mid!x \mid Q) \parallel (y.P \mid!x \mid R) \vdash \Delta, \Delta'; \Gamma} \\
\frac{Q \vdash \Delta, z : \bar{B}; \Gamma, x : A \quad R \vdash \Delta', z : B; \Gamma, x : A}{Q \mid z : \bar{B} \mid R \vdash \Delta, \Delta'; \Gamma, x : A} \\
\frac{P \vdash y : \bar{A}; \Gamma}{y.P \mid!x : \bar{A} \mid (Q \mid z : \bar{B} \mid R) \vdash \Delta, \Delta'; \Gamma} \\
\frac{y.P \mid!x : \bar{A} \mid (Q \mid z : \bar{B} \mid R) \vdash \Delta, \Delta'; \Gamma}{\equiv} \\
\frac{P \vdash y : \bar{A}; \Gamma \quad Q \vdash \Delta, z : \bar{B}; \Gamma, x : A}{y.P \mid!x : \bar{A} \mid Q \vdash \Delta, z : \bar{B}; \Gamma} \quad \frac{P \vdash y : \bar{A}; \Gamma \quad R \vdash \Delta', z : B; \Gamma, x : A}{y.P \mid!x : \bar{A} \mid R \vdash \Delta', z : B; \Gamma} \text{ [D-C!C]} \\
\frac{y.P \mid!x \mid Q \mid z : \bar{B} \mid (y.P \mid!x \mid R) \vdash \Delta, \Delta'; \Gamma}{(y.P \mid!x \mid Q) \mid z : \bar{B} \mid (y.P \mid!x \mid R) \vdash \Delta, \Delta'; \Gamma}
\end{array}$$

Fig. 19

$$\begin{array}{c}
\frac{Q \vdash w : \bar{B}; \Gamma, x : A \quad R \vdash \Delta; \Gamma, x : A, z : B}{P \vdash y : \bar{A}; \Gamma \quad w.Q \mid !z : \bar{B} \mid R \vdash \Delta, \Delta'; \Gamma, x : A} \\
\frac{}{y.P \mid !x : \bar{A} \mid (w.Q \mid !z \mid R) \vdash \Delta, \Delta'; \Gamma} \\
\equiv \\
\frac{P \vdash y : \bar{A}; \Gamma \quad Q \vdash w : \bar{B}; \Gamma, x : A \quad P \vdash y : \bar{A}; \Gamma \quad R \vdash \Delta; \Gamma, x : A, z : B}{y.P \mid !x : \bar{A} \mid Q \vdash w : \bar{B}; \Gamma \quad y.P \mid !x : \bar{A} \mid R \vdash \Delta; \Gamma, z : B} \text{ [D-C!C!]} \\
\frac{}{w.(y.P \mid !x : \bar{A} \mid Q) \mid !z : \bar{B} \mid (y.P \mid !x : \bar{A} \mid R) \vdash \Delta, \Delta'; \Gamma} \\
\frac{Q \vdash \Delta, z : \Box B; \Gamma, x : A \quad R \vdash \Delta', z : \Box B; \Gamma, x : A}{P \vdash y : \bar{A}; \Gamma \quad \text{share } z \{Q \parallel R\} \vdash \Delta, \Delta', z : \Box B; \Gamma, x : A} \\
\frac{}{y.P \mid !x : \bar{A} \mid (\text{share } z \{Q \parallel R\}) \vdash \Delta, \Delta', z : \Box B; \Gamma} \\
\equiv \\
\frac{P \vdash y : \bar{A}; \Gamma \quad Q \vdash \Delta, z : \Box B; \Gamma, x : A \quad P \vdash y : \bar{A}; \Gamma \quad R \vdash \Delta', z : \Box B; \Gamma, x : A}{y.P \mid !x : \bar{A} \mid Q \vdash \Delta, z : \Box B; \Gamma \quad y.P \mid !x : \bar{A} \mid R \vdash \Delta', z : \Box B; \Gamma} \text{ [D-C!Sh]} \\
\frac{}{\text{share } z \{(y.P \mid !x : \bar{A} \mid Q) \parallel (y.P \mid !x : \bar{A} \mid R)\} \vdash \Delta, \Delta', z : \Box B; \Gamma} \\
\frac{Q \vdash \Delta, z : \Box B; \Gamma, x : A \quad R \vdash \Delta', z : \Box B; \Gamma, x : A}{P \vdash y : \bar{A}; \Gamma \quad \text{shareL } z \{Q \parallel R\} \vdash \Delta, \Delta', z : \Box B; \Gamma, x : A} \\
\frac{}{y.P \mid !x : \bar{A} \mid (\text{shareL } z \{Q \parallel R\}) \vdash \Delta, \Delta', z : \Box B; \Gamma} \\
\equiv \\
\frac{P \vdash y : \bar{A}; \Gamma \quad Q \vdash \Delta, z : \Box B; \Gamma, x : A \quad P \vdash y : \bar{A}; \Gamma \quad R \vdash \Delta', z : \Box B; \Gamma, x : A}{y.P \mid !x : \bar{A} \mid Q \vdash \Delta, z : \Box B; \Gamma \quad y.P \mid !x : \bar{A} \mid R \vdash \Delta', z : \Box B; \Gamma} \text{ [D-C!ShL]} \\
\frac{}{\text{share } z \{(y.P \mid !x : \bar{A} \mid Q) \parallel (y.P \mid !x : \bar{A} \mid R)\} \vdash \Delta, \Delta', z : \Box B; \Gamma} \\
\frac{Q \vdash \Delta; \Gamma, x : A \quad R \vdash \Delta; \Gamma, x : A}{P \vdash y : \bar{A}; \Gamma \quad Q + R \vdash \Delta; \Gamma, x : A} \\
\frac{}{y.P \mid !x \mid (Q + R) \vdash \Delta; \Gamma} \\
\equiv \\
\frac{P \vdash y : \bar{A}; \Gamma \quad Q \vdash \Delta; \Gamma, x : A \quad P \vdash y : \bar{A}; \Gamma \quad R \vdash \Delta; \Gamma, x : A}{y.P \mid !x \mid Q \vdash \Delta; \Gamma \quad y.P \mid !x \mid R \vdash \Delta \Gamma} \text{ [D-C!Sm]} \\
\frac{}{(y.P \mid !x \mid Q) + (y.P \mid !x \mid R) \vdash \Delta; \Gamma} \\
\frac{Q \vdash \Delta'; \Gamma \quad R \vdash \Delta'; \Gamma}{P \vdash \Delta; \Gamma \quad Q + R \vdash \Delta'; \Gamma} \\
\frac{}{P \parallel (Q + R) \vdash \Delta, \Delta'; \Gamma} \\
\equiv \\
\frac{P \vdash \Delta; \Gamma \quad Q \vdash \Delta'; \Gamma \quad P \vdash \Delta; \Gamma \quad R \vdash \Delta'; \Gamma}{P \parallel Q \vdash \Delta, \Delta'; \Gamma \quad P \parallel R \vdash \Delta, \Delta'; \Gamma} \text{ [D-MSm]} \\
\frac{}{(P \parallel Q) + (P \parallel R) \vdash \Delta, \Delta'; \Gamma}
\end{array}$$

Fig. 20

$$\begin{array}{c}
\frac{P \vdash \Delta, x : \bar{A}; \Gamma \quad \frac{Q \vdash \Delta', x : A; \Gamma \quad R \vdash \Delta', x : A; \Gamma}{Q + R \vdash \Delta', x : A; \Gamma}}{P \mid x \mid (Q + R) \vdash \Delta, \Delta'; \Gamma} \\
\equiv \\
\frac{P \vdash \Delta, x : \bar{A}; \Gamma \quad Q \vdash \Delta', x : A; \Gamma \quad \frac{P \vdash \Delta, x : \bar{A}; \Gamma \quad R \vdash \Delta', x : A; \Gamma}{P \mid x \mid Q \vdash \Delta, \Delta'; \Gamma}}{\frac{P \mid x \mid Q \vdash \Delta, \Delta'; \Gamma \quad P \mid x \mid R \vdash \Delta, \Delta'; \Gamma}{(P \mid x \mid Q) + (P \mid x \mid R) \vdash \Delta, \Delta'; \Gamma}} \text{ [D-CSm]} \\
\\
\frac{P \vdash \Delta, x : \boxplus A; \Gamma \quad \frac{Q \vdash \Delta', x : \boxminus A; \Gamma \quad R \vdash \Delta', x : \boxminus A; \Gamma}{Q + R \vdash \Delta', x : \boxminus A; \Gamma}}{\text{share } x \{P \parallel Q + R\} \vdash \Delta, \Delta', x : \boxplus A; \Gamma} \\
\equiv \\
\frac{P \vdash \Delta, x : \boxplus A; \Gamma \quad Q \vdash \Delta', x : \boxminus A; \Gamma \quad \frac{P \vdash \Delta, x : \boxplus A; \Gamma \quad R \vdash \Delta', x : \boxminus A; \Gamma}{\text{share } x \{P \parallel R\} \vdash \Delta, \Delta', x : \boxplus A; \Gamma}}{\frac{\text{share } x \{P \parallel Q\} \vdash \Delta, \Delta', x : \boxplus A; \Gamma \quad \text{share } x \{P \parallel R\} \vdash \Delta, \Delta', x : \boxplus A; \Gamma}{\text{share } x \{P \parallel Q\} + \text{share } x \{P \parallel R\} \vdash \Delta, \Delta', x : \boxplus A, \Delta''; \Gamma}} \text{ [D-ShSm]} \\
\\
\frac{P \vdash \Delta, x : \boxtimes A; \Gamma \quad Q \vdash \Delta, x : \boxtimes A; \Gamma}{P + Q \vdash \Delta, x : \boxtimes A; \Gamma} \quad R \vdash \Delta', x : \boxplus A; \Gamma \\
\equiv \\
\frac{\text{shareL } x \{P + Q \parallel R\} \vdash \Delta, \Delta', x : \boxtimes A; \Gamma \quad R \vdash \Delta', x : \boxplus A; \Gamma}{\text{shareL } x \{P \parallel R\} \vdash \Delta, \Delta', x : \boxtimes A; \Gamma \quad \frac{Q \vdash \Delta, x : \boxtimes A; \Gamma \quad R \vdash \Delta', x : \boxplus A; \Gamma}{\text{shareL } x \{Q \parallel R\} \vdash \Delta, \Delta', x : \boxtimes A; \Gamma}} \text{ [D-ShLSm1]} \\
\\
\frac{P \vdash \Delta, x : \boxtimes A; \Gamma \quad \frac{Q \vdash \Delta', x : \boxplus A; \Gamma \quad R \vdash \Delta', x : \boxplus A; \Gamma}{Q + R \vdash \Delta', x : \boxplus A; \Gamma}}{\text{shareL } x \{P \parallel (Q + R)\} \vdash \Delta, \Delta', x : \boxtimes A; \Gamma} \\
\equiv \\
\frac{P \vdash \Delta, x : \boxtimes A; \Gamma \quad Q \vdash \Delta', x : \boxplus A; \Gamma \quad \frac{P \vdash \Delta, x : \boxtimes A; \Gamma \quad R \vdash \Delta', x : \boxplus A; \Gamma}{\text{shareL } x \{P \parallel R\} \vdash \Delta, \Delta', x : \boxtimes A; \Gamma}}{\frac{\text{shareL } x \{P \parallel Q\} \vdash \Delta, \Delta', x : \boxtimes A; \Gamma \quad \text{shareL } x \{P \parallel R\} \vdash \Delta, \Delta', x : \boxtimes A; \Gamma}{(\text{shareL } x \{P \parallel Q\}) + (\text{shareL } x \{P \parallel R\}) \vdash \Delta, \Delta', x : \boxtimes A; \Gamma}} \text{ [D-ShLSm2]}
\end{array}$$

Fig. 21

$$\begin{array}{c}
\frac{P \vdash \Delta; \Gamma}{\text{free } x; P \vdash \Delta, x : \Box A; \Gamma} \quad \frac{Q \vdash \Delta'; \Gamma}{\text{free } x; Q \vdash \Delta', x : \Box A; \Gamma} \equiv \frac{P \vdash \Delta; \Gamma \quad Q \vdash \Delta'; \Gamma}{P \parallel Q \vdash \Delta, \Delta'; \Gamma} \quad [\text{FF}] \\
\frac{}{\text{share } x \{ \text{free } x; P \parallel \text{free } x; Q \} \vdash \Delta, \Delta', x : \Box A; \Gamma} \quad \frac{}{\text{free } x; (P \parallel Q) \vdash \Delta, \Delta', x : \Box A; \Gamma} \\
\\
\frac{P \vdash \Delta, y : ?A, x : \Box A; \Gamma}{\text{read } x(y); P \vdash \Delta, x : \Box A; \Gamma} \quad \frac{Q \vdash \Delta', x : \Box A; \Gamma}{Q \vdash \Delta', x : \Box A; \Gamma} \supset \frac{P \vdash \Delta, y : ?A, x : \Box A; \Gamma \quad Q \vdash \Delta', x : \Box A; \Gamma}{\text{share } x \{ P \parallel Q \} \vdash \Delta, \Delta', y : ?A, x : \Box A; \Gamma} \\
\frac{}{\text{share } x \{ \text{read } x(y); P \parallel Q \} \vdash \Delta, \Delta', x : \Box A; \Gamma} \quad \frac{}{\text{read } x(y); \text{share } x \{ P \parallel Q \} \vdash \Delta, \Delta', x : \Box A; \Gamma} \\
\\
\frac{P \vdash y : !\bar{A}; \Gamma \quad Q \vdash \Delta, x : \Box A; \Gamma}{\text{wrt } x(y.P); Q \vdash \Delta, x : \Box A; \Gamma} \quad \frac{}{R \vdash \Delta', x : \Box A; \Gamma} \\
\frac{}{\text{share } x \{ \text{wrt } x(y.P); Q \parallel R \} \vdash \Delta, \Delta', x : \Box A; \Gamma} \\
\supset \\
\frac{Q \vdash \Delta, x : \Box A; \Gamma \quad R \vdash \Delta', x : \Box A; \Gamma}{\text{share } x \{ Q \parallel R \} \vdash \Delta, \Delta', x : \Box A; \Gamma} \\
\frac{P \vdash y : !\bar{A}; \Gamma \quad \text{share } x \{ Q \parallel R \} \vdash \Delta, \Delta', x : \Box A; \Gamma}{\text{wrt } x(y.P); \text{share } x \{ Q \parallel R \} \vdash \Delta, \Delta', x : \Box A; \Gamma} \\
\\
\frac{P \vdash \Delta, y : ?A, x : \Box A; \Gamma}{\text{read } x(y); P \vdash \Delta, x : \Box A; \Gamma} \quad \frac{Q \vdash \Delta', x : \Box A; \Gamma}{Q \vdash \Delta', x : \Box A; \Gamma} \equiv \frac{P \vdash \Delta, y : ?A, x : \Box A; \Gamma \quad Q \vdash \Delta', x : \Box A; \Gamma}{\text{shareL } x \{ P \parallel Q \} \vdash \Delta, \Delta', y : ?A, x : \Box A; \Gamma} \\
\frac{}{\text{shareL } x \{ \text{read } x(y); P \parallel Q \} \vdash \Delta, \Delta', x : \Box A; \Gamma} \quad \frac{}{\text{read } x(y); \text{share } x \{ P \parallel Q \} \vdash \Delta, \Delta', x : \Box A; \Gamma} \\
\\
\frac{P \vdash y : !\bar{A}; \Gamma \quad Q \vdash \Delta, x : \Box A; \Gamma}{\text{wrt } x(y.P); Q \vdash \Delta, x : \Box A; \Gamma} \quad \frac{}{R \vdash \Delta', x : \Box A; \Gamma} \\
\frac{}{\text{shareL } x \{ \text{wrt } x(y.P); Q \parallel R \} \vdash \Delta, \Delta', x : \Box A; \Gamma} \\
\equiv \\
\frac{Q \vdash \Delta, x : \Box A; \Gamma \quad R \vdash \Delta', x : \Box A; \Gamma}{\text{shareL } x \{ Q \parallel R \} \vdash \Delta, \Delta', x : \Box A; \Gamma} \\
\frac{P \vdash y : !\bar{A}; \Gamma \quad \text{shareL } x \{ Q \parallel R \} \vdash \Delta, \Delta', x : \Box A; \Gamma}{\text{wrt } x(y.P); \text{shareL } x \{ Q \parallel R \} \vdash \Delta, \Delta', x : \Box A; \Gamma} \\
\\
\frac{P \vdash \Delta, x : \Box A; \Gamma}{\text{lock } x; P \vdash \Delta, x : \Box A; \Gamma} \quad \frac{Q \vdash \Delta', x : \Box A; \Gamma}{Q \vdash \Delta', x : \Box A; \Gamma} \supset \frac{P \vdash \Delta, x : \Box A; \Gamma \quad Q \vdash \Delta', x : \Box A; \Gamma}{\text{shareL } x \{ P \parallel Q \} \vdash \Delta, \Delta', x : \Box A; \Gamma} \\
\frac{}{\text{share } x \{ \text{lock } x; P \parallel Q \} \vdash \Delta, \Delta', \Box A; \Gamma} \quad \frac{}{\text{lock } x; \text{shareL } x \{ P \parallel Q \} \vdash \Delta, \Delta', x : \Box A; \Gamma} \\
\\
\frac{P \vdash \Delta, \Box A; \Gamma}{\text{unlock } x; P \vdash \Delta, \Box A; \Gamma} \quad \frac{Q \vdash \Delta', \Box A; \Gamma}{Q \vdash \Delta', \Box A; \Gamma} \equiv \frac{P \vdash \Delta, \Box A; \Gamma \quad Q \vdash \Delta', x : \Box A; \Gamma}{\text{share } x \{ P \parallel Q \} \vdash \Delta, \Delta', x : \Box A; \Gamma} \\
\frac{}{\text{shareL } x \{ \text{unlock } x; P \parallel Q \} \vdash \Delta, \Delta', \Box A; \Gamma} \quad \frac{}{\text{unlock } x; \text{share } x \{ P \parallel Q \} \vdash \Delta, \Delta', x : \Box A; \Gamma}
\end{array}$$

(*) In some cases of this figure (where we use the implication symbol \supset instead of \equiv) we are showing that commuting an action with a share operator is type-preserving. They are not, however, conversions of our language. Nevertheless, those kind of commutations are the building blocks of the interleaving conversions [FA], [FL], [AA], [LA], [LL] and [leftA].

Fig. 22

$$\frac{P \vdash \Delta, x : \boxtimes A; \Gamma \quad Q \vdash \Delta', x : \boxplus A; \Gamma}{\text{shareL } x \{P \parallel Q\} \vdash \Delta, \Delta', x : \boxtimes A; \Gamma} \equiv \frac{Q \vdash \Delta', x : \boxplus A; \Gamma \quad P \vdash \Delta, x : \boxtimes A; \Gamma}{\text{shareR } x \{Q \parallel P\} \vdash \Delta', \Delta, x : \boxtimes A; \Gamma} \text{ [Symm]}$$

$$\frac{P \vdash \Delta; \Gamma \quad \mathbf{0} \vdash \emptyset; \Gamma}{P \parallel \mathbf{0} \vdash \Delta; \Gamma} \equiv P \vdash \Delta; \Gamma \text{ [0M]}$$

$$\frac{\mathbf{0} \vdash \emptyset; \Gamma \quad \mathbf{0} \vdash \emptyset; \Gamma}{\mathbf{0} + \mathbf{0} \vdash \emptyset; \Gamma} \equiv \mathbf{0} \vdash \emptyset; \Gamma \text{ [0Sm]}$$

Fig. 23

$$\frac{\text{fwd } x \ y \vdash x : A, y : \bar{A}; \Gamma \quad P \vdash \Delta, y : A; \Gamma}{\text{fwd } x \ y \ |y| \ P \vdash x : A, \Delta; \Gamma} \rightarrow \{x/y\}P \vdash \Delta, x : A; \Gamma \text{ [fwd]}$$

$$\frac{\frac{}{\text{close } x \vdash x : \mathbf{1}; \Gamma} \quad \frac{P \vdash \Delta; \Gamma}{\text{wait } x; P \vdash \Delta, x : \perp; \Gamma}}{\text{close } x \ |x| \ \text{wait } x; P \vdash \Delta; \Gamma} \rightarrow P \vdash \Delta; \Gamma \text{ [1}\perp\text{]}$$

$$\frac{\frac{P \vdash \Delta, y : \bar{A}; \Gamma \quad Q \vdash \Delta', x : \bar{B}; \Gamma}{\text{send } x(y.P); Q \vdash \Delta, \Delta', x : \bar{A} \otimes \bar{B}; \Gamma} \quad \frac{R \vdash \Delta'', z : A, x : B; \Gamma}{\text{recv } x(z); R \vdash \Delta'', x : A \wp B; \Gamma}}{\text{send } x(y.P); Q \ |x| \ \text{recv } x(z); R \vdash \Delta, \Delta', \Delta''; \Gamma} \rightarrow$$

$$\frac{Q \vdash \Delta', x : \bar{B}; \Gamma \quad \frac{P \vdash \Delta, y : \bar{A}; \Gamma \quad \{y/z\}R \vdash \Delta'', y : A, x : B; \Gamma}{P \ |y| \ \{y/z\}R \vdash \Delta, \Delta'', x : B; \Gamma} \text{ [}\otimes\wp\text{]}}{Q \ |x| \ (P \ |y| \ \{y/z\}R) \vdash \Delta', \Delta, \Delta''; \Gamma}$$

$$\frac{\frac{P \vdash \Delta, x : \bar{A}; \Gamma \quad Q \vdash \Delta, x : \bar{B}; \Gamma}{\text{case } x \ \{\text{inl} : P \ \text{inr} : Q\} \vdash \Delta, x : \bar{A} \& \bar{B}; \Gamma} \quad \frac{R \vdash \Delta', x : A; \Gamma}{x.\text{inl}; R \vdash \Delta', x : A \otimes B; \Gamma}}{\text{case } x \ \{\text{inl} : P \ \text{inr} : Q\} \ |x| \ x.\text{inl}; R \vdash \Delta, \Delta'; \Gamma} \rightarrow$$

$$\frac{P \vdash \Delta, x : \bar{A}; \Gamma \quad R \vdash \Delta', x : A; \Gamma \text{ [}\&\oplus_l\text{]}}{P \ |x| \ R \vdash \Delta, \Delta'; \Gamma}$$

$$\frac{\frac{P \vdash \Delta, x : \bar{A}; \Gamma \quad Q \vdash \Delta, x : \bar{B}; \Gamma}{\text{case } x \ \{\text{inl} : P \ \text{inr} : Q\} \vdash \Delta, x : \bar{A} \& \bar{B}; \Gamma} \quad \frac{R \vdash \Delta', x : B; \Gamma}{x.\text{inr}; R \vdash \Delta', x : A \otimes B; \Gamma}}{\text{case } x \ \{\text{inl} : P \ \text{inr} : Q\} \ |x| \ x.\text{inr}; R \vdash \Delta, \Delta'; \Gamma} \rightarrow$$

$$\frac{Q \vdash \Delta, x : \bar{B}; \Gamma \quad R \vdash \Delta', x : B; \Gamma \text{ [}\&\oplus_r\text{]}}{Q \ |x| \ R \vdash \Delta, \Delta'; \Gamma}$$

$$\frac{\frac{P \vdash y : \bar{A}; \Gamma}{!x(y); P \vdash x : !\bar{A}; \Gamma} \quad \frac{Q \vdash \Delta; \Gamma, x : A}{?x; Q \vdash \Delta, x : ?A; \Gamma}}{!x(y); P \ |x| \ ?x; Q \vdash \Delta; \Gamma} \rightarrow$$

$$\frac{P \vdash y : \bar{A}; \Gamma \quad Q \vdash \Delta; \Gamma, x : A \text{ [!?]}}{y.P \ |!x| \ Q \vdash \Delta; \Gamma}$$

Fig. 24

$$\frac{P \vdash y : \bar{A}; \Gamma \quad \frac{Q \vdash \Delta, z : A; \Gamma, x : A}{\text{call } x(z); Q \vdash \Delta, \Gamma, x : A}}{y.P \text{ |!x| call } x(z); Q \vdash \Delta; \Gamma}$$

→

$$\frac{\{z/y\}P \vdash z : \bar{A}; \Gamma \quad \frac{P \vdash y : \bar{A}; \Gamma \quad Q \vdash \Delta, z : A; \Gamma, x : A}{y.P \text{ |!x| } Q \vdash \Delta, z : A; \Gamma}}{\{z/y\}P \text{ |z| } (y.P \text{ |!x| } Q) \vdash \Delta; \Gamma} \text{ [call]}$$

$$\frac{P \vdash \Delta, x : \{A/X\}\bar{B}; \Gamma \quad \frac{Q \vdash \Delta', x : B; \Gamma}{\text{recv } x(X); Q \vdash \Delta', x : \forall X.B; \Gamma}}{\text{send } x A; P \vdash \Delta, x : \exists X.\bar{B}; \Gamma \quad \text{recv } x(X); Q \vdash \Delta, \Delta'; \Gamma}$$

→

$$\frac{P \vdash \Delta, x : \{A/X\}\bar{B}; \Gamma \quad \{A/X\}Q \vdash \Delta', x : \{A/X\}B; \Gamma}{P \text{ |x| } \{A/X\}Q \vdash \Delta, \Delta'; \Gamma} [\exists\forall]$$

$$\frac{P \vdash y : \bar{A}; \Gamma \quad \frac{Q \vdash \Delta; \Gamma}{\text{free } x; Q \vdash \Delta, x : \Box A; \Gamma}}{\text{cell } x(y.P) \vdash x : \Box \bar{A}; \Gamma \quad \text{free } x; Q \vdash \Delta, x : \Box A; \Gamma}}{\text{cell } x(y.P) \text{ |x| free } x; Q \vdash \Delta; \Gamma}$$

→

$$Q \vdash \Delta; \Gamma \text{ [}\Box\Box\text{f]}$$

$$\frac{P \vdash y : \bar{A}; \Gamma \quad \frac{Q \vdash \Delta, z : ?A, x : \Box A; \Gamma}{\text{read } x(z); Q \vdash \Delta, x : \Box A; \Gamma}}{\text{cell } x(y.P) \vdash x : \Box \bar{A}; \Gamma \quad \text{read } x(z); Q \vdash \Delta, x : \Box A; \Gamma} \text{ [Tcell] [Tread] [Tcut]}$$

→

$$\frac{\{z/y\}P \vdash z : \bar{A}; \Gamma \quad \frac{P \vdash y : \bar{A}; \Gamma \quad \frac{Q \vdash \Delta, z : ?A, x : \Box A; \Gamma}{\text{cell } x(y.P) \vdash x : \Box \bar{A}; \Gamma} \text{ [Tcell]}}{\text{cell } x(y.P) \text{ |x| } Q \vdash \Delta, z : ?A; \Gamma} \text{ [Tcut] [}\Box\Box\text{r]}}{\{z/y\}P \text{ |z| } (\text{cell } x(y.P) \text{ |x| } Q) \vdash \Delta; \Gamma} \text{ [Tcut]}$$

$$\frac{P \vdash y : \bar{A}; \Gamma \quad \frac{Q \vdash z : \bar{A}; \Gamma \quad R \vdash \Delta, x : \Box A; \Gamma}{\text{wrt } x(z.Q); R \vdash \Delta, x : \Box A; \Gamma}}{\text{cell } x(y.P) \vdash x : \Box \bar{A}; \Gamma \quad \text{wrt } x(z.Q); R \vdash \Delta, x : \Box A; \Gamma}}{\text{cell } x(y.P) \text{ |x| wrt } x(z.Q); R \vdash \Delta; \Gamma}$$

→

$$\frac{Q \vdash z : \bar{A}; \Gamma \quad \frac{\text{cell } x(z.Q) \vdash x : \Box \bar{A}; \Gamma \quad R \vdash \Delta, x : \Box A; \Gamma}{\text{cell } x(z.Q) \text{ |x| } R \vdash \Delta; \Gamma} \text{ [}\Box\Box\text{w]}}{\text{cell } x(z.Q) \text{ |x| } R \vdash \Delta; \Gamma}$$

$$\begin{array}{c}
\frac{P \vdash y : !\bar{A}; \Gamma}{\text{cell } x(y.P) \vdash x : \boxed{\bar{A}}; \Gamma} \quad \frac{Q \vdash \Delta, x : \boxed{A}; \Gamma}{\text{lock } x; Q \vdash \Delta, x : \boxed{A}; \Gamma} \\
\hline
\text{cell } x(y.P) \mid x \mid \text{lock } x; Q \vdash \Delta; \Gamma \\
\rightarrow \\
\frac{P \vdash y : !\bar{A}; \Gamma}{\text{cell } x(y.P) \vdash x : \boxed{\bar{A}}; \Gamma} \quad Q \vdash \Delta, x : \boxed{A}; \Gamma \text{ [}\boxed{\square}\boxed{\square}\text{]} \\
\hline
\text{cell } x(y.P) \mid x \mid Q \vdash \Delta; \Gamma \quad \text{[}\boxed{\square}\boxed{\square}\text{u]} \\
\frac{P \vdash y : !\bar{A}; \Gamma}{\text{cell } x(y.P) \vdash x : \boxed{\bar{A}}; \Gamma} \quad \frac{Q \vdash \Delta, x : \boxed{A}; \Gamma}{\text{unlock } x; Q \vdash \Delta, x : \boxed{A}; \Gamma} \\
\hline
\text{cell } x(y.P) \mid x \mid \text{unlock } x; Q \vdash \Delta; \Gamma \\
\rightarrow \\
\frac{P \vdash y : !\bar{A}; \Gamma}{\text{cell } x(y.P) \vdash x : \boxed{\bar{A}}; \Gamma} \quad Q \vdash \Delta, x : \boxed{A}; \Gamma \\
\hline
\text{cell } x(y.P) \mid x \mid Q \vdash \Delta; \Gamma
\end{array}$$

Fig. 26